

---

Subject: Paris hardware problem part II  
Posted by [Tom Bruhl](#) on Tue, 24 Jul 2007 05:03:36 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

This is a multi-part message in MIME format.

-----=\_NextPart\_000\_013D\_01C7CD8E.7702C9B0

Content-Type: text/plain;

charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

Okay, I got a new rig fired up and booting properly with Paris with XP = Pro.

Here's what I've done so far:

- 1) I checked all SCSI cables and they turned out to be fine with one EDS card. I did some finessing of the pins alignment.
- 2) Checked all clock and interconnect cables with two cards. They all seem to be fine using the same A card attached to the 442 and four different B cards as Aaron suggested.
- 3) Tried four cards as card B and they seemed to work with no hardware attached to them. Seemed good.
- 4) I tried to scale back to just one card to try each as an A card with = the 442 attached but now Paris won't boot. Major badness.

It says:"An error occurred while reading the "Default Project" for new = project settings.

A new empty project will be created instead. There are not = enough resources

available." I click that away and it then says:

"Error in creating new project. There are not enough resources = available."

The readme says to try reinstalling the Paris drivers. I did but no = help there.

Two cards have given me the same results. I assume it's a driver = issue

or something else. I tried reducing the cache size in Paris.cfg but = that

didn't help either. I am seeing the Paris MIDI driver and a single = Scherzo.

When I click the faulty Paris project away it takes Windows with it = usually.



two cards.</FONT></DIV>

    They all seem to be =  
fine using=20

the same A card attached to the 442

&nbsp;&nbsp;&nbsp; and four different B = cards as=20

Aaron suggested.

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>

3) Tried four cards as card B and they = seemed to=20

work with no hardware</FONT></DIV>

&nbsp;&nbsp;&nbsp; attached to =  
them.&nbsp;&nbsp;&nbsp; Seemed=20

good.</FONT></DIV>

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>

<DIV><FONT face=3DArial size=3D2>4) I tried to scale back to just one = card to try=20

each as an A card with the

[illegible]

boot.  Major badness.

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>

<DIV><FONT face=3DArial size=3D2>It says:"An error occurred while =  
reading the=20

"Default Project" for new project settings.</FONT></DIV>

[illegible]

empty project will be created instead. There are not enough=20 resources</FONT></DIV>

[illegible][illegible]

I click that away and it then says:

<DIV><FONT face=3DArial size=3D2>&nbsp;&nbsp;"Error in creating new =  
project.&nbsp;&nbsp;=20

There are not enough resources available."

<DIV>&nbsp;</DIV>

<DIV><FONT face=3DArial size=3D2>&nbsp&nbsp The readme says to try =  
reinstalling=20

the Paris drivers.  I did but no help there.</FONT></DIV>

[illegible]

results.  I assume it's a driver issue</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>&nbsp;   or something else.&nbsp;   I =  
tried=20



increase the cache, disk I/O and buffers again.

128/80/8/med or something like that always worked for me.  
Change the settings with a text editor and restart Paris.

David.

Tom Bruhl wrote:

> Okay, I got a new rig fired up and booting properly with Paris with XP Pro.  
> Here's what I've done so far:  
>  
> 1) I checked all SCSI cables and they turned out to be fine with  
> one EDS card. I did some finessing of the pins alignment.  
>  
> 2) Checked all clock and interconnect cables with two cards.  
> They all seem to be fine using the same A card attached to the 442  
> and four different B cards as Aaron suggested.  
>  
> 3) Tried four cards as card B and they seemed to work with no hardware  
> attached to them. Seemed good.  
>  
> 4) I tried to scale back to just one card to try each as an A card with the  
> 442 attached but now Paris won't boot. Major badness.  
>  
> It says:"An error occurred while reading the "Default Project" for new  
> project settings.  
> A new empty project will be created instead. There are not  
> enough resources  
> available." I click that away and it then says:  
> "Error in creating new project. There are not enough resources  
> available."  
>  
> The readme says to try reinstalling the Paris drivers. I did but no  
> help there.  
> Two cards have given me the same results. I assume it's a driver issue  
> or something else. I tried reducing the cache size in Paris.cfg but that  
> didn't help either. I am seeing the Paris MIDI driver and a single  
> Scherzo.  
> When I click the faulty Paris project away it takes Windows with it  
> usually.  
>  
> I really don't have time for this crap (not that it's your fault) but  
> it's making me rethink  
> everything all of the sudden.  
>  
> Oh and since Paris hasn't been in front of Cubase feeding it ADAT WC I  
> can't open any

> of my Cubase projects. I get a white screen and can go nowhere. Great huh?  
> This is getting disgusting. Sorry for the attitude but I have no time,  
> tons of gigs and  
> studio work and I can't get either system to run.  
>  
> Anything at this point would be better than what I've got.  
> Thanks for whatever you can come up with,  
> Tom  
>  
>  
>  
> I choose Polesoft Lockspam to fight spam, and you?  
> <http://www.polesoft.com/refer.html>

---

---

Subject: Re: Paris hardware problem part II  
Posted by [JeffH](#) on Tue, 24 Jul 2007 05:07:42 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Tom,

It's 10pm pacific. I'll be up a couple hours so call me. DON't know if I can help much but I'll do what I can.

Jeff  
503-704-3701

Bruhl wrote:

> Okay, I got a new rig fired up and booting properly with Paris with XP Pro.  
> Here's what I've done so far:  
>  
> 1) I checked all SCSI cables and they turned out to be fine with  
> one EDS card. I did some finessing of the pins alignment.  
>  
> 2) Checked all clock and interconnect cables with two cards.  
> They all seem to be fine using the same A card attached to the 442  
> and four different B cards as Aaron suggested.  
>  
> 3) Tried four cards as card B and they seemed to work with no hardware  
> attached to them. Seemed good.  
>  
> 4) I tried to scale back to just one card to try each as an A card with the  
> 442 attached but now Paris won't boot. Major badness.  
>  
> It says:"An error occurred while reading the "Default Project" for new  
> project settings.  
> A new empty project will be created instead. There are not  
> enough resources

> available." I click that away and it then says:  
> "Error in creating new project. There are not enough resources  
> available."  
>  
> The readme says to try reinstalling the Paris drivers. I did but no  
> help there.  
> Two cards have given me the same results. I assume it's a driver issue  
> or something else. I tried reducing the cache size in Paris.cfg but that  
> didn't help either. I am seeing the Paris MIDI driver and a single  
> Scherzo.  
> When I click the faulty Paris project away it takes Windows with it  
> usually.  
>  
> I really don't have time for this crap (not that it's your fault) but  
> it's making me rethink  
> everything all of the sudden.  
>  
> Oh and since Paris hasn't been in front of Cubase feeding it ADAT WC I  
> can't open any  
> of my Cubase projects. I get a white screen and can go nowhere. Great huh?  
> This is getting disgusting. Sorry for the attitude but I have no time,  
> tons of gigs and  
> studio work and I can't get either system to run.  
>  
> Anything at this point would be better than what I've got.  
> Thanks for whatever you can come up with,  
> Tom  
>  
>  
>  
> I choose Polesoft Lockspam to fight spam, and you?  
> <http://www.polesoft.com/refer.html>

---

---

Subject: Re: Paris hardware problem part II  
Posted by [DJ](#) on Tue, 24 Jul 2007 05:21:10 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

This is a multi-part message in MIME format.

-----=\_NextPart\_000\_04E5\_01C7CD80.27BCA190  
Content-Type: text/plain;  
charset="iso-8859-1"  
Content-Transfer-Encoding: quoted-printable

Tom,

does your Default project have a bunch of patching in the virtual =

patchbay? I've had the same message happen when I disconnected a MEC and =  
I had previously had 4 x MECs with a default patch routing. with 3 x =  
MECs, it freaked out because the patch routing was for 4 x MECs and it =  
suddenly felt insecure and inadequate that it couldn't meet the needs of =  
it's routing config with fewer resources available., I guess.

"Tom Bruhl" <arpeggio@comcast.net> wrote in message =  
news:46a58928@linux...

Okay, I got a new rig fired up and booting properly with Paris with XP =  
Pro.

Here's what I've done so far:

- 1) I checked all SCSI cables and they turned out to be fine with  
one EDS card. I did some finessing of the pins alignment.
- 2) Checked all clock and interconnect cables with two cards.  
They all seem to be fine using the same A card attached to the 442  
and four different B cards as Aaron suggested.
- 3) Tried four cards as card B and they seemed to work with no hardware  
attached to them. Seemed good.
- 4) I tried to scale back to just one card to try each as an A card =  
with the  
442 attached but now Paris won't boot. Major badness.

It says:"An error occurred while reading the "Default Project" for new =  
project settings.

A new empty project will be created instead. There are not =  
enough resources

available." I click that away and it then =  
says:

"Error in creating new project. There are not enough resources =  
available."

The readme says to try reinstalling the Paris drivers. I did but =  
no help there.

Two cards have given me the same results. I assume it's a driver =  
issue

or something else. I tried reducing the cache size in Paris.cfg =  
but that

didn't help either. I am seeing the Paris MIDI driver and a single =  
Scherzo.

When I click the faulty Paris project away it takes Windows with it =  
usually.

I really don't have time for this crap (not that it's your fault) but =  
it's making me rethink  
everything all of the sudden.



Oh and since Paris hasn't been in front of Cubase feeding it ADAT WC I =  
can't open any

of my Cubase projects. I get a white screen and can go nowhere. =  
Great huh?

This is getting disgusting. Sorry for the attitude but I have no =  
time, tons of gigs and=20  
studio work and I can't get either system to run.

Anything at this point would be better than what I've got.

Thanks for whatever you can come up with,=20

Tom

I choose Polesoft Lockspam to fight spam, and you?

<http://www.polesoft.com/refer.html>

-----=\_NextPart\_000\_04E5\_01C7CD80.27BCA190

Content-Type: text/html;

charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">

<HTML><HEAD>

<META http-equiv=3DContent-Type content=3D"text/html; =  
charset=3Diso-8859-1">

<META content=3D"MSHTML 6.00.6000.16414" name=3DGENERATOR>

<STYLE></STYLE>

</HEAD>

<BODY bgColor=3D#ffffff>

<DIV><FONT face=3DArial size=3D2>Tom,</FONT></DIV>

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>

<DIV><FONT face=3DArial size=3D2>does your Default project have a bunch =  
of patching=20

in the virtual patchbay? I've had the same message happen when I =  
disconnected a=20

MEC and I had previously had 4 x MECs with a default patch routing. with =  
3 x=20

MECs, it freaked out because the patch routing was for 4 x MECs and it =  
suddenly=20

felt insecure and inadequate that it couldn't meet the needs of it's =  
routing=20

config with fewer resources available., I guess.</FONT></DIV>

<BLOCKQUOTE dir=3Dltr=20

style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =  
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">

<DIV>"Tom Bruhl" &lt;<A=20

href=3D"mailto:arpeggio@comcast.net">arpeggio@comcast.net</A>&gt; wrote =

<A href=3D"news:46a58928@linux">news:46a58928@linux</A>...</DIV>  
<DIV><FONT face=3DArial size=3D2>Okay, I got a new rig fired up and =  
booting=20

<DIV><FONT face=3DArial size=3D2>Here's what I've done so far:</FONT></DIV>

1) I checked all SCSI cables and they =  
turned out=20  
to be fine with</FONT></DIV>

finessing of the pins alignment.</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>2) Checked all clock and interconnect = cables with=20  
two cards.</FONT></DIV>

the same A card attached to the 442

Aaron suggested.

3) Tried four cards as card B and =  
they seemed to=20

     attached to =  
them.     Seemed=20  
good.</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>4) I tried to scale back to just one = card to try=20

[illegible]

"Default Project" for new project settings.</FONT></DIV>

[illegible]

resources</FONT></DIV>

[illegible]

better than what=20

I've got.</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>Thanks for whatever you can come up=20  
with,&nbsp;</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>Tom</FONT></DIV>

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>

<DIV><FONT size=3D2><BR><BR>I choose Polesoft Lockspam to fight spam, =  
and=20

you?<BR><A=20

=

href=3D"http://www.polesoft.com/refer.html">http://www.polesoft.com/refer=

..html</A>&nbsp;&nbsp;&nbsp;</FONT></DIV></BLOCKQUOTE ></BODY></HTML>

-----=\_NextPart\_000\_04E5\_01C7CD80.27BCA190--

---

Subject: Re: Paris hardware problem part II

Posted by [Tom Bruhl](#) on Tue, 24 Jul 2007 05:31:59 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

This is a multi-part message in MIME format.

-----=\_NextPart\_000\_0026\_01C7CD92.6DF52490

Content-Type: text/plain;

charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

David,

I'll try that first.

Jeff,

Thanks and I might take you up on the offer.

DJ,

It's the default project for a 442 sending to 4 channels

so I'll delete all the patches and save it if I can get into the=20  
project.

Thanks for the fast response you guys!

Tom

"Dave(EK Sound)" <audioguy\_editout\_@shaw.ca> wrote in message =  
news:46a58a03\$1@linux...

A fresh install zeros out your config file. Go in and=20  
increase the cache, disk I/O and buffers again.

128/80/8/med or something like that always worked for me.=20

Change the settings with a text editor and restart Paris.

David.

Tom Bruhl wrote:

> Okay, I got a new rig fired up and booting properly with Paris with =  
XP Pro.  
> Here's what I've done so far:  
> =20  
> 1) I checked all SCSI cables and they turned out to be fine with  
> one EDS card. I did some finessing of the pins alignment.  
> =20  
> 2) Checked all clock and interconnect cables with two cards.  
> They all seem to be fine using the same A card attached to the =  
442  
> and four different B cards as Aaron suggested.  
> =20  
> 3) Tried four cards as card B and they seemed to work with no =  
hardware  
> attached to them. Seemed good.  
> =20  
> 4) I tried to scale back to just one card to try each as an A card =  
with the  
> 442 attached but now Paris won't boot. Major badness.  
> =20  
> It says:"An error occurred while reading the "Default Project" for =  
new=20  
> project settings.  
> A new empty project will be created instead. There are =  
not=20  
> enough resources  
> available." I click that away and it then =  
says:  
> "Error in creating new project. There are not enough resources=20  
> available."  
> =20  
> The readme says to try reinstalling the Paris drivers. I did but =  
no=20  
> help there.  
> Two cards have given me the same results. I assume it's a driver =  
issue  
> or something else. I tried reducing the cache size in Paris.cfg =  
but that  
> didn't help either. I am seeing the Paris MIDI driver and a =  
single=20  
> Scherzo.  
> When I click the faulty Paris project away it takes Windows with =  
it=20  
> usually.

> =20  
> I really don't have time for this crap (not that it's your fault) =  
but=20  
> it's making me rethink  
> everything all of the sudden.  
> =20  
> Oh and since Paris hasn't been in front of Cubase feeding it ADAT WC =  
l=20  
> can't open any  
> of my Cubase projects. I get a white screen and can go nowhere. =  
Great huh?  
> This is getting disgusting. Sorry for the attitude but I have no =  
time,=20

> tons of gigs and=20  
> studio work and I can't get either system to run.  
> =20  
> Anything at this point would be better than what I've got.  
> Thanks for whatever you can come up with,=20  
> Tom  
> =20  
> =20  
> =20  
> I choose Polesoft Lockspam to fight spam, and you?  
> <http://www.polesoft.com/refer.html>

-----=\_NextPart\_000\_0026\_01C7CD92.6DF52490

Content-Type: text/html;  
charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.2800.1400" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT face=3DArial size=3D2>David,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>I'll try that first.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>Jeff,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Thanks and I might take you up on the=20
offer.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>DJ,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>It's the default project for a 442 =
sending to 4=20
channels</FONT></DIV>
```

[illegible]



[illegible]



Lockspam to fight spam, and you?<BR>&gt; <A=20  
=  
href=3D"http://www.polesoft.com/refer.html">http://www.polesoft.com/refer=  
..html</A></BLOCKQUOTE></BODY></HTML>

-----=\_NextPart\_000\_0026\_01C7CD92.6DF52490--

---

---

Subject: Re: Paris hardware problem part II  
Posted by [Tom Bruhl](#) on Tue, 24 Jul 2007 06:16:04 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

This is a multi-part message in MIME format.

-----=\_NextPart\_000\_0050\_01C7CD98.96A9EC30  
Content-Type: text/plain;  
charset="iso-8859-1"  
Content-Transfer-Encoding: quoted-printable

David,  
Your suggestion didn't totally make sense to me.  
Which part of the Config should be set to 8?  
I've never used a number that low there.  
I don't have the option to adjust to med either for some reason.  
Not sure what that's about.

I can tell you one thing though, the Midi drivers are not installed.  
I go to install them manually and it says no good. I am pointing it  
at the Paris folder with all the goods in it. Maybe I have faulty =  
drivers?

That would explain all the crap since after I reinstalled a week ago.  
I'll go look on the web for the drivers I guess.  
Tom

I choose Polesoft Lockspam to fight spam, and you?  
<http://www.polesoft.com/refer.html>  
-----=\_NextPart\_000\_0050\_01C7CD98.96A9EC30  
Content-Type: text/html;  
charset="iso-8859-1"  
Content-Transfer-Encoding: quoted-printable

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">  
<HTML><HEAD>

<META http-equiv=3DContent-Type content=3D"text/html; =  
charset=3Diso-8859-1">  
<META content=3D"MSHTML 6.00.2800.1400" name=3DGENERATOR>  
<STYLE></STYLE>  
</HEAD>  
<BODY bgColor=3D#ffffff>  
<DIV><FONT face=3DArial size=3D2>David,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Your suggestion didn't totally make =  
sense to=20  
me.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Which part of the Config should be set =  
to=20  
8?</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>I've never used a number that low=20  
there.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>I don't have the option to adjust to =  
med either for=20  
some reason.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Not sure what that's =  
about.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>I can tell you one thing though, the =  
Midi drivers=20  
are not installed.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>I go to install them manually and it =  
says no=20  
good.&nbsp;</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>at the Paris folder with all the goods =  
in it.&nbsp;</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Maybe I have faulty drivers?</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>That would explain all the crap since =  
after I=20  
reinstalled a week ago.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>I'll go look on the web for the drivers =  
I=20  
guess.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Tom</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT size=3D2><BR><BR>I choose Polesoft Lockspam to fight spam, =  
and=20  
you?<BR><A=20  
href=3D"http://www.polesoft.com/refer.html">http://www.polesoft.com/refer=  
..html</A>&nbsp;&nbsp;&nbsp;</FONT></DIV></BODY></HTML>

-----=\_NextPart\_000\_0050\_01C7CD98.96A9EC30--

---

Subject: Re: Paris hardware problem part II  
Posted by [Tom Bruhl](#) on Tue, 24 Jul 2007 06:39:36 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

This is a multi-part message in MIME format.

-----=\_NextPart\_000\_006C\_01C7CD9B.DFB6E9C0  
Content-Type: text/plain;  
charset="iso-8859-1"  
Content-Transfer-Encoding: quoted-printable

Okay everyone Jeff straightened me out right quick.

I had made a default project . . . As I now understand from Jeff, that's the final stage after all is totally well with hardware, plugins drivers etc.. Jeff had me remove the default project and all was better.

So back to my final testing of cards and I'll keep you informed on the next step with the Magma in a week or so.

I can at least sleep tonight knowing I have another trick up my sleeve to harness Paris' unruly tendencies.  
T.

"Tom Bruhl" <arpeggio@comcast.net> wrote in message =  
news:46a59a24@linux...

David,

Your suggestion didn't totally make sense to me.

Which part of the Config should be set to 8?

I've never used a number that low there.

I don't have the option to adjust to med either for some reason.

Not sure what that's about.

I can tell you one thing though, the Midi drivers are not installed. I go to install them manually and it says no good. I am pointing it at the Paris folder with all the goods in it. Maybe I have faulty = drivers?

That would explain all the crap since after I reinstalled a week ago. I'll go look on the web for the drivers I guess.

Tom

I choose Polesoft Lockspam to fight spam, and you?



href=3D"mailto:arpeggio@comcast.net">arpeggio@comcast.net</A>&gt; wrote =  
in message=20  
<A href=3D"news:46a59a24@linux">news:46a59a24@linux</A>...</DIV>  
<DIV><FONT face=3DArial size=3D2>David,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Your suggestion didn't totally make =  
sense to=20  
me.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Which part of the Config should be =  
set to=20  
8?</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>I've never used a number that low=20  
there.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>I don't have the option to adjust to =  
med either=20  
for some reason.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Not sure what that's =  
about.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>I can tell you one thing though, the =  
Midi drivers=20  
are not installed.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>I go to install them manually and it =  
says no=20  
good.&nbsp;</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>at the Paris folder with all the =  
goods in=20  
it.&nbsp;</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>That would explain all the crap since =  
after I=20  
reinstalled a week ago.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>I'll go look on the web for the =  
drivers I=20  
guess.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Tom</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT size=3D2><BR><BR>I choose Polesoft Lockspam to fight spam, =  
and=20  
you?<BR><A=20  
=  
href=3D"http://www.polesoft.com/refer.html">http://www.polesoft.com/refer=  
..html</A>&nbsp;&nbsp;&nbsp;</FONT></DIV></BLOCKQUOTE ></BODY></HTML>

-----=\_NextPart\_000\_006C\_01C7CD9B.DFB6E9C0--

---