

---

Subject: issues with headphone mix setup

Posted by [Oui\\_Oui](#) on Mon, 19 Apr 2010 13:16:29 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I have an mec , 8in card, adat card.. Followed path that was suggested in paris wiki .. Still having issues with seperating headphone left and right to furman hds... I found the only way I get the aux send to work is to put an effect on it (compressor 1:1) . Is that true?? The monitor out L/R on the back of the mec is what I'm sending to headphone amp... should be two seperate channels .. I'm hearing things on both channels not seperated... Any ideas...????????? Tried pushing mono on sends ... Compressor is a mono effect I think.... thx

---

---

Subject: Re: issues with headphone mix setup

Posted by [drfrankencopter](#) on Mon, 19 Apr 2010 14:18:55 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Not sure what the wiki says, but if you want to headphone monitor using the aux sends for 2 independent, mono mixes, then do the following:

- 1) Make your physical connections (e.g. MEC out 3&4 to Furman In 1 & 2)
- 2) In the Paris patch bay, connect MEC output 3 to Aux 1, and output 4 to Aux 2
- 3) In the mixer window select 'External' for the FX on Aux 1 & 2 (note that this has to be on the same Submix as your mec is attached to). While you're here, select mono on the sends
- 4) Enable the aux sends on the channels you want to monitor...
- 5) Now you should have independant mono auxes

Cheers

Kris

---