
Subject: my next fun endeavor

Posted by [Deej](#) on Sat, 22 Dec 2007 06:29:08 GMT

[View Forum Message](#) <> [Reply to Message](#)

It may not really be too much of a big deal, but one thing I hate about Cubase is that I can't seem to find a way to save a template that has the I/O named according to the way the ASIO drivers configure them when working at 44.1/48k and another one set up solely for 88.2/96k. Maybe I'm missing something here, but right now I've got the I/O labelled in Cubase so that when, say, a certain numbered input is for one of my D/A's at 88.2 but correlates to one of the ADAT returns from my slave DAW at 44.1, I can recognize it by naming it something like In8/Slave 16 or something like that.

What I want to be able to do is open up a project at 88.2 and all of the I/O are named according to what they are interfacing with, with no double names. Same thing at 44.1. the only way I can see to do this would be to have dual boot OS drives on both my master and slave machines.

What I would like to be able to do is take Acronis True Image and clone both my Master and Slave HD's to two separate drives, as safety copies, just in case, and then use some sort of disk utility to create a new partition on each of the original drives, then use True Image to clone the disk image to the new partition on each of the drives. That way I could have an 88.2 partition and a 44.1 partition, each with a template of Cubase set up to work at whatever sample rates I need to use, and each template will have the Cubase I/O named correctly.

This also sounds like something I could **** up about as bad as a soup sandwich.

Subject: Re: my next fun endeavor

Posted by [Neil](#) on Sat, 22 Dec 2007 17:55:37 GMT

[View Forum Message](#) <> [Reply to Message](#)

Deej, you know you can re-name you i/o's, right? What if you just created a 44.1k template & named all the i/o's according to their sources & destinations, save it, and THEN change the samplerate to 88.2k, refresh your i/o's (which will cause half of your lightpipe i/o's to disappear) then rename as necessary, & save that as your 88.2k template... no need for none o' 'dat dual-boot/dual-partition/dual-sized-headache garbage.

Neil

"Deej" <noway@jose.org> wrote:

>It may not really be too much of a big deal, but one thing I hate about

>Cubase is that I can't seem to find a way to save a template that has the

>I/O named according to the way the ASIO drivers configure them when working

>at 44.1/48k and another one set up solely for 88.2/96k. Maybe I'm missing

>something here, but right now I've got the I/O labelled in Cubase so that

>when, say, a certain numbered input is for one of my D/A's at 88.2 but

>correlates to one of the ADAT returns from my slave DAW at 44.1, I can

>recognize it by naming it something like In8/Slave 16 or something like

>that.

>

>What I want to be able to do is open up a project at 88.2 and all of the

I/O

>are named according to what they are interfacing with, with no double names.

>Same thing at 44.1. the only way I can see to do this would be to have dual

>boot OS drives on both my master and slave machines.

>

>What I would like to be able to do is take Acronis True Image and clone both

>my Master and Slave HD's to two separate drives, as safety copies, just in

>case, and then use some sort of disk utility to create a new partition on

>each of the original drives, then use True Image to clone the disk image to

>the new partition on each of the drives. That way I could have an 88.2

>partition and a 44.1 partition, each with a template of Cubase set up to

>work at whatever sample rates I need to use, and each template will have the

>Cubase I/O named correctly.

>

>This also sounds like something I could **** up about as bad as a soup

>sandwich.

>

>

Subject: Re: my next fun endeavor

This is a multi-part message in MIME format.

-----=_NextPart_000_0016_01C84497.CE4B9730

Content-Type: text/plain;

charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

Neil,

I'm dealing with a MADI system here. On the Multiface, yes, half the = ADAT I/O disappears, but this is also the case with a MADI system = because it's all ADAT I/O. When 8 x I/O on my Multiface plus the 64 I/O = on the MADI system (32 of which are connected to a pair of AD/DA = converters) are reconfigured between the two sample rates, there is a = hell of a bunch of confusion with the naming of ports. On a MADI system. = my ADAT 1-32 is connected to a pair of ADI 8-DS AD/DA converters. In = 44.1K mode, I/O #'s 9-16 and 25-32 are not even being used because they = are connected to the 8 Aux ports of the ADI 8-DS units which are not = running at double speed, but in 88.2 mode, they are being used. My = system configures itself as follows:

MF A 1 - 8 =3D AD/DA I/O 1-8

MF SPDIF L & R input =3D return from HDSP 9652, output to DAC-1

MF ADAT 1-4 inputs =3D return 1-4 from HDSP 9652 slave at 44.1 and 88.2

MF ADAT 5-8 inputs =3D return 5-8 from HDSP 9652 slave at 44.1 only

MADI 1-8 =3D AD/DA I/O 9-16 at both 44.1 and 88.2

MADI 9-16=3D open at 44.1 but correlate to analog I/O 17-24 at 88.2

MADI 17-24 =3D AD/DA 17-24 at 44.1 but correlate to HDSP 9652 ADAT slave = returns 5-8 at 88.2

MADI 25-32 =3D open at 44.1 but correlate to HDSP 9652 ADAT slave = returns 9-16 at 88.2

MADI 33-40=3D AD/DA 17-24 at 44.1

MADI 41-64=3D returns from HDSP 9652 ADAT slave at 44.1

This creates a less than elegant scenario for the naming of the ports = and even more suckage when assigning them and reassigning them from = project to project.....and even more suckage when assigning names of =

ports to the analog I/O for external hardware and the saving of same as = favorites.=20

If I had two separate drive images, things would be a lot less cluttered = and much easier to configure/reconfigure and it would only take as much = time as it takes to reboot the computer.

Much of this idiocy is due to Cubase not allowing the saving of = templates for port configurations.....or if it does I can't find where = it allows this.

The Neve box there yet?

;o)

"Neil" <OIUOIU@OIU.com> wrote in message news:476d4189\$1@linux...>=20

> DeeJ, you know you can re-name you i/o's, right? What if you
> just created a 44.1k template & named all the i/o's according
> to their sources & destinations, save it, and THEN change the
> samplerate to 88.2k, refresh your i/o's (which will cause half
> of your lightpipe i/o's to disappear) then rename as necessary,
> & save that as your 88.2k template... no need for none o' 'dat
> dual-boot/dual-partition/dual-sized-headache garbage.

>=20

> Neil

>=20

>=20

>=20

> "Deej" <noway@jose.org> wrote:

>>It may not really be too much of a big deal, but one thing I hate = about

>=20

>>Cubase is that I can't seem to find a way to save a template that has = the

>=20

>>I/O named according to the way the ASIO drivers configure them when = working

>=20

>>at 44.1/48k and another one set up solely for 88.2/96k. Maybe I'm = missing

>=20

>>something here, but right now I've got the I/O labelled in Cubase so =
that
>=20
>>when, say, a certain numbered input is for one of my D/A's at 88.2 but =

>>correlates to one of the ADAT returns from my slave DAW at 44.1, I can =

>>recognize it by naming it something like In8/Slave 16 or something =
like
>=20
>>that.
>>
>>What I want to be able to do is open up a project at 88.2 and all of =
the
> I/O=20
>>are named according to what they are interfacing with, with no double =
names.
>=20
>>Same thing at 44.1. the only way I can see to do this would be to have =
dual
>=20
>>boot OS drives on both my master and slave machines.
>>
>>What I would like to be able to do is take Acronis True Image and =
clone
> both=20
>>my Master and Slave HD's to two separate drives, as safety copies, =
just
> in=20
>>case, and then use some sort of disk utility to create a new partition =
on
>=20
>>each of the original drives, then use True Image to clone the disk =
image
> to=20
>>the new partition on each of the drives. That way I could have an 88.2 =

>>partition and a 44.1 partition, each with a template of Cubase set up =
to
>=20
>>work at whatever sample rates I need to use, and each template will =
have
> the=20
>>Cubase I/O named correctly.
>>
>>This also sounds like something I could **** up about as bad as a soup =

>>sandwich.

```

>>
>>
>
-----=_NextPart_000_0016_01C84497.CE4B9730
Content-Type: text/html;
  charset="iso-8859-1"
Content-Transfer-Encoding: quoted-printable

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.6000.16587" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY>
<DIV><FONT face=3DArial size=3D2>Neil,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>I'm dealing with a MAD I system here. On =
the=20
Multiface, yes, half the ADAT I/O disappears, but this is also the case =
with a=20
MADI system because it's </FONT><EM>all</EM> ADAT&nbsp; I/O. When 8 x =
I/O on my=20
Multiface plus the 64&nbsp;I/O on the MADI system (32 of which are =
connected to=20
a pair of AD/DA converters) are reconfigured between the two sample =
rates, there=20
is a hell of a bunch of confusion with the naming of ports. On a MADI =
system. my=20
ADAT 1-32 is connected to a pair of ADI 8-DS AD/DA converters. In 44.1K =
mode,=20
I/O #'s 9-16 and 25-32 are not even being used because they are =
connected to the=20
8 Aux ports of the ADI 8-DS units which are not running at double speed, =
but in=20
88.2 mode, they&nbsp;are being used. My system configures itself as=20
follows:</DIV>
<DIV>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>MF A 1 - 8 =3D AD/DA I/O =
1-8</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>MF SPDIF L & R input =3Dreturn from =
HDSP 9652,=20
output to DAC-1</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>MF ADAT 1-4 inputs =3D return 1-4 from =
HDSP 9652=20

```

slave at 44.1 and 88.2</DIV>
<DIV> </DIV>
<DIV>MF ADAT 5-8 inputs =3D return 5-8 from =
HDSP 9652=20
slave at 44.1 only</DIV>
<DIV> </DIV>
<DIV>MADI 1-8 =3D AD/DA I/O 9-16 at both =
44.1 and=20
88.2</DIV>
<DIV> </DIV>
<DIV>MADI 9-16=3Dopen at 44.1 but correlate =
to analog 1/0=20
17-24 at 88.2</DIV>
<DIV> </DIV>
<DIV>MADI 17-24 =3D AD/DA 17-24 at 44.1 but =
correlate to=20
HDSP 9652 ADAT slave returns 5-8 at 88.2</DIV>
<DIV> </DIV>
<DIV>MADI 25-32 =3D open at 44.1 but =
correlate to HDSP=20
9652 ADAT slave returns 9-16 at 88.2</DIV>
<DIV> </DIV>
<DIV>MADI 33-40=3DAD/DA 17-24 at =
44.1</DIV>
<DIV> </DIV>
<DIV>MADI 41-64=3Dreturns from HDSP 9652 =
ADAT slave at=20
44.1</DIV>
<DIV> </DIV>
<DIV>This creates a less than elegant =
scenario for the=20
naming of the ports and even more suckage when assigning them and =
reassigning=20
them from project to project.....and even more suckage when =
assigning names=20
of ports to the analog I/O for external hardware and the saving of =
same as=20
favorites. </DIV>
<DIV> </DIV>
<DIV>If I had two separate drive images, =
things would be=20
a lot less cluttered and much easier to configure/reconfigure and it =
would only=20
take as much time as it takes to reboot the computer.</DIV>
<DIV> </DIV>
<DIV>Much of this idiocy is due to Cubase =
not allowing=20
the saving of templates for port configurations.....or if it does I =

can't find=20
 where it allows this.</DIV>
 <DIV> </DIV>
 <DIV>The Neve box there yet?</DIV>
 <DIV> </DIV>
 <DIV>;o)</DIV>
 <DIV> </DIV>
 <DIV> </DIV>
 <DIV><FONT face=3DArial =
 size=3D2> </DIV>
 <DIV> </DIV>
 <DIV> </DIV>
 <DIV> </DIV>
 <DIV> </DIV>
 <DIV>"Neil" <<A=20
 href=3D"mailto:OIUOIU@OIU.com"><FONT face=3DArial=20
 size=3D2>OIUOIU@OIU.com> wrote =
 in message=20
 <FONT face=3DArial=20
 size=3D2>news:476d4189\$1@linux<FONT face=3DArial=20
 size=3D2>...</DIV>>
> DeeJ, =
 you know you=20
 can re-name you i/o's, right? What if you
> just created a 44.1k =
 template=20
 & named all the i/o's according
> to their sources & =
 destinations,=20
 save it, and THEN change the
> samplerate to 88.2k, refresh your =
 i/o's=20
 (which will cause half
> of your lightpipe i/o's to disappear) =
 then rename=20
 as necessary,
> & save that as your 88.2k template... no need =
 for none=20
 o' 'dat
> dual-boot/dual-partition/dual-sized-headache =
 garbage.
>=20

> Neil
>
>
>
> "DeeJ" <<A=20
 href=3D"mailto:noway@jose.org"><FONT face=3DArial=20
 size=3D2>noway@jose.org>=20
 wrote:
>>It may not really be too much of a big deal, but one =
 thing I=20
 hate about
>
>>Cubase is that I can't seem to find a way =
 to save=20
 a template that has the
>
>>I/O named according to the =
 way the=20
 ASIO drivers configure them when working
>
>>at 44.1/48k =
 and=20
 another one set up solely for 88.2/96k. Maybe I'm missing
>=20

>>something here, but right now I've got the I/O labelled in =
 Cubase so=20

that
> > when, say, a certain numbered input is for one =
of my=20
D/A's at 88.2 but > > correlates to one of the ADAT returns from =
my=20
slave DAW at 44.1, I can > > recognize it by naming it something =
like=20
In8/Slave 16 or something like> >=20
> > that.> > > > What I want to be able to do is =
open up=20
a project at 88.2 and all of the> > I/O > > are named =
according to=20
what they are interfacing with, with no double names.> > =
> > Same=20
thing at 44.1. the only way I can see to do this would be to have =
dual> >=20
> > boot OS drives on both my master and slave=20
machines.> > > > What I would like to be able to do is =
take=20
Acronis True Image and clone> > both > > my Master and =
Slave HD's=20
to two separate drives, as safety copies, just> > in =
> > case, and=20
then use some sort of disk utility to create a new partition on> >=20
> > each of the original drives, then use True Image to clone =
the disk=20
image> > to > > the new partition on each of the drives. =
That way I=20
could have an 88.2 > > partition and a 44.1 partition, each with =
a=20
template of Cubase set up to> > > > work at whatever sample =
rates I=20
need to use, and each template will have> > the > > Cubase =
I/O=20
named correctly.> > > > This also sounds like something =
I could=20
**** up about as bad as a soup=20
> > sandwich.> > > > > </BODY></HTML=
>

-----=_NextPart_000_0016_01C84497.CE4B9730--

Subject: Re: my next fun endeavor
Posted by [Deej](#) on Sat, 22 Dec 2007 20:37:49 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hmmmm.....OK then.....you're saying the port names that are named in
the device manager can be saved with a project template?

I haven't been able to accomplish this. Maybe it's because I'm not setting my sample rate in a correct sequence of events?

I'll look into this.

thanks,

Deej

"Neil" <OIUOIU@OIU.com> wrote in message news:476d6cde\$1@linux...

>

> Oops, i meant:

>

> "when you boot up, let's say your 44.1k image - if you have

> your clock set to ***88.2k***..." etc, etc

>

> Neil

>

>

> "Neil" <IUOIU@OIU.com> wrote:

>>

>>"Deej" <noway@jose.org> wrote:

>>

>>>If I had two separate drive images, things would be a lot less cluttered

>>=

>>>and much easier to configure/reconfigure and it would only take as much

>>=

>>>time as it takes to reboot the computer.

>>

>>OK, i think i kinda see where you're going, but I think you're

>>still going to have the following problem: when you boot up,

>>let's say your 44.1k image - if you have your clock set to 44.1k

>>it's STILL going to only display half of your lightpipe i/o's

>>until you re-clock... really I think all you have to do is to

>>make sure you're clocked at your chosen samplerate as you boot

>>up, and then you can open the appropriate template & the i/o's

>>should be correct.

>>

>>>Much of this idiocy is due to Cubase not allowing the saving of

>>>templates for port configurations.....or if it does I can't

>>>find where it allows this.

>>

>>The i/o configurations all save with the project, as long as

>>your clock matches the samplerate of the project that you're

>>opening... unless i'm somehow not understanding your meaning.

>>

>>>The Neve box there yet?

>>
>>YES! Didn't you see my post where I was raving about it?
>>
>>Neil
>

Subject: Re: my next fun endeavor
Posted by [Deej](#) on Sat, 22 Dec 2007 20:56:12 GMT
[View Forum Message](#) <> [Reply to Message](#)

This is a multi-part message in MIME format.

-----=_NextPart_000_007A_01C844A2.6A0A9BD0
Content-Type: text/plain;
charset="iso-8859-1"
Content-Transfer-Encoding: quoted-printable

Wait!!!.....I'm not talking about the I/O assignments, I'm talking about =
I/O names and whether or not they are hidden or not in the device =
manager.....oh..nevermind.....

;o)

"Neil" <IUOIU@OIU.com> wrote in message news:476d6c57\$1@linux...

>=20

> "Deej" <noway@jose.org> wrote:

>=20

>>If I had two separate drive images, things would be a lot less =
cluttered

> =3D

>>and much easier to configure/reconfigure and it would only take as =
much

> =3D

>>time as it takes to reboot the computer.

>=20

> OK, i think i kinda see where you're going, but I think you're

> still going to have the following problem: when you boot up,

> let's say your 44.1k image - if you have your clock set to 44.1k

> it's STILL going to only display half of your lightpipe i/o's

> until you re-clock... really I think all you have to do is to

> make sure you're clocked at your chosen samplerate as you boot

> up, and then you can open the appropriate template & the i/o's

> should be correct.

>=20

>>Much of this idiocy is due to Cubase not allowing the saving of

>>templates for port configurations.....or if it does I can't=20

>>find where it allows this.

>=20

> The i/o configurations all save with the project, as long as
> your clock matches the samplerate of the project that you're
> opening... unless i'm somehow not understanding your meaning.

>=20

>>The Neve box there yet?

>=20

> YES! Didn't you see my post where I was raving about it?

>=20

> Neil

-----=_NextPart_000_007A_01C844A2.6A0A9BD0

Content-Type: text/html;

charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">

<HTML><HEAD>

<META http-equiv=3DContent-Type content=3D"text/html; =

charset=3Diso-8859-1">

<META content=3D"MSHTML 6.00.6000.16587" name=3DGENERATOR>

<STYLE></STYLE>

</HEAD>

<BODY>

<DIV>Wait!!!.....I'm not talking about the =

I/O=20

assignments, I'm talking about I/O names and whether or not =

they are=20

hidden or not in the device=20

manager.....oh..nevermind.....</DIV>

<DIV> </DIV>

<DIV>;o</DIV>

<DIV> </DIV>

<DIV>"Neil" <<A=20

href=3D"mailto:IUOIU@OIU.com"><FONT face=3DArial=20

size=3D2>IUOIU@OIU.com> wrote =

in message=20

<FONT face=3DArial=20

size=3D2>news:476d6c57\$1@linux<FONT face=3DArial=20

size=3D2>...</DIV>>
> =

"Deej"=20

<<FONT face=3DArial=20

size=3D2>noway@jose.org> =

wrote:
>=20

>>If I had two separate drive images, things would be a lot =

less=20

cluttered
>=3D
>>and much easier to =

configure/reconfigure and it=20

would only take as much
>=3D
>>time as it takes to =

reboot the=20
computer.
>
> OK, i think i kinda see where you're going, =
but I=20
think you're
> still going to have the following problem: when you =
boot=20
up,
> let's say your 44.1k image - if you have your clock set to=20
44.1k
> it's STILL going to only display half of your lightpipe=20
i/o's
> until you re-clock... really I think all you have to do is =

to
> make sure you're clocked at your chosen samplerate as you=20
boot
> up, and then you can open the appropriate template &=20
the=20
i/o's
> should be correct.
>
>>Much of this idiocy =
is due=20
to Cubase not allowing the saving of
>>templates for port=20
configurations.....or if it does I can't
>>find where it =
allows=20
this.
>
> The i/o configurations all save with the project, =
as long=20
as
> your clock matches the samplerate of the project that =
you're
>=20
opening... unless i'm somehow not understanding your meaning.
>=20

>>The Neve box there yet?
>
> YES! Didn't you see =
my post=20
where I was raving about it?
>
> Neil</BODY></HTML>

-----=_NextPart_000_007A_01C844A2.6A0A9BD0--

Subject: Re: my next fun endeavor
Posted by [Nil](#) on Sat, 22 Dec 2007 20:58:15 GMT
[View Forum Message](#) <> [Reply to Message](#)

"Deej" <noway@jose.org> wrote:

>If I had two separate drive images, things would be a lot less cluttered
=
>and much easier to configure/reconfigure and it would only take as much
=
>time as it takes to reboot the computer.

OK, i think i kinda see where you're going, but I think you're
still going to have the following problem: when you boot up,
let's say your 44.1k image - if you have your clock set to 44.1k
it's STILL going to only display half of your lightpipe i/o's
until you re-clock... really I think all you have to do is to
make sure you're clocked at your chosen samplerate as you boot
up, and then you can open the appropriate template & the i/o's

should be correct.

>Much of this idiocy is due to Cubase not allowing the saving of
>templates for port configurations.....or if it does I can't
>find where it allows this.

The i/o configurations all save with the project, as long as
your clock matches the samplerate of the project that you're
opening... unless i'm somehow not understanding your meaning.

>The Neve box there yet?

YES! Didn't you see my post where I was raving about it?

Neil

Subject: Re: my next fun endeavor
Posted by [Neil](#) on Sat, 22 Dec 2007 21:00:30 GMT
[View Forum Message](#) <> [Reply to Message](#)

Oops, i meant:

"when you boot up, let's say your 44.1k image - if you have
your clock set to ***88.2k***..." etc, etc

Neil

"Neil" <IUOIU@OIU.com> wrote:

>

>"Deej" <noway@jose.org> wrote:

>

>>If I had two separate drive images, things would be a lot less cluttered

>=

>>and much easier to configure/reconfigure and it would only take as much

>=

>>time as it takes to reboot the computer.

>

>OK, i think i kinda see where you're going, but I think you're

>still going to have the following problem: when you boot up,

>let's say your 44.1k image - if you have your clock set to 44.1k

>it's STILL going to only display half of your lightpipe i/o's

>until you re-clock... really I think all you have to do is to

>make sure you're clocked at your chosen samplerate as you boot

>up, and then you can open the appropriate template & the i/o's

>should be correct.

>

>>Much of this idiocy is due to Cubase not allowing the saving of
>>templates for port configurations.....or if it does I can't
>>find where it allows this.
>
>The i/o configurations all save with the project, as long as
>your clock matches the samplerate of the project that you're
>opening... unless i'm somehow not understanding your meaning.
>
>>The Neve box there yet?
>
>YES! Didn't you see my post where I was raving about it?
>
>Neil

Subject: Re: my next fun endeavor - DeeJ, here's your answer
Posted by [Neil](#) on Sun, 23 Dec 2007 02:28:53 GMT
[View Forum Message](#) <> [Reply to Message](#)

OK, look, here's the way you do it... if you go to the topbar menu & select: Devices/VST Connections & select either the "Inputs" or "Outputs" tab, you'll see a little teeny black window in the upper area that says "presets"; it has several stock presets that you can load using the drop-down arrow on the right-hand side of that, but what you want to do is note the little - even teensier - folder icon with the plus sign, just to the right of the little presets windowette... THAT's how you save your i/o preset templates.

Make one for 88.2k first, ensuring that your clock is set to 88.2 so you see all the lightpipe ports, name everything the way you want on the Input side (tab), then click the little folder icon with the plus sign in it, and save it as: "88k Insies" or whatever makes sense to you, then go over to the Output tab & name everything the way you want, repeat the folder icon save procedure & name it "88k Outsies" or what have you... THEN reclock to 44.1k. At this point, of course, your lightpipe i/o's will collapse down & you can refresh the i/o's under "Devices/Device Setup", then look down the list for VST inputs & VST outputs - go to each one & hit "reset". (in fact, you may want to do this even before you do the 88.2k i/o template - i keep forgetting you're not exclusively on 88.2, so you may have to reset/refresh before you start, just to make sure you're seeing all of them).

OK, once you've done that at 44.1k, start naming your i/o's for the 44.1k versions of what you just saved, as described above... then save one for the Input side & one under the

output tab, each with it's own name, appropriately.

And there you have it!!!!!!! No muss, no fuss, no dual-partitioning needed. All you'll have to make sure you do is to refresh your VST connections each time you go between a 44.1k project & an 88.2k one, then pull up the your saved i/o templates!

Neil

"Deej" <noway@jose.org> wrote:

>

>

>Wait!!!.....I'm not talking about the I/O assignments, I'm talking about

=

>I/O names and whether or not they are hidden or not in the device =

>manager.....oh..nevermind.....

Subject: Re: my next fun endeavor - Deej, here's your answer

Posted by [Deej](#) on Sun, 23 Dec 2007 05:40:23 GMT

[View Forum Message](#) <> [Reply to Message](#)

This is a multi-part message in MIME format.

-----=_NextPart_000_00FC_01C844EB.A423C4B0

Content-Type: text/plain;

charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

Hey Neil,

I get what you're saying and I do use the presets, but what I'm talking about is completely different. the following is what I'm unhappy about:

Navigate to:

Devices>Device Setup>VST Audio System>ASIO Hammerfall DSP

On the right is the screen where you choose to enable/disable direct monitoring. Below that is where the I/O ports are shown. the port system name is shown and to it's right you can name the port in the Show As column. The Show As names cannot be saved in an 88.2 template and a 44.1 template. No matter what template you save, the names in the Show As column and any ports you might want to choose to hide because you =

aren't using them in 44.1 mode (MF ADAT ports 4-8 and and MAD1 ports = 33-64 when using 88.2 and MAD1 ADAT ports 9-16 and 25 through 32 when = using 44.1 in my particular situation) will carry over no matter what = the template/sample rate you save/use. Well, if I'm working at 44.1, = I've got all these ports showing up that I want to hide because they are = of no possible use to me, they have double names because some of them = correlate to totally different ports at 88.2 and they just tend to = clutter up the I/O configurations that I want to be able to create = quickly.

Using a dual boot system, one strictly for 44.1 and the other for 88.2 = would solve this completely....and it's the only way I can see that = would do this.

Regards,

Deej

"Neil" <OIUOIU@OIU.com> wrote in message news:476db9d5\$1@linux...

>=20

> OK, look, here's the way you do it... if you go to the topbar
> menu & select: Devices/VST Connections & select
> either the "Inputs" or "Outputs" tab, you'll se a little teeny
> black window in the upper area that says "presets"; it has
> several stock presets that you can load using the drop-down
> arrow on the right-hand side of that, but what you want to do
> is note the little - even teensier - folder icon with the plus
> sign, just to the right of the little presets windowette...
> THAT's how you save your i/o preset templates.

>=20

> Make one for 88.2k first, ensuring that your clock is set to
> 88.2 so you see all the lightpipe ports, name everything the
> way you want on the Input side (tab), then click the little
> folder icon with the plus sign in it, and save it as: "88k
> Insies" or whatever makes sense to you, then go over to the
> Output tab & name everything the way you want, repeat the
> folder icon save procedure & name it "88k Outsies" or what have
> you... THEN reclock to 44.1k. At this point, of course, your
> lightpipe i/o's will collapse down & you can refresh the i/o's
> under "Devices/Device Setup", then look down the list for VST
> inputs & VST outputs - go to each one & hit "reset". (in fact,
> you may want to do this even before you do the 88.2k i/o
> template - i keep forgetting you're not exclusively on 88.2, so
> you may have to reset/refresh before you start, just to make
> sure you're seeing all of them).

>=20

> OK, once you've done that at 44.1k, start naming your i/o's for
> the 44.1k versions of what you just saved, as described
> above... then save one for the Input side & one under the
> output tab, each with it's own name, appropriately.
>=20
> And there you have it!!!!!!! No muss, no fuss, no dual-
> partitioning needed. All you'll have to make sure you do is to
> refresh your VST connections each time you go between a 44.1k
> project & an 88.2k one, then pull up the your saved i/o
> templates!
>=20
> Neil
>=20
>=20
>=20
>=20
> "Deej" <noway@jose.org> wrote:
>>
>>
>>Wait!!!.....I'm not talking about the I/O assignments, I'm talking =
about
> =3D
>>I/O names and whether or not they are hidden or not in the device =3D
>>manager.....oh..nevermind.....
-----=_NextPart_000_00FC_01C844EB.A423C4B0
Content-Type: text/html;
charset="iso-8859-1"
Content-Transfer-Encoding: quoted-printable

```

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.6000.16587" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY>
<DIV><FONT face=3DArial size=3D2>Hey Neil,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>I get what you're saying and I do use =
the presets,=20
but what I'm talking about is completely different. the =
following&nbsp;&nbsp;&nbsp;is=20
what I'm unhappy about:</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>Navigate to:</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>Devices>Device Setup>VST Audio =

```

System>ASIO=20
 Hammerfall DSP</DIV>
 <DIV> </DIV>
 <DIV>On the right is the screen where you =
 choose to=20
 enable/disable direct monitoring. Below that is where the I/O ports are =
 shown.=20
 the port system name is shown and to it's right you can name the =
 port <in=20
 the Show As <column. The
 Show=20
 As <names cannot be saved in an 88.2 template and a =
 44.1=20
 template. No matter what template you save, the names in the =
 Show=20
 As column and any ports you might want to choose to hide =
 because=20
 you aren't using them in 44.1 mode (MF ADAT ports 4-8 and and MADI ports =
 33-64=20
 when using 88.2 and MADI ADAT ports 9-16 and 25 through 32 when using =
 44.1 in my=20
 particular situation) will carry over no matter what the template/sample =
 rate=20
 you save/use. Well, if I'm working at 44.1, <I've got all these =
 ports=20
 showing up that I want to hide because they are of no possible use to =
 me, they=20
 have double names because some of them correlate to totally different =
 ports at=20
 88.2 and they just tend to clutter up the I/O configurations that I want =
 to be=20
 able to create quickly.</DIV>
 <DIV> </DIV>
 <DIV>Using a dual boot system, one strictly =
 for 44.1 and=20
 the other for 88.2 would solve this completely....and it's the only way =
 I can=20
 see that would do this.</DIV>
 <DIV> </DIV>
 <DIV>Regards,</DIV>
 <DIV> </DIV>
 <DIV>Deej</DIV>
 <DIV> </DIV>
 <DIV> </DIV>
 <DIV> </DIV>
 <DIV>"Neil" <<A=20
 href=3D"mailto:OIUOIU@OIU.com"><FONT face=3DArial=20
 size=3D2>OIUOIU@OIU.com> wrote =

in message=20
 <FONT face=3DArial=20
 size=3D2>news:476db9d5\$1@linux<FONT face=3DArial=20
 size=3D2>...</DIV>>
> OK, =
 look, here's=20
 the way you do it... if you go to the topbar
> menu & select:=20
 Devices/VST Connections & select
> either the "Inputs" or =
 "Outputs"=20
 tab, you'll se a little teeny
> black window in the upper area =
 that says=20
 "presets"; it has
> several stock presets that you can load using =
 the=20
 drop-down
> arrow on the right-hand side of that, but what you =
 want to=20
 do
> is note the little - even teensier - folder icon with the=20
 plus
> sign, just to the right of the little presets =
 windowette...
>=20
 THAT's how you save your i/o preset templates.
>
> Make one =
 for=20
 88.2k first, ensuring that your clock is set to
> 88.2 so you see =
 all the=20
 lightpipe ports, name everything the
> way you want on the Input =
 side=20
 (tab), then click the little
> folder icon with the plus sign in =
 it, and=20
 save it as: "88k
> Insies" or whatever makes sense to you, then go =
 over to=20
 the
> Output tab & name everything the way you want, repeat=20
 the
> folder icon save procedure & name it "88k Outsies" or =
 what=20
 have
> you... THEN reclock to 44.1k. At this point, of course,=20
 your
> lightpipe i/o's will collapse down & you can refresh =
 the=20
 i/o's
> under "Devices/Device Setup", then look down the list for=20
 VST
> inputs & VST outputs - go to each one & hit "reset". =
 (in=20
 fact,
> you may want to do this even before you do the 88.2k =
 i/o
>=20
 template - i keep forgetting you're not exclusively on 88.2, so
> =
 you may=20
 have to reset/refresh before you start, just to make
> sure you're =
 seeing=20
 all of them).
>
> OK, once you've done that at 44.1k, start =
 naming=20
 your i/o's for
> the 44.1k versions of what you just saved, as=20
 described
> above... then save one for the Input side & one =
 under=20
 the
> output tab, each with it's own name, appropriately.
> =

>>
>>Hey Neil,
>>
>>I get what you're saying and I do use the presets, but what I'm talking
> =
>>about is completely different. the following is what I'm unhappy about:
>>
>>Navigate to:
>>
>>Devices>Device Setup>VST Audio System>ASIO Hammerfall DSP
>>
>>On the right is the screen where you choose to enable/disable direct =
>>monitoring. Below that is where the I/O ports are shown. the port system
> =
>>name is shown and to it's right you can name the port in the Show As =
>>column. The Show As names cannot be saved in an 88.2 template and a =
>>44.1 template. No matter what template you save, the names in the Show =
>>As column and any ports you might want to choose to hide because you =
>>aren't using them in 44.1 mode (MF ADAT ports 4-8 and and MADI ports =
>>33-64 when using 88.2 and MADI ADAT ports 9-16 and 25 through 32 when =
>>using 44.1 in my particular situation) will carry over no matter what =
>>the template/sample rate you save/use. Well, if I'm working at 44.1, =
>>I've got all these ports showing up that I want to hide because they are
> =
>>of no possible use to me, they have double names because some of them =
>>correlate to totally different ports at 88.2 and they just tend to =
>>clutter up the I/O configurations that I want to be able to create =
>>quickly.
>>
>>Using a dual boot system, one strictly for 44.1 and the other for 88.2 =
>>would solve this completely....and it's the only way I can see that =
>>would do this.
>>
>>Regards,
>>
>>Deej
>>
>>
>>
>>"Neil" <OIUOIU@OIU.com> wrote in message news:476db9d5\$1@linux...
>>>=20
>>> OK, look, here's the way you do it... if you go to the topbar
>>> menu & select: Devices/VST Connections & select
>>> either the "Inputs" or "Outputs" tab, you'll se a little teeny
>>> black window in the upper area that says "presets"; it has
>>> several stock presets that you can load using the drop-down
>>> arrow on the right-hand side of that, but what you want to do
>>> is note the little - even teensier - folder icon with the plus

```

>>> sign, just to the right of the little presets windowette...
>>> THAT's how you save your i/o preset templates.
>>>=20
>>> Make one for 88.2k first, ensuring that your clock is set to
>>> 88.2 so you see all the lightpipe ports, name everything the
>>> way you want on the Input side (tab), then click the little
>>> folder icon with the plus sign in it, and save it as: "88k
>>> Insies" or whatever makes sense to you, then go over to the
>>> Output tab & name everything the way you want, repeat the
>>> folder icon save procedure & name it "88k Outsies" or what have
>>> you... THEN reclock to 44.1k. At this point, of course, your
>>> lightpipe i/o's will collapse down & you can refresh the i/o's
>>> under "Devices/Device Setup", then look down the list for VST
>>> inputs & VST outputs - go to each one & hit "reset". (in fact,
>>> you may want to do this even before you do the 88.2k i/o
>>> template - i keep forgetting you're not exclusively on 88.2, so
>>> you may have to reset/refresh before you start, just to make
>>> sure you're seeing all of them).
>>>=20
>>> OK, once you've done that at 44.1k, start naming your i/o's for
>>> the 44.1k versions of what you just saved, as described
>>> above... then save one for the Input side & one under the
>>> output tab, each with it's own name, appropriately.
>>>=20
>>> And there you have it!!!!!!! No muss, no fuss, no dual-
>>> partitioning needed. All you'll have to make sure you do is to
>>> refresh your VST connections each time you go between a 44.1k
>>> project & an 88.2k one, then pull up the your saved i/o
>>> templates!
>>>=20
>>> Neil
>>>=20
>>>=20
>>>=20
>>>=20
>>> "Deej" <noway@jose.org> wrote:
>>>>
>>>>
>>>>Wait!!!.....I'm not talking about the I/O assignments, I'm talking =
>>about
>>> =3D
>>>>I/O names and whether or not they are hidden or not in the device =3D
>>>>manager.....oh..nevermind.....
>>
>><!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
>><HTML><HEAD>
>><META http-equiv=3DContent-Type content=3D"text/html; =
>>charset=3Diso-8859-1">

```

```

>><META content=3D"MSHTML 6.00.6000.16587" name=3DGENERATOR>
>><STYLE></STYLE>
>></HEAD>
>><BODY>
>><DIV><FONT face=3DArial size=3D2>Hey Neil,</FONT></DIV>
>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>><DIV><FONT face=3DArial size=3D2>I get what you're saying and I do use =
>>the presets,=20
>>but what I'm talking about is completely different. the =
>>following is=20
>>what I'm unhappy about:</FONT></DIV>
>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>><DIV><FONT face=3DArial size=3D2>Navigate to:</FONT></DIV>
>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>><DIV><FONT face=3DArial size=3D2>Devices>Device Setup>VST Audio =
>>System>ASIO=20
>>Hammerfall DSP</FONT></DIV>
>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>><DIV><FONT face=3DArial size=3D2>On the right is the screen where you =
>>choose to=20
>>enable/disable direct monitoring. Below that is where the I/O ports are
> =
>>shown.=20
>>the port system name is shown and to it's right you can name the =
>>port in=20
>>the <STRONG>S<EM>how As</EM></STRONG> column. The <EM><STRONG>Show=20
>>As</STRONG></EM> names cannot be saved in an 88.2 template and a =
>>44.1=20
>>template. No matter what template you save, the names in the =
>><EM><STRONG>Show=20
>>As</STRONG></EM> column and any ports you might want to choose to hide =
>>because=20
>>you aren't using them in 44.1 mode (MF ADAT ports 4-8 and and MADI ports
> =
>>33-64=20
>>when using 88.2 and MADI ADAT ports 9-16 and 25 through 32 when using =
>>44.1 in my=20
>>particular situation) will carry over no matter what the template/sample
> =
>>rate=20
>>you save/use. Well, if I'm working at 44.1, I've got all these =
>>ports=20
>>showing up that I want to hide because they are of no possible use to =
>>me, they=20
>>have double names because some of them correlate to totally different =
>>ports at=20
>>88.2 and they just tend to clutter up the I/O configurations that I want
> =

```

```

>>to be=20
>>able to create quickly.</FONT></DIV>
>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>><DIV><FONT face=3DArial size=3D2>Using a dual boot system, one strictly
> =
>>for 44.1 and=20
>>the other for 88.2 would solve this completely....and it's the only way
> =
>>I can=20
>>see that would do this.</FONT></DIV>
>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>><DIV><FONT face=3DArial size=3D2>Regards,</FONT></DIV>
>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>><DIV><FONT face=3DArial size=3D2>Deej</FONT></DIV>
>><DIV> </DIV>
>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>><DIV><FONT face=3DArial size=3D2>"Neil" </FONT><A=20
>>href=3D"mailto:OIUOIU@OIU.com"><FONT face=3DArial=20
>>size=3D2>OIUOIU@OIU.com</FONT></A><FONT face=3DArial size=3D2>> wrote =
>>in message=20
>></FONT><A href=3D"news:476db9d5$1@linux"><FONT face=3DArial=20
>>size=3D2>news:476db9d5$1@linux</FONT></A><FONT face=3DArial=20
>>size=3D2>...</FONT></DIV><FONT face=3DArial size=3D2>> <BR>> OK, =
>>look, here's=20
>>the way you do it... if you go to the topbar<BR>> menu & select:=20
>>Devices/VST Connections & select<BR>> either the "Inputs" or =
>>"Outputs"=20
>>tab, you'll se a little teeny<BR>> black window in the upper area =
>>that says=20
>>"presets"; it has<BR>> several stock presets that you can load using =
>>the=20
>>drop-down<BR>> arrow on the right-hand side of that, but what you =
>>want to=20
>>do<BR>> is note the little - even teensier - folder icon with the=20
>>plus<BR>> sign, just to the right of the little presets =
>>windowette...<BR>>=20
>>THAT's how you save your i/o preset templates.<BR>> <BR>> Make one =
>>for=20
>>88.2k first, ensuring that your clock is set to<BR>> 88.2 so you see =
>>all the=20
>>lightpipe ports, name everything the<BR>> way you want on the Input =
>>side=20
>>(tab), then click the little<BR>> folder icon with the plus sign in =
>>it, and=20
>>save it as: "88k<BR>> Insies" or whatever makes sense to you, then go =
>>over to=20
>>the<BR>> Output tab & name everything the way you want, repeat=20

```

>>the
> folder icon save procedure & name it "88k Outsies" or =
>>what=20
>>have
> you... THEN reclock to 44.1k. At this point, of course,=20
>>your
> lightpipe i/o's will collapse down & you can refresh =
>>the=20
>>i/o's
> under "Devices/Device Setup", then look down the list for=20
>>VST
> inputs & VST outputs - go to each one & hit "reset". =
>>(in=20
>>fact,
> you may want to do this even before you do the 88.2k =
>>i/o
>=20
>>template - i keep forgetting you're not exclusively on 88.2, so
> =
>>you may=20
>>have to reset/refresh before you start, just to make
> sure you're =
>>seeing=20
>>all of them).
>
> OK, once you've done that at 44.1k, start =
>>naming=20
>>your i/o's for
> the 44.1k versions of what you just saved, as=20
>>described
> above... then save one for the Input side & one =
>>under=20
>>the
> output tab, each with it's own name, appropriately.
> =
>>
>=20
>>And there you have it!!!!!!! No muss, no fuss, no =
>>dual-
>=20
>>partitioning needed. All you'll have to make sure you do is to
> =
>>refresh=20
>>your VST connections each time you go between a 44.1k
> project =
>>& an=20
>>88.2k one, then pull up the your saved i/o
> templates!
> =
>>
>=20
>>Neil
>
>
>
>
> "Deej" <A=20
>>href=3D"mailto:noway@jose.org"><FONT face=3DArial=20
>>size=3D2>noway@jose.org>=20
>>wrote:
>>
>>
>>Wait!!!.....I'm not talking =
>>about the=20
>>I/O assignments, I'm talking about
> =3D
>>I/O names and =
>>whether or=20
>>not they are hidden or not in the device=20
>>=3D
>>manager.....oh..nevermind.....</BODY></H=20
>>TML>
>>
>>
>

Subject: Re: my next fun endeavor - Deej, here's your answer
Posted by [Neil](#) on Sun, 23 Dec 2007 07:03:48 GMT
[View Forum Message](#) <> [Reply to Message](#)

Deej, but if you're clocked at 88.2k, those extra ports won't even show up once you hit "reset" on your VST Inputs & Outputs. I think this might be the issue in this case... you need to refresh those i/o's & it'll detect the clockspeed & slice your ADAT's in half - again, unless I'm just not understanding what you're trying to accomplish.

Neil

"Deej" <noway@jose.org> wrote:

>
>
>Hey Neil,
>
>I get what you're saying and I do use the presets, but what I'm talking
=
>about is completely different. the following is what I'm unhappy about:
>
>Navigate to:
>
>Devices>Device Setup>VST Audio System>ASIO Hammerfall DSP
>
>On the right is the screen where you choose to enable/disable direct =
>monitoring. Below that is where the I/O ports are shown. the port system
=
>name is shown and to it's right you can name the port in the Show As =
>column. The Show As names cannot be saved in an 88.2 template and a =
>44.1 template. No matter what template you save, the names in the Show =
>As column and any ports you might want to choose to hide because you =
>aren't using them in 44.1 mode (MF ADAT ports 4-8 and and MADI ports =
>33-64 when using 88.2 and MADI ADAT ports 9-16 and 25 through 32 when =
>using 44.1 in my particular situation) will carry over no matter what =
>the template/sample rate you save/use. Well, if I'm working at 44.1, =
>I've got all these ports showing up that I want to hide because they are
=
>of no possible use to me, they have double names because some of them =
>correlate to totally different ports at 88.2 and they just tend to =
>clutter up the I/O configurations that I want to be able to create =
>quickly.
>
>Using a dual boot system, one strictly for 44.1 and the other for 88.2 =
>would solve this completely....and it's the only way I can see that =
>would do this.
>
>Regards,
>
>Deej

>
>
>
>"Neil" <OIUOIU@OIU.com> wrote in message news:476db9d5\$1@linux...
>>=20
>> OK, look, here's the way you do it... if you go to the topbar
>> menu & select: Devices/VST Connections & select
>> either the "Inputs" or "Outputs" tab, you'll se a little teeny
>> black window in the upper area that says "presets"; it has
>> several stock presets that you can load using the drop-down
>> arrow on the right-hand side of that, but what you want to do
>> is note the little - even teensier - folder icon with the plus
>> sign, just to the right of the little presets windowette...
>> THAT's how you save your i/o preset templates.
>>=20
>> Make one for 88.2k first, ensuring that your clock is set to
>> 88.2 so you see all the lightpipe ports, name everything the
>> way you want on the Input side (tab), then click the little
>> folder icon with the plus sign in it, and save it as: "88k
>> Insies" or whatever makes sense to you, then go over to the
>> Output tab & name everything the way you want, repeat the
>> folder icon save procedure & name it "88k Outsies" or what have
>> you... THEN reclock to 44.1k. At this point, of course, your
>> lightpipe i/o's will collapse down & you can refresh the i/o's
>> under "Devices/Device Setup", then look down the list for VST
>> inputs & VST outputs - go to each one & hit "reset". (in fact,
>> you may want to do this even before you do the 88.2k i/o
>> template - i keep forgetting you're not exclusively on 88.2, so
>> you may have to reset/refresh before you start, just to make
>> sure you're seeing all of them).
>>=20
>> OK, once you've done that at 44.1k, start naming your i/o's for
>> the 44.1k versions of what you just saved, as described
>> above... then save one for the Input side & one under the
>> output tab, each with it's own name, appropriately.
>>=20
>> And there you have it!!!!!!!!! No muss, no fuss, no dual-
>> partitioning needed. ALI you'll have to make sure you do is to
>> refresh your VST connections each time you go between a 44.1k
>> project & an 88.2k one, then pull up the your saved i/o
>> templates!
>>=20
>> Neil
>>=20
>>=20
>>=20
>>=20
>> "Deej" <noway@jose.org> wrote:

```

>>>
>>>
>>>Wait!!!.....I'm not talking about the I/O assignments, I'm talking =
>about
>> =3D
>>>I/O names and whether or not they are hidden or not in the device =3D
>>>manager.....oh..nevermind.....
>
><!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
><HTML><HEAD>
><META http-equiv=3DContent-Type content=3D"text/html; =
>charset=3Diso-8859-1">
><META content=3D"MSHTML 6.00.6000.16587" name=3DGENERATOR>
><STYLE></STYLE>
></HEAD>
><BODY>
><DIV><FONT face=3DArial size=3D2>Hey Neil,</FONT></DIV>

><DIV><FONT face=3DArial size=3D2>I get what you're saying and I do use =
>the presets,=20
>but what I'm talking about is completely different. the =

>what I'm unhappy about:</FONT></DIV>

><DIV><FONT face=3DArial size=3D2>Navigate to:</FONT></DIV>

><DIV><FONT face=3DArial size=3D2>Devices>Device Setup>VST Audio =
>System>ASIO=20
>Hammerfall DSP</FONT></DIV>

><DIV><FONT face=3DArial size=3D2>On the right is the screen where you =
>choose to=20
>enable/disable direct monitoring. Below that is where the I/O ports are
=
>shown.=20
>the port system name is shown and to it's right you can name the =

>44.1=20
>template. No matter what template you save, the names in the =
><EM><STRONG>Show=20
>As</STRONG></EM> column and any ports you might want to choose to hide =
>because=20
>you aren't using them in 44.1 mode (MF ADAT ports 4-8 and and MADI ports
=
>33-64=20
>when using 88.2 and MADI ADAT ports 9-16 and 25 through 32 when using =

```

>44.1 in my=20
>particular situation) will carry over no matter what the template/sample
=
>rate=20

>ports=20
>showing up that I want to hide because they are of no possible use to =
>me, they=20
>have double names because some of them correlate to totally different =
>ports at=20
>88.2 and they just tend to clutter up the I/O configurations that I want
=
>to be=20
>able to create quickly.</DIV>

><DIV>Using a dual boot system, one strictly
=
>for 44.1 and=20
>the other for 88.2 would solve this completely....and it's the only way
=
>I can=20
>see that would do this.</DIV>

><DIV>Regards,</DIV>

><DIV>Deej</DIV>

><DIV>"Neil" <<A=20
>href=3D"mailto:OIUOIU@OIU.com"><FONT face=3DArial=20
>size=3D2>OIUOIU@OIU.com> wrote =
>in message=20
><FONT face=3DArial=20
>size=3D2>news:476db9d5\$1@linux<FONT face=3DArial=20
>size=3D2>...</DIV>>
> OK, =
>look, here's=20
>the way you do it... if you go to the topbar
> menu & select:=20
>Devices/VST Connections & select
> either the "Inputs" or =
>"Outputs"=20
>tab, you'll se a little teeny
> black window in the upper area =
>that says=20
>"presets"; it has
> several stock presets that you can load using =
>the=20
>drop-down
> arrow on the right-hand side of that, but what you =
>want to=20
>do
> is note the little - even teensier - folder icon with the=20
>plus
> sign, just to the right of the little presets =

>windowette...
>=20
 >THAT's how you save your i/o preset templates.
>
> Make one =
 >for=20
 >88.2k first, ensuring that your clock is set to
> 88.2 so you see =
 >all the=20
 >lightpipe ports, name everything the
> way you want on the Input =
 >side=20
 >(tab), then click the little
> folder icon with the plus sign in =
 >it, and=20
 >save it as: "88k
> Insies" or whatever makes sense to you, then go =
 >over to=20
 >the
> Output tab & name everything the way you want, repeat=20
 >the
> folder icon save procedure & name it "88k Outsies" or =
 >what=20
 >have
> you... THEN reclock to 44.1k. At this point, of course,=20
 >your
> lightpipe i/o's will collapse down & you can refresh =
 >the=20
 >i/o's
> under "Devices/Device Setup", then look down the list for=20
 >VST
> inputs & VST outputs - go to each one & hit "reset". =
 >(in=20
 >fact,
> you may want to do this even before you do the 88.2k =
 >i/o
>=20
 >template - i keep forgetting you're not exclusively on 88.2, so
> =
 >you may=20
 >have to reset/refresh before you start, just to make
> sure you're =
 >seeing=20
 >all of them).
>
> OK, once you've done that at 44.1k, start =
 >naming=20
 >your i/o's for
> the 44.1k versions of what you just saved, as=20
 >described
> above... then save one for the Input side & one =
 >under=20
 >the
> output tab, each with it's own name, appropriately.
> =
 >
>=20

 >dual-
>=20
 >partitioning needed. All you'll have to make sure you do is to
> =
 >refresh=20
 >your VST connections each time you go between a 44.1k
> project =
 >& an=20
 >88.2k one, then pull up the your saved i/o
> templates!
> =
 >
>=20
 >Neil
>
>
>
>
> "Deej" <<A=20
 >href=3D"mailto:noway@jose.org"><FONT face=3DArial=20
 >size=3D2>noway@jose.org>=20
 >wrote:
>>
>>
>>Wait!!!.....I'm not talking =
 >about the=20
 >I/O assignments, I'm talking about
> =3D
>>I/O names and =
 >whether or=20

>not they are hidden or not in the device=20
>=3D
>>manager.....oh..nevermind.....</BODY></H=
>TML>
>
>

Subject: Re: my next fun endeavor - DeeJ, here's your answer
Posted by [Neil](#) on Mon, 24 Dec 2007 02:21:50 GMT
[View Forum Message](#) <> [Reply to Message](#)

Heck, I have no idea, then. Hey, did u get a chance to listen
to the Portico Tape Sim clip I posted?

Neil

"Deej" <noway@jose.org> wrote:

>
>"Neil" <OIUOIU@OIU.com> wrote in message news:476dfa44\$1@linux...
>>
>> DeeJ, but if you're clocked at 88.2k, those extra ports won't
>> even show up once you hit "reset" on your VST Inputs & Outputs.
>> I think this might be the issue in this case... you need to
>> refresh those i/o's & it'll detect the clockspeed & slice your
>> ADAT's in half - again, unless I'm just not understanding what
>> you're trying to accomplish.
>>
>> Neil
>
>
>No matter whether you refresh or not, the double names will have to be used

>and if you hide any unnecessary ports between #'s 1 & 32, in one or the

>other config, your physical I/O will not line up properly unless you go
back

>into the menu and reset them to be shown. It's a royal PITA.

>;o)

>

>>

>> "Deej" <noway@jose.org> wrote:

>>>

>>>

>>>Hey Neil,

>>>

>>>I get what you're saying and I do use the presets, but what I'm talking

>> =

>>>about is completely different. the following is what I'm unhappy about:

>>>

>>>Navigate to:

>>>

>>>Devices>Device Setup>VST Audio System>ASIO Hammerfall DSP

>>>

>>>On the right is the screen where you choose to enable/disable direct =

>>>monitoring. Below that is where the I/O ports are shown. the port system

>> =

>>>name is shown and to it's right you can name the port in the Show As =

>>>column. The Show As names cannot be saved in an 88.2 template and a =

>>>44.1 template. No matter what template you save, the names in the Show

=

>>>As column and any ports you might want to choose to hide because you =

>>>aren't using them in 44.1 mode (MF ADAT ports 4-8 and and MADI ports =

>>>33-64 when using 88.2 and MADI ADAT ports 9-16 and 25 through 32 when

=

>>>using 44.1 in my particular situation) will carry over no matter what

=

>>>the template/sample rate you save/use. Well, if I'm working at 44.1,

=

>>>I've got all these ports showing up that I want to hide because they are

>> =

>>>of no possible use to me, they have double names because some of them

=

>>>correlate to totally different ports at 88.2 and they just tend to =

>>>clutter up the I/O configurations that I want to be able to create =

>>>quickly.

>>>

>>>Using a dual boot system, one strictly for 44.1 and the other for 88.2

=

>>>would solve this completely....and it's the only way I can see that =

>>>would do this.

>>>

>>>Regards,

>>>

>>>Deej

>>>

>>>

>>>

>>>"Neil" <OIUOIU@OIU.com> wrote in message news:476db9d5\$1@linux...

>>>=20

>>>> OK, look, here's the way you do it... if you go to the topbar

>>>> menu & select: Devices/VST Connections & select

>>>> either the "Inputs" or "Outputs" tab, you'll se a little teeny

>>>> black window in the upper area that says "presets"; it has

>>>> several stock presets that you can load using the drop-down

>>>> arrow on the right-hand side of that, but what you want to do
>>>> is note the little - even teensier - folder icon with the plus
>>>> sign, just to the right of the little presets windowette...
>>>> THAT's how you save your i/o preset templates.
>>>>=20
>>>> Make one for 88.2k first, ensuring that your clock is set to
>>>> 88.2 so you see all the lightpipe ports, name everything the
>>>> way you want on the Input side (tab), then click the little
>>>> folder icon with the plus sign in it, and save it as: "88k
>>>> Insies" or whatever makes sense to you, then go over to the
>>>> Output tab & name everything the way you want, repeat the
>>>> folder icon save procedure & name it "88k Outsies" or what have
>>>> you... THEN reclock to 44.1k. At this point, of course, your
>>>> lightpipe i/o's will collapse down & you can refresh the i/o's
>>>> under "Devices/Device Setup", then look down the list for VST
>>>> inputs & VST outputs - go to each one & hit "reset". (in fact,
>>>> you may want to do this even before you do the 88.2k i/o
>>>> template - i keep forgetting you're not exclusively on 88.2, so
>>>> you may have to reset/refresh before you start, just to make
>>>> sure you're seeing all of them).
>>>>=20
>>>> OK, once you've done that at 44.1k, start naming your i/o's for
>>>> the 44.1k versions of what you just saved, as described
>>>> above... then save one for the Input side & one under the
>>>> output tab, each with it's own name, appropriately.
>>>>=20
>>>> And there you have it!!!!!!!!! No muss, no fuss, no dual-
>>>> partitioning needed. ALL you'll have to make sure you do is to
>>>> refresh your VST connections each time you go between a 44.1k
>>>> project & an 88.2k one, then pull up the your saved i/o
>>>> templates!
>>>>=20
>>>> Neil
>>>>=20
>>>>=20
>>>>=20
>>>>=20
>>>>=20
>>>> "Deej" <noway@jose.org> wrote:
>>>>>
>>>>>
>>>>>Wait!!!!.....I'm not talking about the I/O assignments, I'm talking =
>>>>about
>>>>=3D
>>>>>I/O names and whether or not they are hidden or not in the device =3D
>>>>>manager.....oh..nevermind.....
>>>>
>>>><!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
>>>><HTML><HEAD>

```

>>><META http-equiv=3DContent-Type content=3D"text/html; =
>>>charset=3Diso-8859-1">
>>><META content=3D"MSHTML 6.00.6000.16587" name=3DGENERATOR>
>>><STYLE></STYLE>
>>></HEAD>
>>><BODY>
>>><DIV><FONT face=3DArial size=3D2>Hey Neil,</FONT></DIV>
>>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>>><DIV><FONT face=3DArial size=3D2>I get what you're saying and I do use
=
>>>the presets,=20
>>>but what I'm talking about is completely different. the =
>>>following is=20
>>>what I'm unhappy about:</FONT></DIV>
>>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>>><DIV><FONT face=3DArial size=3D2>Navigate to:</FONT></DIV>
>>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>>><DIV><FONT face=3DArial size=3D2>Devices>Device Setup>VST Audio =
>>>System>ASIO=20
>>>Hammerfall DSP</FONT></DIV>
>>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>>><DIV><FONT face=3DArial size=3D2>On the right is the screen where you
=
>>>choose to=20
>>>enable/disable direct monitoring. Below that is where the I/O ports are
>> =
>>>shown.=20
>>>the port system name is shown and to it's right you can name the =
>>>port in=20
>>>the <STRONG>S<EM>how As</EM></STRONG> column. The <EM><STRONG>Show=20
>>>As</STRONG></EM> names cannot be saved in an 88.2 template and a =
>>>44.1=20
>>>template. No matter what template you save, the names in the =
>>><EM><STRONG>Show=20
>>>As</STRONG></EM> column and any ports you might want to choose to hide
=
>>>because=20
>>>you aren't using them in 44.1 mode (MF ADAT ports 4-8 and and MADI ports
>> =
>>>33-64=20
>>>when using 88.2 and MADI ADAT ports 9-16 and 25 through 32 when using
=
>>>44.1 in my=20
>>>particular situation) will carry over no matter what the template/sample
>> =
>>>rate=20
>>>you save/use. Well, if I'm working at 44.1, I've got all these =
>>>ports=20

```

```

>>>showing up that I want to hide because they are of no possible use to
=
>>>me, they=20
>>>have double names because some of them correlate to totally different
=
>>>ports at=20
>>>88.2 and they just tend to clutter up the I/O configurations that I want
>> =
>>>to be=20
>>>able to create quickly.</FONT></DIV>
>>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>>><DIV><FONT face=3DArial size=3D2>Using a dual boot system, one strictly
>> =
>>>for 44.1 and=20
>>>the other for 88.2 would solve this completely....and it's the only way
>> =
>>>I can=20
>>>see that would do this.</FONT></DIV>
>>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>>><DIV><FONT face=3DArial size=3D2>Regards,</FONT></DIV>
>>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>>><DIV><FONT face=3DArial size=3D2>Deej</FONT></DIV>
>>><DIV> </DIV>
>>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>>><DIV><FONT face=3DArial size=3D2></FONT> </DIV>
>>><DIV><FONT face=3DArial size=3D2>"Neil" </FONT><A=20
>>>href=3D"mailto:OIUOIU@OIU.com"><FONT face=3DArial=20
>>>size=3D2>OIUOIU@OIU.com</FONT></A><FONT face=3DArial size=3D2>> wrote
=
>>>in message=20
>>></FONT><A href=3D"news:476db9d5$1@linux"><FONT face=3DArial=20
>>>size=3D2>news:476db9d5$1@linux</FONT></A><FONT face=3DArial=20
>>>size=3D2>...</FONT></DIV><FONT face=3DArial size=3D2>> <BR>> OK, =
>>>look, here's=20
>>>the way you do it... if you go to the topbar<BR>> menu & select:=20
>>>Devices/VST Connections & select<BR>> either the "Inputs" or =
>>>"Outputs"=20
>>>tab, you'll se a little teeny<BR>> black window in the upper area =
>>>that says=20
>>>"presets"; it has<BR>> several stock presets that you can load using =
>>>the=20
>>>drop-down<BR>> arrow on the right-hand side of that, but what you =
>>>want to=20
>>>do<BR>> is note the little - even teensier - folder icon with the=20
>>>plus<BR>> sign, just to the right of the little presets =
>>>windowette...<BR>>=20
>>>THAT's how you save your i/o preset templates.<BR>> <BR>> Make one =
>>>for=20

```

>>>88.2k first, ensuring that your clock is set to
> 88.2 so you see =
 >>>all the=20
 >>>lightpipe ports, name everything the
> way you want on the Input =
 >>>side=20
 >>>(tab), then click the little
> folder icon with the plus sign in =
 >>>it, and=20
 >>>save it as: "88k
> Insies" or whatever makes sense to you, then go
 =
 >>>over to=20
 >>>the
> Output tab & name everything the way you want, repeat=20
 >>>the
> folder icon save procedure & name it "88k Outsies" or =
 >>>what=20
 >>>have
> you... THEN reclock to 44.1k. At this point, of course,=20
 >>>your
> lightpipe i/o's will collapse down & you can refresh =
 >>>the=20
 >>>i/o's
> under "Devices/Device Setup", then look down the list for=20
 >>>VST
> inputs & VST outputs - go to each one & hit "reset". =
 >>>(in=20
 >>>fact,
> you may want to do this even before you do the 88.2k =
 >>>i/o
>=20
 >>>template - i keep forgetting you're not exclusively on 88.2, so
> =
 >>>you may=20
 >>>have to reset/refresh before you start, just to make
> sure you're
 =
 >>>seeing=20
 >>>all of them).
>
> OK, once you've done that at 44.1k, start =
 >>>naming=20
 >>>your i/o's for
> the 44.1k versions of what you just saved, as=20
 >>>described
> above... then save one for the Input side & one =
 >>>under=20
 >>>the
> output tab, each with it's own name, appropriately.
> =
 >>>
>=20
 >>>And there you have it!!!!!!!!! No muss, no fuss, no =
 >>>dual-
>=20
 >>>partitioning needed. All you'll have to make sure you do is to
> =
 >>>refresh=20
 >>>your VST connections each time you go between a 44.1k
> project =
 >>>& an=20
 >>>88.2k one, then pull up the your saved i/o
> templates!
> =
 >>>
>=20
 >>>Neil
>
>
>
>
> "Deej" <A=20
 >>>href=3D"mailto:noway@jose.org"><FONT face=3DArial=20
 >>>size=3D2>noway@jose.org>=20
 >>>wrote:
>>
>>
>>Wait!!!.....I'm not talking =
 >>>about the=20
 >>>I/O assignments, I'm talking about
> =3D
>>I/O names and =
 >>>whether or=20
 >>>not they are hidden or not in the device=20

>>>=3D
>>manager.....oh..nevermind.....</BODY></H=
>>>TML>
>>>
>>>
>>
>
>

Subject: Re: my next fun endeavor - DeeJ, here's your answer
Posted by [Deej](#) on Mon, 24 Dec 2007 04:55:04 GMT
[View Forum Message](#) <> [Reply to Message](#)

"Neil" <OIUOIU@OIU.com> wrote in message news:476f09ae\$1@linux...
>
> Heck, I have no idea, then. Hey, did u get a chance to listen
> to the Portico Tape Sim clip I posted?
>
> Neil

Yep!!! Sounds very familiar ;o) You gonna keep it??

Subject: Re: my next fun endeavor - DeeJ, here's your answer
Posted by [Neil](#) on Mon, 24 Dec 2007 16:29:28 GMT
[View Forum Message](#) <> [Reply to Message](#)

"Deej" <noway@jose.org> wrote:
>
>"Neil" <OIUOIU@OIU.com> wrote in message news:476f09ae\$1@linux...
>>
>> Heck, I have no idea, then. Hey, did u get a chance to listen
>> to the Portico Tape Sim clip I posted?
>>
>> Neil
>
>
>Yep!!! Sounds very familiar ;o) You gonna keep it??

Absotively!

:)

Subject: Re: my next fun endeavor - DeeJ, here's your answer

Posted by [Deej](#) on Mon, 24 Dec 2007 18:36:35 GMT

[View Forum Message](#) <> [Reply to Message](#)

"Neil" <OIUIU@IOU.com> wrote in message news:476fd058\$1@linux...
>
> "Deej" <noway@jose.org> wrote:
>>
>>"Neil" <OIUIU@IOU.com> wrote in message news:476f09ae\$1@linux...
>>>
>>> Heck, I have no idea, then. Hey, did u get a chance to listen
>>> to the Portico Tape Sim clip I posted?
>>>
>>> Neil
>>
>>
>>Yep!!! Sounds very familiar ;o) You gonna keep it??
>
> Absotively!
>
> :)
>

Picture me shaking my finger and saying see???..SEE????

sheesh!!!! it only took ya' a year to join the club.

:oD

Merry Christmas buddy,

Deej

Subject: Re: my next fun endeavor - Deej, here's your answer

Posted by [rick](#) on Tue, 25 Dec 2007 10:18:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

aussies are sworn to secrecy in the whole time continuum thing...i
know cuz i've tried...alas to no avail...sigh
