Subject: Optimum Stereo Signal Recording with the Jecklin Disk Posted by excelar on Mon, 24 Oct 2005 06:30:08 GMT

View Forum Message <> Reply to Message

he audio part yet, but Cubase and Paris look like there staying locked via adat 9 pin sync. rod

"Rod Lincoln" <rlincoln@kc.rr.com

Subject: Re: Optimum Stereo Signal Recording with the Jecklin Disk Posted by Deej [1] on Mon, 24 Oct 2005 14:57:27 GMT

View Forum Message <> Reply to Message

itting oiverload (in my most recent imx.

this

- > >was around -2.2dB, then using NoLimit for making up the gain and then a
- > >little more.....usually a threshold setting of
- >> -4.4dB. This yields a sound which is, to my ears, sorta like using

> a

> >nicely colored bus compressor like a VariMu.

> >

> >Deej

> >

- > > "cujo" < chris@nospamapplemanstudio.com > wrote in message
- > >news:435bfd41\$1@linux...

> >>

> >>

- >>> What type os setting do you use?
- >>> I can;t seem to trust Nolimit on the Mix bus as it always gives me a

Subject: Re: Optimum Stereo Signal Recording with the Jecklin Disk Posted by Deej [1] on Mon, 24 Oct 2005 15:00:09 GMT

View Forum Message <> Reply to Message

```
>>> >news:435bf479$1@linux...
>>> >> Do most users prefer to mix in paris with or without
>>> >> the eds
Subject: Re: Optimum Stereo Signal Recording with the Jecklin Disk
Posted by EK Sound on Mon, 24 Oct 2005 15:38:56 GMT
View Forum Message <> Reply to Message
stereo comp across the mix buss?
> >> >
> >> >
> >
> >
>Nope. I'll send you an MP3 if you want to hear the results. If you've got an
editor that can open MP3's you can see for yourself.
Deej
"cujo" <chris@applemanstudio.com> wrote in message news:435d0c5b$1@linux...
>
>
> And this does not give you a block wave form?
>
>
> "DJ" <animix_spam-this-ahole_@animas.net> wrote:
> >I'm mixing with the channel faders fairly hot, the submix faders down to
> > where the submix isn't guite hitting oiverload (in my most recent imx.
> >was around -2.2dB, then using NoLimit for making up the gain and then a
> >little more.....usually a threshold setting of
> >
Subject: Re: Optimum Stereo Signal Recording with the Jecklin Disk
Posted by excelar on Mon, 24 Oct 2005 18:14:02 GMT
View Forum Message <> Reply to Message
g the
adat 9 pin for syncing with other audio cards, at least for me, just not
for syncing with an actual adat. For that I still have to use ME.
Rod
"Rod Lincoln" <rlincoln@kc.rr.com> wrote:
>Yeah
```

```
>"Aaron Allen" <nospam@not here.dude> wrote:
>>You guys are getting this in XP?
>>AA
>>
>>
>>"Rod Lincoln" <rlincoln@kc.rr.com> wrote in message news:435d0f6d$1@linux...
>>> OK I just verified sample accurate sync between Paris and SX3 for 10:00,
>>> SO
>>> I'm happy. This is using the cubase metronome.
>>> Flip phase and I get total cancellation..100%
>>> Next step is the audio. I seem to remember you having to set up RME as
>the
>>> master clock to avoid clicks and pops...is that right??
>>> rod
>>> "DJ" <animix spam-this-ahole @animas.net> wrote:
>>>Looks like you've got it. Occassionally, I'll get some stubbornness from
```

Subject: Re: Optimum Stereo Signal Recording with the Jecklin Disk Posted by Dale on Mon, 24 Oct 2005 20:30:46 GMT

View Forum Message <> Reply to Message

```
@linux...
>>
>> Do most users prefer to mix in paris with or without
>> the eds stereo comp across the mix buss?
>
>>Background singing on a Grammy album is a great honor, but being a writer
>is a much bigger honor, and a very small group. Congrats again.
>Gene.
>
```

Can't argue with that!

```
Thanks Gene"cujo" <chris@applemanstudio.com> wrote: >
>
>
>You do mostly R&B? correct?
>
```

No, our work is quite diverse. Currently, we are working allot on projects that are Pop/Rock driven..even adding a tinge of country.

TyroneYou bypass Pace by using the anti pace software.

Martin Harrington www.lendanear-sound.com

"tonehouse" <zmcleod@comcast.net> wrote in message news:

Subject: Re: Optimum Stereo Signal Recording with the Jecklin Disk Posted by DC on Mon, 24 Oct 2005 21:26:58 GMT

View Forum Message <> Reply to Message

ning here. I've had 3 drives today report that

- > > they only 20 gig drives when they were actually 40 or 80 gig. This all happened
- > > when I put them in my Cubase comp(I have matching removable trays in both
- > > comps)Both comps run win xp.
- > > (my cubase comp has a DVD burner...I was attempting to archive some files.
- > > these are all removable audio drives, not system drives, and are all formatted
- > > fat 32.)
- >> When I put it back in the Paris comp, it still reports the wrong size and
- > > some of the files say they're corrupt.
- > > When I look at the disks under the management window it show's there correct
- > > size, but looks like they got repartitioned and there's a large unallocated
- > > partition there.
- > > So far I havn't lost anything (I don't think) as I am pretty good about backing
- >> up. But I don't want to stick any drives in the Cubase comp.
- > > New changes to the comp are as follows. (all last night or today)
- > > 1.flashed the bios to the most recent (gigabyte K8V Triton)
- > >
- > > 2.installed and updated RME 9652 (after uninstalling Dakota Frontier)
- > >
- > > 3.installed and updated Cubase SX 3 (retail)
- > >
- >> 4. That's about it. While I was updating the drivers via the net
- > > (temporary Lan connection) I inadvertantly had automatic updates turned on
- > > and Windows updated a bunch of "Hotfix" security updates. (this comp is not
- > > normally on the net and I have been running XP Home SP1 on it)
- > >

- > > 5. Last night I got a "Windows has recovered from a serious error" during
- > > the beggining of installing cubase, so I re-ghost