

---

Subject: Paris won't start because of hardware  
Posted by [Tom Bruhl](#) on Wed, 04 Jul 2007 16:41:26 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

This is a multi-part message in MIME format.

-----=\_NextPart\_000\_00C9\_01C7BE38.A2B78290  
Content-Type: text/plain;  
charset="iso-8859-1"  
Content-Transfer-Encoding: quoted-printable

I was more stable than ever before with Lucid WC,  
2 MECs and one 442. Never crashed once. I added  
a third MEC and that was okay but it's in/outs weren't  
functional. I tried it in a different position and ever since  
then I get this after Paris has gotten to the EDS/DX effects  
part of the start up.

Unhandled Exception:c00000005  
at address: 77c35ea

I tried removing the last MEC and putting it in the last working =  
position.  
All I get is this error and can't boot up Paris.

Last working configuration:  
Submix A MEC  
Submix B 442  
Submix C MEC (no working audio)  
Submix E MEC

I tried swapping hardware between Submix B and C and that's when the =  
trouble began.  
I also reseated the eds cards and their cables.

Is it possible it's an effect? I have added nothing new in months and =  
it was very stable.  
Maybe a defective default project?

I'll try another one to boot from that happens to be at 48k.

Tips graciously accepted,  
Tom

I choose Polesoft Lockspam to fight spam, and you?  
<http://www.polesoft.com/refer.html>

-----=\_NextPart\_000\_00C9\_01C7BE38.A2B78290

Content-Type: text/html;  
charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.2800.1400" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT face=3DArial size=3D2>I was more stable than ever before with =
Lucid=20
WC,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>2 MECs and one 442.&nbsp; Never crashed =
once.&nbsp;=20
I added</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>a third MEC and that was okay but it's =
in/outs=20
weren't</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>functional.&nbsp; I tried it in a =
different=20
position and ever since</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>then I get this after Paris has gotten =
to the=20
EDS/DX effects</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>part of the start up.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>Unhandled =
Exception:c00000005</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>at address: 77c35ea</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>I tried removing the last MEC and =
putting it in the=20
last working position.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>All I get is this error and can't boot =
up=20
Paris.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>Last working =
configuration:</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Submix A MEC</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Submix B 442</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Submix C MEC (no working =
audio)</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Submix E MEC</FONT></DIV>
```

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>I tried swapping hardware&nbsp;</FONT></DIV>  
Submix B and=20  
C and that's when the trouble began.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>I also reseated the eds cards and their =  
cables.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Is it possible it's an effect?&nbsp;</FONT></DIV>  
I =  
have added=20  
nothing new in months and it was very stable.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Maybe&nbsp;</FONT></DIV>  
a defective default=20  
project?</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>I'll try another one to boot from that =  
happens to=20  
be at 48k.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Tips graciously accepted,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Tom</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT size=3D2><BR><BR>I choose Polesoft Lockspam to fight spam, =  
and=20  
you?<BR><A=20  
href=3D"http://www.polesoft.com/refer.html">http://www.polesoft.com/refer=  
..html</A>&nbsp;&nbsp;&nbsp;</FONT></DIV></BODY ></HTML>

-----=\_NextPart\_000\_00C9\_01C7BE38.A2B78290--

---

---

Subject: Re: Paris won't start because of hardware  
Posted by [DJ](#) on Wed, 04 Jul 2007 17:05:17 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

This is a multi-part message in MIME format.

-----=\_NextPart\_000\_0313\_01C7BE2B.34E8ED60  
Content-Type: text/plain;  
charset="iso-8859-1"  
Content-Transfer-Encoding: quoted-printable

Tom,

After you have edited your Pairs .cfg file to add the line =  
"UseHouseSync=3D1" (no quotes), save this and reboot your computer.

1. Get the 442 completely out of the equation. Forget about using it =  
ever again in a multicard setup. It's just going to make your life =

miserable.

2. Connect the three MECs to the Lucid clock outputs with cables of equal length, connect the MEC on card A to clock output #1, Mec on card B to output #2, etc.....I don't know why, but this is what worked for me.....then ((very important) set the Lucid clock to 44.1KHz = sample rate (if that's what you're using)

3. Boot Paris from the Paris.exe in the C:\Program files\EMU\Paris folder

4. Set the project to 48KHz and save it back to the same folder under the name "Default Project" (no quotes).

5. Save it again to the desktop under the same name.

6. Reboot your computer and launch Paris from the icon on your desktop. Do not ever change the sample rate of your Default Project. Leave it at 48KHz. You will be able to open all of your old 44.1 projects or create new 44.1 projects from this one once Paris has booted and fully initialized.

Deej

"Tom Bruhl" <arpeggio@comcast.net> wrote in message = news:468bceee@linux...

I was more stable than ever before with Lucid WC, 2 MECs and one 442. Never crashed once. I added a third MEC and that was okay but it's in/out's weren't functional. I tried it in a different position and ever since then I get this after Paris has gotten to the EDS/DX effects part of the start up.

Unhandled Exception:c00000005  
at address: 77c35ea

I tried removing the last MEC and putting it in the last working position.

All I get is this error and can't boot up Paris.

Last working configuration:  
Submix A MEC  
Submix B 442  
Submix C MEC (no working audio)  
Submix E MEC

I tried swapping hardware between Submix B and C and that's when the trouble began.

I also reseated the eds cards and their cables.

Is it possible it's an effect? I have added nothing new in months and = it was very stable.

Maybe a defective default project?

I'll try another one to boot from that happens to be at 48k.

Tips graciously accepted,  
Tom

I choose Polesoft Lockspam to fight spam, and you?

<http://www.polesoft.com/refer.html>

-----=\_NextPart\_000\_0313\_01C7BE2B.34E8ED60

Content-Type: text/html;

charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.6000.16414" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT face=3DArial size=3D2>Tom,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>After you have edited your Pairs .cfg =
file to add=20
the line "UseHouseSync=3D1" (no quotes), save this and reboot your=20
computer.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>1. Get the 442 completely out of the =
equation.=20
Forget about using it ever again in a multocard setup. It's just going =
to make=20
your life miserable.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>2. Connect the three MECs to the Lucid =
clock=20
outputs with cables of equal length, connect the MEC on card A to clock =
output=20
#1, Mec on card B to output #2, etc.....I don't know why, but this =
is what=20
worked for me.....then ((very important) set the Lucid clock to =
```



gotten to the=20  
EDS/DX effects</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>part of the start up.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Unhandled =  
Exception:c00000005</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>at address: 77c35ea</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>I tried removing the last MEC and =  
putting it in=20  
the last working position.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>All I get is this error and can't =  
boot up=20  
Paris.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Last working =  
configuration:</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Submix A MEC</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Submix B 442</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Submix C MEC (no working =  
audio)</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Submix E MEC</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>I tried swapping =  
hardware&nbsp;</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>between Submix B=20  
and C and that's when the trouble began.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>I also reseated the eds cards and =  
their=20  
cables.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Is it possible it's an effect?&nbsp;</FONT> =  
I have added=20  
nothing new in months and it was very stable.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Maybe&nbsp;</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>a defective default=20  
project?</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>I'll try another one to boot from =  
that happens to=20  
be at 48k.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Tips graciously =  
accepted,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Tom</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT size=3D2><BR><BR>I choose Polesoft Lockspam to fight spam, =  
and=20  
you?<BR><A=20  
=







6. Reboot your computer and launch Paris from the icon on your =  
desktop. Do not ever change the sample rate of your Default Project. =  
Leave it at 48KHz. You will be able to open all of your old 44.1 =  
projects or create new 44.1 projects from this one once Paris has booted =  
and fully initialized.

Deej

"Tom Bruhl" <arpeggio@comcast.net> wrote in message =  
news:468bceee@linux...

I was more stable than ever before with Lucid WC,  
2 MECs and one 442. Never crashed once. I added  
a third MEC and that was okay but it's in/outs weren't  
functional. I tried it in a different position and ever since  
then I get this after Paris has gotten to the EDS/DX effects  
part of the start up.

Unhandled Exception:c00000005  
at address: 77c35ea

I tried removing the last MEC and putting it in the last working =  
position.

All I get is this error and can't boot up Paris.

Last working configuration:

Submix A MEC

Submix B 442

Submix C MEC (no working audio)

Submix E MEC

I tried swapping hardware between Submix B and C and that's when the =  
trouble began.

I also reseated the eds cards and their cables.

Is it possible it's an effect? I have added nothing new in months =  
and it was very stable.

Maybe a defective default project?

I'll try another one to boot from that happens to be at 48k.

Tips graciously accepted,

Tom

I choose Polesoft Lockspam to fight spam, and you?  
<http://www.polesoft.com/refer.html>

-----=\_NextPart\_000\_0009\_01C7BE3D.7F033E70

Content-Type: text/html;  
charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.2800.1400" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT face=3DArial size=3D2>Hey DJ,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>I've been doing everything here except =
no=20
442.&nbsp; I'll give that a whirl.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Does that error look like a hardware =
issue to=20
you?</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Tom</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV>&nbsp;</DIV>
<BLOCKQUOTE dir=3Dltr=20
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">
  <DIV>"DJ" &lt;animix _ at _ animas _ dot _ net&gt; wrote in message <A =
href=3D"news:468bd4bf@linux">news:468bd4bf@linux</A>...</DIV>
  <DIV><FONT face=3DArial size=3D2>Tom,</FONT></DIV>
  <DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
  <DIV><FONT face=3DArial size=3D2>After you have edited your Pairs .cfg =
file to add=20
  the line "UseHouseSync=3D1" (no quotes), save this and reboot your=20
  computer.</FONT></DIV>
  <DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
  <DIV><FONT face=3DArial size=3D2>1. Get the 442 completely out of the =
equation.=20
  Forget about using it ever again in a multcard setup. It's just going =
to make=20
  your life miserable.</FONT></DIV>
  <DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
  <DIV><FONT face=3DArial size=3D2>2. Connect the three MECs to the =
Lucid clock=20
  outputs with cables of equal length, connect the MEC on card A to =
clock output=20
  #1, Mec on card B to output #2, etc.....I don't know why, but this =
is what=20
```

worked for me.....then ((very important) set the Lucid clock to =  
44.1KHz=20  
sample rate (if that's what you're using)</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>3. Boot Paris from the Paris.exe in =  
the C\Program=20  
files\EMU\Paris folder</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>4. Set the project to 48KHz and save =  
it back to=20  
the same folder under the name "Default Project" (no =  
quotes).</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>5. Save it again to the desktop under =  
the same=20  
name.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>6.&nbsp;</FONT>&nbsp;</DIV>Reboot your computer and =  
launch Paris=20  
from the icon on your desktop. Do not ever change the sample rate of =  
your=20  
Default Project. Leave it at 48KHz. You will be able to open all of =  
your old=20  
44.1 projects or create new 44.1 projects from this one once Paris has =  
booted=20  
and fully initialized.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Deej</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<BLOCKQUOTE dir=3Dltr=20  
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =  
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">  
<DIV>"Tom Bruhl" &lt;<A=20  
href=3D"mailto:arpeggio@comcast.net">arpeggio@comcast.net</A>&gt; =  
wrote in=20  
message <A =  
href=3D"news:468bceee@linux">news:468bceee@linux</A>...</DIV>  
<DIV><FONT face=3DArial size=3D2>I was more stable than ever before =  
with Lucid=20  
WC,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>2 MECs and one 442.&nbsp;</FONT>&nbsp;</DIV>Never =  
crashed=20  
once.&nbsp;</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>a third MEC and that was okay but =  
it's in/outs=20  
weren't</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>functional.&nbsp;</FONT>&nbsp;</DIV>I tried it in a =

different=20

position and ever since</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>then I get this after Paris has =  
gotten to the=20

EDS/DX effects</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>part of the start up.</FONT></DIV>

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>

<DIV><FONT face=3DArial size=3D2>Unhandled =

Exception:c00000005</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>at address: 77c35ea</FONT></DIV>

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>

<DIV><FONT face=3DArial size=3D2>I tried removing the last MEC and =  
putting it in=20

the last working position.</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>All I get is this error and can't =  
boot up=20

Paris.</FONT></DIV>

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>

<DIV><FONT face=3DArial size=3D2>Last working =  
configuration:</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>Submix A MEC</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>Submix B 442</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>Submix C MEC (no working =  
audio)</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>Submix E MEC</FONT></DIV>

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>

<DIV><FONT face=3DArial size=3D2>I tried swapping =  
hardware&nbsp;</FONT></DIV>

between Submix B=20  
and C and that's when the trouble began.</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>I also reseated the eds cards and =  
their=20

cables.</FONT></DIV>

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>

<DIV><FONT face=3DArial size=3D2>Is it possible it's an =  
effect?&nbsp;</FONT></DIV>

I have=20  
added nothing new in months and it was very stable.</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>Maybe&nbsp;</FONT></DIV>

a defective default=20  
project?</FONT></DIV>

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>

<DIV><FONT face=3DArial size=3D2>I'll try another one to boot from =  
that happens=20

to be at 48k.</FONT></DIV>

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>

<DIV><FONT face=3DArial size=3D2>Tips graciously =  
accepted,</FONT></DIV>

<DIV><FONT face=3DArial size=3D2>Tom</FONT></DIV>

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>

<DIV><FONT size=3D2><BR><BR>I choose Polesoft Lockspam to fight =

spam, and=20

you?<BR><A=20

=

href=3D"http://www.polesoft.com/refer.html">http://www.polesoft.com/refer=

..html</A>&nbsp;.&nbsp;.&nbsp;.</FONT></DIV></BLOCKQUOTE ></BLOCKQUOTE></BODY>=  
</HTML>

-----=\_NextPart\_000\_0009\_01C7BE3D.7F033E70--

---

---

Subject: Re: Paris won't start because of hardware

Posted by [DJ](#) on Wed, 04 Jul 2007 17:29:07 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

This is a multi-part message in MIME format.

-----=\_NextPart\_000\_0367\_01C7BE2E.88FEEE10

Content-Type: text/plain;

charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

Tom,

It looks like a "having a 442 in a multiMEC setup" issue. If removing =  
the 442 and setting up things exactly as I described doesn't work, =  
remove the third MEC (the one I sen you) and try your original =  
configuration again. That MEC was working perfectly as MEC #3 in a x 4 =  
MEC Paris rig before I tore it down. All I/O (including the clock I/O =  
were functioning perfectly. You do have the MEC BNC outputs terminated =  
with 75ohm caps, don't you?

Deej

"Tom Bruhl" <arpeggio@comcast.net> wrote in message =  
news:468bd715@linux...

Hey DJ,

I've been doing everything here except no 442. I'll give that a =  
whirl.

Does that error look like a hardware issue to you?

Tom

"DJ" <animix \_ at \_ animas \_ dot \_ net> wrote in message =  
news:468bd4bf@linux...

Tom,

After you have edited your Pairs .cfg file to add the line =  
"UseHouseSync=3D1" (no quotes), save this and reboot your computer.

1. Get the 442 completely out of the equation. Forget about using it =  
ever again in a multiscard setup. It's just going to make your life =  
miserable.

2. Connect the three MECs to the Lucid clock outputs with cables of =  
equal length, connect the MEC on card A to clock output #1, Mec on card =  
B to output #2, etc.....I don't know why, but this is what worked =  
for me.....then ((very important) set the Lucid clock to 44.1KHz =  
sample rate (if that's what you're using)

3. Boot Paris from the Paris.exe in the C:\Program files\EMU\Paris =  
folder

4. Set the project to 48KHz and save it back to the same folder =  
under the name "Default Project" (no quotes).

5. Save it again to the desktop under the same name.

6. Reboot your computer and launch Paris from the icon on your =  
desktop. Do not ever change the sample rate of your Default Project. =  
Leave it at 48KHz. You will be able to open all of your old 44.1 =  
projects or create new 44.1 projects from this one once Paris has booted =  
and fully initialized.

Deej

"Tom Bruhl" <arpeggio@comcast.net> wrote in message =  
news:468bceee@linux...

I was more stable than ever before with Lucid WC,  
2 MECs and one 442. Never crashed once. I added  
a third MEC and that was okay but it's in/outs weren't  
functional. I tried it in a different position and ever since  
then I get this after Paris has gotten to the EDS/DX effects  
part of the start up.

Unhandled Exception:c0000005  
at address: 77c35ea

I tried removing the last MEC and putting it in the last working =  
position.

All I get is this error and can't boot up Paris.

Last working configuration:  
Submix A MEC

Submix B 442  
Submix C MEC (no working audio)  
Submix E MEC

I tried swapping hardware between Submix B and C and that's when =  
the trouble began.

I also reseated the eds cards and their cables.

Is it possible it's an effect? I have added nothing new in months =  
and it was very stable.

Maybe a defective default project?

I'll try another one to boot from that happens to be at 48k.

Tips graciously accepted,  
Tom

I choose Polesoft Lockspam to fight spam, and you?

<http://www.polesoft.com/refer.html>

-----=\_NextPart\_000\_0367\_01C7BE2E.88FEEE10

Content-Type: text/html;

charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.6000.16414" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT face=3DArial size=3D2>Tom,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>It looks like a "having a 442 in a =
multiMEC setup"=20
issue. If removing the 442 and setting up things exactly as I described =
doesn't=20
work, remove the third MEC (the one I sen you) and try your original=20
configuration again. That MEC was working perfectly as MEC #3 in a x 4 =
MEC Paris=20
rig before I tore it down. All I/O (including the clock I/O were =
functioning=20
perfectly. You do have the MEC BNC outputs terminated with 75ohm caps, =
don't=20
you?</FONT></DIV>
```



<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Deej</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<BLOCKQUOTE dir=3Dltr=20  
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =  
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">  
<DIV>"Tom Bruhl" &lt;<A=20  
href=3D"mailto:arpeggio@comcast.net">arpeggio@comcast.net</A>&gt; wrote =  
in message=20  
<A href=3D"news:468bd715@linux">news:468bd715@linux</A>...</DIV>  
<DIV><FONT face=3DArial size=3D2>Hey DJ,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>I've been doing everything here =  
except no=20  
442.&nbsp;</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Does that error look like a hardware =  
issue to=20  
you?</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Tom</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV>&nbsp;</DIV>  
<BLOCKQUOTE dir=3Dltr=20  
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =  
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">  
<DIV>"DJ" &lt;animix \_ at \_ animas \_ dot \_ net&gt; wrote in message =  
<A=20  
href=3D"news:468bd4bf@linux">news:468bd4bf@linux</A>...</DIV>  
<DIV><FONT face=3DArial size=3D2>Tom,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>After you have edited your Pairs =  
..cfg file to=20  
add the line "UseHouseSync=3D1" (no quotes), save this and reboot =  
your=20  
computer.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>1. Get the 442 completely out of =  
the equation.=20  
Forget about using it ever again in a multcard setup. It's just =  
going to=20  
make your life miserable.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>2. Connect the three MECs to the =  
Lucid clock=20  
outputs with cables of equal length, connect the MEC on card A to =  
clock=20  
output #1, Mec on card B to output #2, etc.....I don't know why, =  
but=20

this is what worked for me.....then ((very important) set the =  
Lucid clock=20  
to 44.1KHz sample rate (if that's what you're using)</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>3. Boot Paris from the Paris.exe in =  
the=20  
C:\Program files\EMU\Paris folder</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>4. Set the project to 48KHz and =  
save it back to=20  
the same folder under the name "Default Project" (no =  
quotes).</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>5. Save it again to the desktop =  
under the same=20  
name.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>6.&nbsp;</FONT>&nbsp;</DIV>Reboot your computer and =  
launch Paris=20  
from the icon on your desktop. Do not ever change the sample rate of =  
your=20  
Default Project. Leave it at 48KHz. You will be able to open all of =  
your old=20  
44.1 projects or create new 44.1 projects from this one once Paris =  
has=20  
booted and fully initialized.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Deej</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<BLOCKQUOTE dir=3Dltr=20  
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =  
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">  
<DIV>"Tom Bruhl" &lt;<A=20  
href=3D"mailto:arpegio@comcast.net">arpegio@comcast.net</A>&gt; =  
wrote in=20  
message <A =  
href=3D"news:468bceee@linux">news:468bceee@linux</A>...</DIV>  
<DIV><FONT face=3DArial size=3D2>I was more stable than ever =  
before with Lucid=20  
WC,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>2 MECs and one 442.&nbsp;</FONT>&nbsp;</DIV>Never =  
crashed=20  
once.&nbsp;</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>a third MEC and that was okay but =  
it's=20  
in/outs weren't</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>functional.&nbsp;</FONT>&nbsp;</DIV>I tried it in a =

different=20  
position and ever since</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>then I get this after Paris has =  
gotten to the=20  
EDS/DX effects</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>part of the start =  
up.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Unhandled =  
Exception:c0000005</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>at address: 77c35ea</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>I tried removing the last MEC and =  
putting it=20  
in the last working position.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>All I get is this error and can't =  
boot up=20  
Paris.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Last working =  
configuration:</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Submix A MEC</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Submix B 442</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Submix C MEC (no working =  
audio)</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Submix E MEC</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>I tried swapping =  
hardware&nbsp;</FONT></DIV>  
between Submix=20  
B and C and that's when the trouble began.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>I also reseated the eds cards and =  
their=20  
cables.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Is it possible it's an =  
effect?&nbsp;</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>I have=20  
added nothing new in months and it was very stable.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Maybe&nbsp;</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>a defective default=20  
project?</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>I'll try another one to boot from =  
that=20  
happens to be at 48k.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Tips graciously =  
accepted,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Tom</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>



> I'll try another one to boot from that happens to be at 48k.  
>  
> Tips graciously accepted,  
> Tom  
>  
>  
>  
> I choose Polesoft Lockspam to fight spam, and you?  
> <http://www.polesoft.com/refer.html>

---

---

Subject: Re: Paris won't start because of hardware  
Posted by [John](#) on Wed, 04 Jul 2007 17:59:30 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

This is the part where I talk about the balls of Edmund still charging for Paris, taking up to 7 days for challenge response and offering no support. WOOT

DJ wrote:

> Tom,  
>  
> It looks like a "having a 442 in a multiMEC setup" issue. If removing  
> the 442 and setting up things exactly as I described doesn't work,  
> remove the third MEC (the one I sen you) and try your original  
> configuration again. That MEC was working perfectly as MEC #3 in a x 4  
> MEC Paris rig before I tore it down. All I/O (including the clock I/O  
> were functioning perfectly. You do have the MEC BNC outputs terminated  
> with 75ohm caps, don't you?  
>  
> Deej  
>  
>  
>  
> "Tom Bruhl" <[arpegio@comcast.net](mailto:arpegio@comcast.net) <<mailto:arpegio@comcast.net>>> wrote  
> in message news:468bd715@linux...  
> Hey DJ,  
> I've been doing everything here except no 442. I'll give that a whirl.  
> Does that error look like a hardware issue to you?  
> Tom  
>  
>  
>  
> "DJ" <[animix \\_\\_ at \\_\\_ animas \\_\\_ dot \\_\\_ net](mailto:animix__at__animas__dot__net)> wrote in message  
> news:468bd4bf@linux...  
> Tom,  
>

> After you have edited your Pairs .cfg file to add the line  
> "UseHouseSync=1" (no quotes), save this and reboot your computer.

>  
> 1. Get the 442 completely out of the equation. Forget about  
> using it ever again in a multicard setup. It's just going to  
> make your life miserable.

>  
> 2. Connect the three MECs to the Lucid clock outputs with cables  
> of equal length, connect the MEC on card A to clock output #1,  
> Mec on card B to output #2, etc.....I don't know why, but  
> this is what worked for me.....then ((very important) set the  
> Lucid clock to 44.1KHz sample rate (if that's what you're using)

>  
> 3. Boot Paris from the Paris.exe in the C:\Program  
> files\EMU\Paris folder

>  
> 4. Set the project to 48KHz and save it back to the same folder  
> under the name "Default Project" (no quotes).

>  
> 5. Save it again to the desktop under the same name.

>  
> 6. Reboot your computer and launch Paris from the icon on your  
> desktop. Do not ever change the sample rate of your Default  
> Project. Leave it at 48KHz. You will be able to open all of your  
> old 44.1 projects or create new 44.1 projects from this one once  
> Paris has booted and fully initialized.

>  
> Deej

>  
>  
>  
> "Tom Bruhl" <arpeggio@comcast.net  
> <mailto:arpeggio@comcast.net>> wrote in message  
> news:468bceee@linux...

> I was more stable than ever before with Lucid WC,  
> 2 MECs and one 442. Never crashed once. I added  
> a third MEC and that was okay but it's in/out's weren't  
> functional. I tried it in a different position and ever since  
> then I get this after Paris has gotten to the EDS/DX effects  
> part of the start up.

>  
> Unhandled Exception:c00000005  
> at address: 77c35ea

>  
> I tried removing the last MEC and putting it in the last  
> working position.  
> All I get is this error and can't boot up Paris.

> Last working configuration:  
> Submix A MEC  
> Submix B 442  
> Submix C MEC (no working audio)  
> Submix E MEC  
>  
> I tried swapping hardware between Submix B and C and that's  
> when the trouble began.  
> I also reseated the eds cards and their cables.  
>  
> Is it possible it's an effect? I have added nothing new in  
> months and it was very stable.  
> Maybe a defective default project?  
>  
> I'll try another one to boot from that happens to be at 48k.  
>  
> Tips graciously accepted,  
> Tom  
>  
>  
>  
> I choose Polesoft Lockspam to fight spam, and you?  
> <http://www.polesoft.com/refer.html>

---

---

Subject: Re: Paris won't start because of hardware  
Posted by [Tom Bruhl](#) on Thu, 05 Jul 2007 04:08:55 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

This is a multi-part message in MIME format.

-----=\_NextPart\_000\_003C\_01C7BE98.AD7DFCD0  
Content-Type: text/plain;  
charset="iso-8859-1"  
Content-Transfer-Encoding: quoted-printable

John,  
Magma here, IRQs are very happy.

Deej,  
Ya terminated for sure. To try the original setup  
with my mobo means WC in series to mec A  
then to mec B. Silly but that's the only way it worked.  
David has the same issue with this ASUS mobo and a Lucid.

Never a dull moment here in Paris on 4rth of July.  
Thanks guys,  
Tom



"John" <aint@itawful.com> wrote in message news:468be028@linux...  
What is you motherboard. You have 3 eds cards? IRQ conflicts are the =

biggest problem. Make sure you don't have conflicts which is damn =  
hard=20  
with 3 cards. You may need a magma for that many cards. I think used =  
they are \$250 or so.

Tom Bruhl wrote:

> I was more stable than ever before with Lucid WC,  
> 2 MECs and one 442. Never crashed once. I added  
> a third MEC and that was okay but it's in/out's weren't  
> functional. I tried it in a different position and ever since  
> then I get this after Paris has gotten to the EDS/DX effects  
> part of the start up.  
> =20  
> Unhandled Exception:c00000005  
> at address: 77c35ea  
> =20  
> I tried removing the last MEC and putting it in the last working =  
position.  
> All I get is this error and can't boot up Paris.  
> =20  
> Last working configuration:  
> Submix A MEC  
> Submix B 442  
> Submix C MEC (no working audio)  
> Submix E MEC  
> =20  
> I tried swapping hardware between Submix B and C and that's when the =  
> trouble began.  
> I also reseated the eds cards and their cables.  
> =20  
> Is it possible it's an effect? I have added nothing new in months =  
and=20  
> it was very stable.  
> Maybe a defective default project?  
> =20  
> I'll try another one to boot from that happens to be at 48k.  
> =20  
> Tips graciously accepted,  
> Tom  
> =20  
> =20

>=20  
> I choose Polesoft Lockspam to fight spam, and you?  
> <http://www.polesoft.com/refer.html>

-----=\_NextPart\_000\_003C\_01C7BE98.AD7DFCD0

Content-Type: text/html;  
 charset="iso-8859-1"  
Content-Transfer-Encoding: quoted-printable

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.2800.1400" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT face=3DArial size=3D2>John,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Magma here, IRQs are very =
happy.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>Deej,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Ya terminated for sure.&nbsp;</DIV> To try =
the original=20
setup</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>with my mobo means WC in series to mec=20
A</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>then to mec B.&nbsp;</DIV> Silly but that's =
the only way=20
it worked.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>David has the same issue with this ASUS =
mobo and a=20
Lucid.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>Never a dull moment here in Paris on =
4rth of=20
July.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Thanks guys,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Tom</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<BLOCKQUOTE=20
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">
  <DIV>"John" &lt;<A =
href=3D"mailto:aint@itawful.com">aint@itawful.com</A>&gt;=20
  wrote in message <A=20
  href=3D"news:468be028@linux">news:468be028@linux</A>...</DIV>What is =
you=20
```

motherboard.&nbsp; You have 3 eds cards?&nbsp; IRQ conflicts are the=20  
<BR>biggest problem.&nbsp; Make sure you don't have conflicts which is =  
damn=20  
hard <BR>with 3 cards.&nbsp; You may need a magma for that many =  
cards.&nbsp; I=20  
think used <BR>they are \$250 or so.<BR><BR>Tom Bruhl wrote:<BR>&gt; I =  
was more=20  
stable than ever before with Lucid WC,<BR>&gt; 2 MECs and one =  
442.&nbsp; Never=20  
crashed once.&nbsp; I added<BR>&gt; a third MEC and that was okay but =  
it's=20  
in/outs weren't<BR>&gt; functional.&nbsp; I tried it in a different =  
position=20  
and ever since<BR>&gt; then I get this after Paris has gotten to the =  
EDS/DX=20  
effects<BR>&gt; part of the start up.<BR>&gt;&nbsp; <BR>&gt; Unhandled =  
  
Exception:c0000005<BR>&gt; at address: 77c35ea<BR>&gt;&nbsp; <BR>&gt; =  
I tried=20  
removing the last MEC and putting it in the last working =  
position.<BR>&gt; All=20  
I get is this error and can't boot up Paris.<BR>&gt;&nbsp; <BR>&gt; =  
Last=20  
working configuration:<BR>&gt; Submix A MEC<BR>&gt; Submix B =  
442<BR>&gt;=20  
Submix C MEC (no working audio)<BR>&gt; Submix E MEC<BR>&gt;&nbsp; =  
<BR>&gt; I=20  
tried swapping hardware between Submix B and C and that's when the =  
<BR>&gt;=20  
trouble began.<BR>&gt; I also reseated the eds cards and their=20  
cables.<BR>&gt;&nbsp; <BR>&gt; Is it possible it's an effect?&nbsp; I =  
have=20  
added nothing new in months and <BR>&gt; it was very stable.<BR>&gt; =  
Maybe a=20  
defective default project?<BR>&gt;&nbsp; <BR>&gt; I'll try another one =  
to boot=20  
from that happens to be at 48k.<BR>&gt;&nbsp; <BR>&gt; Tips graciously =  
  
accepted,<BR>&gt; Tom<BR>&gt;&nbsp; <BR>&gt; <BR>&gt; <BR>&gt; I =  
choose=20  
Polesoft Lockspam to fight spam, and you?<BR>&gt; <A=20  
=  
href=3D"http://www.polesoft.com/refer.html">http://www.polesoft.com/refer=  
..html</A></BLOCKQUOTE></BODY></HTML>

-----=\_NextPart\_000\_003C\_01C7BE98.AD7DFCD0--

---

---

Subject: Re: Paris won't start because of hardware  
Posted by [DJ](#) on Thu, 05 Jul 2007 04:10:33 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

This is a multi-part message in MIME format.

-----=\_NextPart\_000\_003B\_01C7BE88.2472C700  
Content-Type: text/plain;  
charset="iso-8859-1"  
Content-Transfer-Encoding: quoted-printable

Tom,

Did you lose the 442 yet?

"Tom Bruhl" <arpeggio@comcast.net> wrote in message =  
news:468c700a@linux...

John,  
Magma here, IRQs are very happy.

Deej,  
Ya terminated for sure. To try the original setup  
with my mobo means WC in series to mec A  
then to mec B. Silly but that's the only way it worked.  
David has the same issue with this ASUS mobo and a Lucid.

Never a dull moment here in Paris on 4rth of July.  
Thanks guys,  
Tom

"John" <aint@itawful.com> wrote in message news:468be028@linux...  
What is you motherboard. You have 3 eds cards? IRQ conflicts are =  
the=20  
biggest problem. Make sure you don't have conflicts which is damn =  
hard=20  
with 3 cards. You may need a magma for that many cards. I think =  
used=20  
they are \$250 or so.

Tom Bruhl wrote:

> I was more stable than ever before with Lucid WC,  
> 2 MECs and one 442. Never crashed once. I added  
> a third MEC and that was okay but it's in/outs weren't  
> functional. I tried it in a different position and ever since  
> then I get this after Paris has gotten to the EDS/DX effects  
> part of the start up.

> =20  
> Unhandled Exception:c00000005  
> at address: 77c35ea  
> =20  
> I tried removing the last MEC and putting it in the last working =  
position.  
> All I get is this error and can't boot up Paris.  
> =20  
> Last working configuration:  
> Submix A MEC  
> Submix B 442  
> Submix C MEC (no working audio)  
> Submix E MEC  
> =20  
> I tried swapping hardware between Submix B and C and that's when =  
the=20  
> trouble began.  
> I also reseated the eds cards and their cables.  
> =20  
> Is it possible it's an effect? I have added nothing new in months =  
and=20  
> it was very stable.  
> Maybe a defective default project?  
> =20  
> I'll try another one to boot from that happens to be at 48k.  
> =20  
> Tips graciously accepted,  
> Tom  
> =20  
> =20  
> =20  
> I choose Polesoft Lockspam to fight spam, and you?  
> <http://www.polesoft.com/refer.html>

-----=\_NextPart\_000\_003B\_01C7BE88.2472C700

Content-Type: text/html;  
charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.6000.16414" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>Tom,</FONT></DIV>
```

<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Did you lose the 442 yet?</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<BLOCKQUOTE dir=3Dltr=20  
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =  
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">  
<DIV>"Tom Bruhl" &lt;<A=20  
href=3D"mailto:arpegio@comcast.net">arpegio@comcast.net</A>&gt; wrote =  
in message=20  
<A href=3D"news:468c700a@linux">news:468c700a@linux</A>...</DIV>  
<DIV><FONT face=3DArial size=3D2>John,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Magma here, IRQs are very =  
happy.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Deej,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Ya terminated for sure.&nbsp;</DIV> To try =  
the original=20  
setup</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>with my mobo means WC in series to =  
mec=20  
A</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>then to mec B.&nbsp;</DIV> Silly but that's =  
the only=20  
way it worked.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>David has the same issue with this =  
ASUS mobo and=20  
a Lucid.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>Never a dull moment here in Paris on =  
4rth of=20  
July.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Thanks guys,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Tom</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<BLOCKQUOTE=20  
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =  
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">  
<DIV>"John" &lt;<A =  
href=3D"mailto:aint@itawful.com">aint@itawful.com</A>&gt;=20  
wrote in message <A=20  
href=3D"news:468be028@linux">news:468be028@linux</A>...</DIV>What is =  
you=20  
motherboard.&nbsp;</DIV> You have 3 eds cards?&nbsp;</DIV> IRQ conflicts are the =  
  
<BR>biggest problem.&nbsp;</DIV> Make sure you don't have conflicts which =  
is damn=20

hard <BR>with 3 cards.&nbsp; You may need a magma for that many =  
cards.&nbsp;=20  
I think used <BR>they are \$250 or so.<BR><BR>Tom Bruhl =  
wrote:<BR>&gt; I was=20  
more stable than ever before with Lucid WC,<BR>&gt; 2 MECs and one=20  
442.&nbsp; Never crashed once.&nbsp; I added<BR>&gt; a third MEC and =  
that=20  
was okay but it's in/outs weren't<BR>&gt; functional.&nbsp; I tried =  
it in a=20  
different position and ever since<BR>&gt; then I get this after =  
Paris has=20  
gotten to the EDS/DX effects<BR>&gt; part of the start =  
up.<BR>&gt;&nbsp;=20  
<BR>&gt; Unhandled Exception:c00000005<BR>&gt; at address:=20  
77c35ea<BR>&gt;&nbsp; <BR>&gt; I tried removing the last MEC and =  
putting it=20  
in the last working position.<BR>&gt; All I get is this error and =  
can't boot=20  
up Paris.<BR>&gt;&nbsp; <BR>&gt; Last working configuration:<BR>&gt; =  
Submix=20  
A MEC<BR>&gt; Submix B 442<BR>&gt; Submix C MEC (no working =  
audio)<BR>&gt;=20  
Submix E MEC<BR>&gt;&nbsp; <BR>&gt; I tried swapping hardware =  
between Submix=20  
B and C and that's when the <BR>&gt; trouble began.<BR>&gt; I also =  
reseated=20  
the eds cards and their cables.<BR>&gt;&nbsp; <BR>&gt; Is it =  
possible it's=20  
an effect?&nbsp; I have added nothing new in months and <BR>&gt; it =  
was very=20  
stable.<BR>&gt; Maybe a defective default project?<BR>&gt;&nbsp; =  
<BR>&gt;=20  
I'll try another one to boot from that happens to be at =  
48k.<BR>&gt;&nbsp;=20  
<BR>&gt; Tips graciously accepted,<BR>&gt; Tom<BR>&gt;&nbsp; =  
<BR>&gt;=20  
<BR>&gt; <BR>&gt; I choose Polesoft Lockspam to fight spam, and =  
you?<BR>&gt;=20  
<A=20  
=  
href=3D"http://www.polesoft.com/refer.html">http://www.polesoft.com/refer=  
..html</A></BLOCKQUOTE></BLOCKQUOTE></BODY></HTML>  
-----=\_NextPart\_000\_003B\_01C7BE88.2472C700--

---

Subject: Re: Paris won't start because of hardware



Posted by [Tom Bruhl](#) on Thu, 05 Jul 2007 04:30:29 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

This is a multi-part message in MIME format.

-----=\_NextPart\_000\_00A0\_01C7BE9B.B0A9E100

Content-Type: text/plain;

charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

DJ,

I just got back from a gig and the beer is more inviting than the machine room. I will asap though. An early gig tomorrow at [http://www.chathambarsinn.com/dining/beach\\_house\\_grill.asp](http://www.chathambarsinn.com/dining/beach_house_grill.asp) and a wedding on Saturday. =20

Either Thursday night after an early evening with friends on the cape or Sunday after I recover from the rest of the week. =20

Good news, only two successful sessions this week already.

"DJ" <[animix\\_at\\_animas\\_dot\\_net](mailto:animix_at_animas_dot_net)> wrote in message = news:468c70a8\$1@linux...

Tom,

Did you lose the 442 yet?

"Tom Bruhl" <[arpeggio@comcast.net](mailto:arpeggio@comcast.net)> wrote in message = news:468c700a@linux...

John,

Magma here, IRQs are very happy.

Deej,

Ya terminated for sure. To try the original setup with my mobo means WC in series to mec A then to mec B. Silly but that's the only way it worked. David has the same issue with this ASUS mobo and a Lucid.

Never a dull moment here in Paris on 4rth of July.

Thanks guys,

Tom

"John" <[aint@itawful.com](mailto:aint@itawful.com)> wrote in message news:468be028@linux...  
What is you motherboard. You have 3 eds cards? IRQ conflicts are = the=20

biggest problem. Make sure you don't have conflicts which is damn = hard=20

with 3 cards. You may need a magma for that many cards. I think =  
used=20  
they are \$250 or so.

Tom Bruhl wrote:

> I was more stable than ever before with Lucid WC,  
> 2 MECs and one 442. Never crashed once. I added  
> a third MEC and that was okay but it's in/outs weren't  
> functional. I tried it in a different position and ever since  
> then I get this after Paris has gotten to the EDS/DX effects  
> part of the start up.  
> =20  
> Unhandled Exception:c00000005  
> at address: 77c35ea  
> =20  
> I tried removing the last MEC and putting it in the last working =  
position.  
> All I get is this error and can't boot up Paris.  
> =20  
> Last working configuration:  
> Submix A MEC  
> Submix B 442  
> Submix C MEC (no working audio)  
> Submix E MEC  
> =20  
> I tried swapping hardware between Submix B and C and that's when =  
the=20  
> trouble began.  
> I also reseated the eds cards and their cables.  
> =20  
> Is it possible it's an effect? I have added nothing new in =  
months and=20  
> it was very stable.  
> Maybe a defective default project?  
> =20  
> I'll try another one to boot from that happens to be at 48k.  
> =20  
> Tips graciously accepted,  
> Tom  
> =20  
> =20  
> =20  
> I choose Polesoft Lockspam to fight spam, and you?  
> <http://www.polesoft.com/refer.html>

-----=\_NextPart\_000\_00A0\_01C7BE9B.B0A9E100

Content-Type: text/html;  
charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.2800.1400" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT face=3DArial size=3D2>DJ,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>I just got back from a gig and the beer =
is more=20
inviting</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>than the machine room.&nbsp; I will =
asap=20
though.&nbsp; An early gig</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>tomorrow at <A=20
href=3D"http://www.chathambarsinn.com/dining/beach_house_grill.asp">http:=
//www.chathambarsinn.com/dining/beach_house_grill.asp</A></FONT ></DIV>
<DIV><FONT face=3DArial size=3D2>and a wedding on Saturday.&nbsp; =
</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>Either Thursday night after an early =
evening with=20
friends on the cape</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>or Sunday after I recover from =
the&nbsp;rest of=20
the&nbsp;week.&nbsp;</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>Good news, only two successful sessions =
this week=20
already.</FONT></DIV>
<BLOCKQUOTE dir=3Dltr=20
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">
  <DIV>"DJ" &lt;animix _ at _ animas _ dot _ net&gt; wrote in message <A =
href=3D"news:468c70a8$1 @linux">news:468c70a8$1 @linux</A>...</DIV>
  <DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
  <DIV><FONT face=3DArial size=3D2>Tom,</FONT></DIV>
  <DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
  <DIV><FONT face=3DArial size=3D2>Did you lose the 442 =
yet?</FONT></DIV>
  <DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
  <DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
  <BLOCKQUOTE dir=3Dltr=20
    style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =
    BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">
```

<DIV>"Tom Bruhl" &lt;<A=20  
href=3D"mailto:arpeggio@comcast.net">arpeggio@comcast.net</A>&gt; =  
wrote in=20  
message <A =  
href=3D"news:468c700a@linux">news:468c700a@linux</A>...</DIV>  
<DIV><FONT face=3DArial size=3D2>John,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Magma here, IRQs are very =  
happy.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Deej,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Ya terminated for sure.&nbsp;</FONT> To =  
try the=20  
original setup</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>with my mobo means WC in series to =  
mec=20  
A</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>then to mec B.&nbsp;</FONT> Silly but =  
that's the only=20  
way it worked.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>David has the same issue with this =  
ASUS mobo=20  
and a Lucid.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2>Never a dull moment here in Paris =  
on 4rth of=20  
July.</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Thanks guys,</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2>Tom</FONT></DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>  
<BLOCKQUOTE=20  
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =  
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">  
<DIV>"John" &lt;<A =  
href=3D"mailto:aint@itawful.com">aint@itawful.com</A>&gt;=20  
wrote in message <A=20  
href=3D"news:468be028@linux">news:468be028@linux</A>...</DIV>What =  
is you=20  
motherboard.&nbsp;</FONT> You have 3 eds cards?&nbsp;</FONT> IRQ conflicts are =  
the=20  
<BR>biggest problem.&nbsp;</FONT> Make sure you don't have conflicts =  
which is=20  
damn hard <BR>with 3 cards.&nbsp;</FONT> You may need a magma for that =  
many=20  
cards.&nbsp;</FONT> I think used <BR>they are \$250 or so.<BR><BR>Tom =  
Bruhl=20  
wrote:<BR>&gt; I was more stable than ever before with Lucid =  
WC,<BR>&gt; 2=20

MECs and one 442. Never crashed once. I added  
a third  
MEC and that was okay but it's in/outs weren't  
functional. I  
tried it in a different position and ever since then I get  
this  
after Paris has gotten to the EDS/DX effects; part of the  
start  
up. Unhandled Exception:c00000005  
at  
address: 77c35ea; I tried removing the last  
MEC and  
putting it in the last working position. All I get is this  
error  
and can't boot up Paris. Last working  
configuration: Submix A MEC; Submix B 442;  
Submix C  
MEC (no working audio); Submix E MEC; I  
tried  
swapping hardware between Submix B and C and that's when the  
trouble began. I also reseated the eds cards and their  
cables. Is it possible it's an  
effect? I have  
added nothing new in months and it was very  
stable. Maybe  
a defective default project? I'll try  
another one  
to boot from that happens to be at 48k. Tips  
graciously accepted, Tom  
I choose Polesoft Lockspam to fight spam, and you? <http://www.polesoft.com/refer.html>

---

-----=\_NextPart\_000\_00A0\_01C7BE9B.B0A9E100--