
Subject: Update....

Posted by [mikeaudet](#) on Thu, 19 May 2022 15:00:55 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi Everyone,

It's been tough to make progress this year, but I'm finally getting traction. I've just started testing a version of the PSCL that is designed to work with jBridge. For those who haven't used jBridge, it allows a 32 bit host to connect with 64 bit VST files. I just started testing it with some 64 bit Waves plugins. So far, so good. The updated PSCL has a low priority thread that checks for jBridge processes and moves them off the CPU used by the PARIS application. This way, we can run 64 bit VSTs on all but one available CPU cores, while not running into the thread-safety issues in the PARIS application.

jBridge can be found here:

<https://jstuff.wordpress.com/jbridge/>

My next move is to work on the kernel driver (scherzo.sys). I bought a new ASUS motherboard with a PCI slot, and the driver does not work with this new board. The new board uses a I/O MMU, which is a new thing for PCs. I suspect that this is the problem, but I'll know more next week. An I/O MMU puts the PCI bus behind a memory controller that has to be programmed in order to allow PCI cards to access main memory. It's an extra level of indirection put in place for security reasons. The driver was not designed for this kind of thing.

I still haven't gotten the EV security certificate. The eventually rejected by documents that were signed by a justice of the peace. It's completely insane. An accountant or a lawyer will do just fine, but a judge can't be trusted. It's nuts. I'm going to go see a notary after I get the kernel driver updated. I only get a year on the certificate, so I think it makes sense to wait until I have this next phase done.

That's all I have to report for now.

All the best,
Mike

File Attachments

1) [PARIS_with_Waves.jpg](#), downloaded 7874 times

Edit Functions Settings EQ Aux Tracks Automation

The mixer interface displays 10 tracks, each with a set of controls. At the top, there are buttons for 'BYPASS' and 'EQ 1 OFF'. Below these are three EQ sections for each track, each with a frequency knob (set to 1000 Hz), a gain knob (set to 0.0 dB), and a bandwidth knob (set to 1.5). An 'ALL EQ' indicator is lit for each track. Below the EQ sections are 'SOLO' and 'MUTE' buttons, followed by a volume fader with a scale from 0 to 70. At the bottom of each track are 'REC' and 'AUTO' buttons. The mixer is currently in 'REC' mode, as indicated by the 'REC' buttons being lit.

The IR-L window is titled 'IR-L' and shows settings for a reverb processor. The name is 'Hall - 1', type is 'Concert Hall', and date is '24 Mar 2004'. The sample rate is 'SR: 96000Hz -> 44100Hz' and the emitter is 'Genelec S30D'. The window displays a frequency response graph and various parameters: Convolution (1.85s), RT60 (1.4s), Channels (4), Size (11267), and Distance (13m). The 'Reverb Time' is set to 0.000s, 'Latency' is 11ms, and 'Dry/Wet' is 100. The 'Output' is set to 0.0. The window also has 'Zoom' and 'Reset' buttons.

Options:

Post Notific

The transport control panel shows the current time as '00:01:48:16.6' and the SMPTE time as '00:00:00:00.0'. It includes buttons for 'PUNCH' and 'LOCK', and a display for 'SMPT'.

Disable smiles in this message