
Subject: Re: Wordclock still need clarification !, Anyone ?

Posted by [Deej \[4\]](#) on Sun, 25 Feb 2007 19:16:15 GMT

[View Forum Message](#) <> [Reply to Message](#)

ALSO the ADAT input of pulsar
that accepts that four digital outs from the preamps ?!!!

The Mytek WC is sending sync to to Pulsar. The Pulsar is your main audio interface. It is interfacing with your ADAT>AES format converter and therefore should be clocking this device. The AES signals that are being received by the format converter may be being reclocked between the converter inputs and outputs as they are being returned to the Pulsar which is being clocked from the Mytek. At least, that is what I think would hopefully happen. Are you hearing any pops, clicks or audible midrange (or othter distortion/bursts of digital noise)? If not, then this is probably happening. If so, then I don't know WTF I'm talking about.....wouldn't be the first time.

;o)

"Dimitrios" <musurgio@otenet.gr> wrote in message news:45e1dcd9\$1@linux...

>

> Hi,

> My head is turning wheels.

> I have connected 4 AES outputting digital preamps into an AES to adat
> coonverter

> and then inputing the adat signal that carries 4 stereo aes signals from
> for preamps int my Pul;sar scope card adat input.

> Noww Pulsar card has the syncplate attatched which has wordclock input and
> wordclock input is clocked by Mytek digitalclock.

>

> Now instead of running wordclock to each and everyone preamp of these four
> devices occupying 4 mytek wordclock outputs SHOULDN'T The one and only
> wordclock

> input on Pulsar (clocked from Mytek) clock ALSO the ADAT input of pulsar
> that accepts that four digital outs from the preamps ?!!!

> I don't see why this cannot be done but maybe I am wrong hee...

> Anyone has digged into this deep wordclock issues ?

> Regards,

> Dimitrios

Subject: Wordclock still need clarification !, Anyone ?

Posted by [Dimitrios](#) on Sun, 25 Feb 2007 20:00:41 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi,

My head is turning wheels.

I have connected 4 AES outputting digital preamps into an AES to ADAT converter and then inputting the ADAT signal that carries 4 stereo AES signals from preamps into my Pulsar scope card ADAT input.

Now Pulsar card has the syncplate attached which has wordclock input and wordclock input is clocked by Mytek digitalclock.

Now instead of running wordclock to each and every preamp of these four devices occupying 4 Mytek wordclock outputs SHOULDN'T The one and only wordclock input on Pulsar (clocked from Mytek) clock ALSO the ADAT input of Pulsar that accepts that four digital outs from the preamps ?!!!

I don't see why this cannot be done but maybe I am wrong hee...

Anyone has dugged into this deep wordclock issues ?

Regards,
Dimitrios

Subject: Re: Wordclock still need clarification !, Anyone ?

Posted by [Dimitrios](#) on Sun, 25 Feb 2007 20:31:30 GMT

[View Forum Message](#) <> [Reply to Message](#)

Dear DJ thanks,

The format converter does NOT reclock the signal so only Pulsar would be the candidate if it can reclock what comes in its digital inputs...

Don't know

Regards,
Dimitrios

"DJ" <www.aarrrrggghhh!!!.com> wrote:

>ALSO the ADAT input of Pulsar

>that accepts that four digital outs from the preamps ?!!!

>

>The Mytek WC is sending sync to Pulsar. The Pulsar is your main audio

>interface. It is interfacing with your ADAT>AES format converter and

>therefore should be clocking this device. The AES signals that are being

>received by the format converter may be being reclocked between the

>converter inputs and outputs as they are being returned to the Pulsar which

>is being clocked from the Mytek. At least, that is what I think would

>hopefully happen. Are you hearing any pops, clicks or audible midrange (or

>other distortion/bursts of digital noise)? If not, then this is probably

>happening. If so, then I don't know WTF I'm talking about.....wouldn't

be

>the first time.

>
>;0)
>
>
>
>"Dimitrios" <musurgio@otenet.gr> wrote in message news:45e1dcd9\$1@linux...
>>
>> Hi,
>> My head is turning wheels.
>> I have connected 4 AES outputting digital preamps into an AES to adat

>> coconverter
>> and then inputing the adat signal that carries 4 stereo aes signals from
>> for preamps int my Pul;sar scope card adat input.
>> Noww Pulsar card has the syncplate attched which has wordclock input
and
>> wordclock input is clocked by Mytek digitalclock.
>>
>> Now instead of running wordclock to each and everyone preamp of these
four
>> devices occuping 4 mytek wordclock outputs SHOULDN'T The one and only

>> wordclock
>> input on Pulsar (clocked from Mytek) clock ALSO the ADAT input of pulsar
>> that accepts that four digital outs from the preamps ?!!!
>> I don't see why this cannot be done but maybe I am wrong hee...
>> Anyone has digged into this deep wordclock issues ?
>> Regards,
>> Dimitrios
>
>

Subject: Re: Wordclock still need clarification !, Anyone ?
Posted by [gene lennon](#) on Sun, 25 Feb 2007 20:34:48 GMT
[View Forum Message](#) <> [Reply to Message](#)

Which ADAT>AES format converter are you using? RME?
Gene

"Dimitrios" <musurgio@otenet.gr> wrote:
>
>Dear DJ thanks,
>The format converter does NOT reclock the signal so only Oulsar would be
>the candidate iuf it can reclock what comes in its digital inputs...
>Don't know
>Regards,
>Dimitrios
>

>"DJ" <www.aarrrrggghhh!!!.com> wrote:
>>ALSO the ADAT input of pulsar
>>that accepts that four digital outs from the preamps ?!!!
>>
>>The Mytek WC is sending sync to to Pulsar. The Pulsar is your main audio
>
>>interface. It is interfacing with your ADAT>AES format converter and
>>therefore should be clocking this device. The AES signals that are being
>
>>received by the format converter may be being reclocked between the
>>converter inputs and outputs as they are being returned to the Pulsar which
>
>>is being clocked from the Mytek. At least, that is what I think would
>>hopefully happen. Are you hearing any pops, clicks or audible midrange
(or
>
>>othter distortion/bursts of digital noise)? If not, then this is probably
>
>>happening. If so, then I don't know WTF I'm talking about.....wouldn't
>be
>>the first time.
>>
>>;o)
>>
>>
>>"Dimitrios" <musurgio@otenet.gr> wrote in message news:45e1dcd9\$1@linux...
>>>
>>> Hi,
>>> My head is turning wheels.
>>> I have connected 4 AES outputting digital preamps into an AES to adat
>
>>> coconverter
>>> and then inputing the adat signal that carries 4 stereo aes signals from
>>> for preamps int my Pul;sar scope card adat input.
>>> Noww Pulsar card has the syncplate attched which has wordclock input
>and
>>> wordclock input is clocked by Mytek digitalclock.
>>>
>>> Now instead of running wordclock to each and everyone preamp of these
>four
>>> devices occupying 4 mytek wordclock outputs SHOULDN'T The one and only
>
>>> wordclock
>>> input on Pulsar (clocked from Mytek) clock ALSO the ADAT input of pulsar
>>> that accepts that four digital outs from the preamps ?!!!
>>> I don't see why this cannot be done but maybe I am wrong hee...
>>> Anyone has digged into this deep wordclock issues ?
>>> Regards,

>>> Dimitrios

>>

>>

>

Subject: Re: Wordclock still need clarification !, Anyone ?

Posted by [Morgan](#) on Sun, 25 Feb 2007 22:00:58 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi Dimitrios,

Whatever Digital signals you are using must see the master word clock by direct connect via BNC or via SPDIF/AES or ADAT looking for master operating as slave.

If you have 4 preamps with Digital outs - Those clocks are all doing their own thing so to speak.

If I understand your setup correctly - these 4 preamps need to see master word clock , then go through the converter < Converter may not need the WC signal - which one are you using ? > Then out via Light pipe to the Pulsar synchplate which should also have master WC piped into it. All devices should be set to look for external source.

Morgan :)

Dimitrios wrote:

> Hi,

> My head is turning wheels.

> I have connected 4 AES outputting digital preamps into an AES to adat coconverter

> and then inputing the adat signal that carries 4 stereo aes signals from

> for preamps int my Pul;sar scope card adat input.

> Noww Pulsar card has the syncplate attched which has wordclock input and

> wordclock input is clocked by Mytek digitalclock.

>

> Now instead of running wordclock to each and everyone preamp of these four

> devices occuping 4 mytek wordclock outputs SHOULDN'T The one and only wordclock

> input on Pulsar (clocked from Mytek) clock ALSO the ADAT input of pulsar

> that accepts that four digital outs from the preamps ?!!!

> I don't see why this cannot be done but maybe I am wrong hee...

> Anyone has digged into this deep wordclock issues ?

> Regards,

> Dimitrios

Subject: Re: Wordclock still need clarification !, Anyone ?

Posted by [Dimitrios](#) on Mon, 26 Feb 2007 07:46:51 GMT

[View Forum Message](#) <> [Reply to Message](#)

Thanks.

I am using the Graham Patten ADAT-3 an "old" 16 bit format converter ,it has wc input but does nothing in clocking the rightb way the signals. I know the other way of doing it by clocking each device separately befor going in the format converter and then into Pulsar, but I thought that I might skip that and maybe by JUST GETTING IN TO Pulsar card (which is clocked with syncplate by mytek and slaved) that would be enough !

Isn't that the same thing as by buying a format converter like rme and use the RME's wordclock in to sync all 4 devices ?

My real question is if these four signals have their own jitter problems would the format converter WC input solve that for all 4 devices ?

Regards,
Dimitrios

Morgan

<morganp@ntplx.net> wrote:
>Hi Dimitrios,
>
>Whatever Digital signals you are using
>must see the master word clock by direct
>connect via BNC or via SPDIF/AES or ADAT looking for
>master operating as slave.
>If you have 4 preamps with Digital outs -
>Those clocks are all doing their own thing so to speak.
>
>If I understand your setup correctly - these 4 preamps
>need to see master word clock , then go through the converter
>< Converter may not need the WC signal - which one are you using ? >
>Then out via Light pipe to the Pulsar synchplate which should also have

>master WC piped into it. All devices should be set to look for external

>source.
>
>Morgan :)
>
>
>
>Dimitrios wrote:
>> Hi,

>> My head is turning wheels.
>> I have connected 4 AES outputting digital preamps into an AES to adat
coconverter
>> and then inputing the adat signal that carries 4 stereo aes signals from
>> for preamps int my Pul;sar scope card adat input.
>> Noww Pulsar card has the syncplate attched which has wordclock input
and
>> wordclock input is clocked by Mytek digitalclock.
>>
>> Now instead of running wordclock to each and everyone preamp of these
four
>> devices occupying 4 mytek wordclock outputs SHOULDN'T The one and only
wordclock
>> input on Pulsar (clocked from Mytek) clock ALSO the ADAT input of pulsar
>> that accepts that four digital outs from the preamps ?!!!
>> I don't see why this cannot be done but maybe I am wrong hee...
>> Anyone has digged into this deep wordclock issues ?
>> Regards,
>> Dimitrios
>

Subject: Re: Wordclock still need clarification !, Anyone ?

Posted by [Deej \[4\]](#) on Mon, 26 Feb 2007 08:02:33 GMT

[View Forum Message](#) <> [Reply to Message](#)

Agreed. I've got one of those here. The price for these in the US just went
up a bit. A couple of months ago I saw them on EBay pretty regularly. No
more. Very cool boxes.

"Gene Lennon" <glennon@NOSPmyrealbox.com> wrote in message
news:45e28a68\$1@linux...

>

>

> ADI-4 DD is your friend.

> Gene

>

>

>

> "Dimitrios" <musurgio@otenet.gr> wrote:

>>

>>Thanks.

>>I am using the Graham Patten ADAT-3 an "old" 16 bit format converter ,it

>>has wc input but does nothing in clocking the rightb way the signals.

>>I know the other way of doing it by clocking each device separately befor

>>going in the format converter and then into Pulsar, but I thought that I

>>might skip that and maybe by JUST GETTING IN TO Pulsar card (which is

>>clocked

>>with syncplate by mytek and slaved) that would be enough !
>>
>>Isn't that the same thing as by buying a format converter like rme and use
>>the RME's wordclock in to sync all 4 devices ?
>>My real question is if these four signals have their own jitter problems
>>would the format converter WC input solve that for all 4 devices ?
>>
>>Regards,
>>Dimitrios
>>
>>
>

Subject: Re: Wordclock still need clarification !, Anyone ?
Posted by [gene lennon](#) on Mon, 26 Feb 2007 08:21:12 GMT
[View Forum Message](#) <> [Reply to Message](#)

ADI-4 DD is your friend.
Gene

"Dimitrios" <musurgio@otenet.gr> wrote:

>
>Thanks.
>I am using the Graham Patten ADAT-3 an "old" 16 bit format converter ,it
>has wc input but does nothing in clocking the rightb way the signals.
>I know the other way of doing it by clocking each device separately befor
>going in the format converter and then into Pulsar, but I thought that I
>might skip that and maybe by JUST GETTING IN TO Pulsar card (which is clocked
>with syncplate by mytek and slaved) that would be enough !
>
>Isn't that the same thing as by buying a format converter like rme and use
>the RME's wordclock in to sync all 4 devices ?
>My real question is if these four signals have their own jitter problems
>would the format converter WC input solve that for all 4 devices ?
>
>Regards,
>Dimitrios
>
>
