
Subject: Update....

Posted by [mikeaudet](#) on Thu, 19 May 2022 15:00:55 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi Everyone,

It's been tough to make progress this year, but I'm finally getting traction. I've just started testing a version of the PSCL that is designed to work with jBridge. For those who haven't used jBridge, it allows a 32 bit host to connect with 64 bit VST files. I just started testing it with some 64 bit Waves plugins. So far, so good. The updated PSCL has a low priority thread that checks for jBridge processes and moves them off the CPU used by the PARIS application. This way, we can run 64 bit VSTs on all but one available CPU cores, while not running into the thread-safety issues in the PARIS application.

jBridge can be found here:

<https://jstuff.wordpress.com/jbridge/>

My next move is to work on the kernel driver (scherzo.sys). I bought a new ASUS motherboard with a PCI slot, and the driver does not work with this new board. The new board uses a I/O MMU, which is a new thing for PCs. I suspect that this is the problem, but I'll know more next week. An I/O MMU puts the PCI bus behind a memory controller that has to be programmed in order to allow PCI cards to access main memory. It's an extra level of indirection put in place for security reasons. The driver was not designed for this kind of thing.

I still haven't gotten the EV security certificate. The eventually rejected by documents that were signed by a justice of the peace. It's completely insane. An accountant or a lawyer will do just fine, but a judge can't be trusted. It's nuts. I'm going to go see a notary after I get the kernel driver updated. I only get a year on the certificate, so I think it makes sense to wait until I have this next phase done.

That's all I have to report for now.

All the best,
Mike

File Attachments

1) [PARIS_with_Waves.jpg](#), downloaded 4596 times

Edit Functions Settings EQ Aux Tracks Automation

The mixer interface shows 10 channels, each with a 'BYPASS' button and a list of EQ plugins: Abbey Road, CLA-2A Ster, and dbx-160 Ster. The EQ section for each channel includes a frequency knob (set to 1000 Hz), a gain knob (set to 0.0 dB), and a bandwidth knob (set to 1.5). Below the EQ is an 'ALL EQ' toggle (set to ON) and an 'EQ ON' indicator. The solo/mute section features 'SOLO' and 'MUTE' buttons and a fader. The bottom of the mixer shows a transport bar with a time display of 00:01:48.555.

The IR-L window shows settings for a 'Hall - 1' (Concert Hall) with a date of 24 Mar 2004 and a sample rate of 96000Hz. The emitter is identified as a Genelec S30D. A table compares 'Original' and 'Current' values for Convolution (1.85s), RT60 (1.4s), Channels (4), and Size (11267). The 'Reverb Time' is set to 1.85s, 'Latency' is 11ms, and 'Dry/Wet' is 100. The 'Output' level is 0.0. The window also includes a 'Full CPU' indicator and a 'Post Notification' checkbox.

	Original	Current
Convolution:	1.85s	1.85s
RT60:	1.4s	1.4s
Channels:	4	4
Size:	11267	11267
Distance:	13m	NA

The transport window includes buttons for Stop, Play, Record, and other transport functions. The time display shows 00:01:48:16.6 SMPTE and 00:00:00:00.0 SMPTE. There are also 'PUNCH' and 'LOCK' buttons.