

---

Subject: Update....

Posted by [mikeaudet](#) on Thu, 19 May 2022 15:00:55 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hi Everyone,

It's been tough to make progress this year, but I'm finally getting traction. I've just started testing a version of the PSCL that is designed to work with jBridge. For those who haven't used jBridge, it allows a 32 bit host to connect with 64 bit VST files. I just started testing it with some 64 bit Waves plugins. So far, so good. The updated PSCL has a low priority thread that checks for jBridge processes and moves them off the CPU used by the PARIS application. This way, we can run 64 bit VSTs on all but one available CPU cores, while not running into the thread-safety issues in the PARIS application.

jBridge can be found here:

<https://jstuff.wordpress.com/jbridge/>

My next move is to work on the kernel driver (scherzo.sys). I bought a new ASUS motherboard with a PCI slot, and the driver does not work with this new board. The new board uses a I/O MMU, which is a new thing for PCs. I suspect that this is the problem, but I'll know more next week. An I/O MMU puts the PCI bus behind a memory controller that has to be programmed in order to allow PCI cards to access main memory. It's an extra level of indirection put in place for security reasons. The driver was not designed for this kind of thing.

I still haven't gotten the EV security certificate. The eventually rejected by documents that were signed by a justice of the peace. It's completely insane. An accountant or a lawyer will do just fine, but a judge can't be trusted. It's nuts. I'm going to go see a notary after I get the kernel driver updated. I only get a year on the certificate, so I think it makes sense to wait until I have this next phase done.

That's all I have to report for now.

All the best,  
Mike

---

## File Attachments

1) [PARIS\\_with\\_Waves.jpg](#), downloaded 6084 times

**Edit Functions Settings EQ Aux Tracks Automation**

1	2	3	4	5	6	7	8	9	10
BYPASS	BYPASS	BYPASS	BYPASS	BYPASS	BYPASS	BYPASS	BYPASS	BYPASS	BYPASS
Abbey Road	<<<<<<<<<<<<<<<	IR-L full Ste	<<<<<<<<<<<<<<<						
CLA-2A Ster	<<<<<<<<<<<<<<<								
dbx-160 Ster	<<<<<<<<<<<<<<<								
EQ 1 OFF	EQ 1 OFF	EQ 1 OFF	EQ 1 OFF	EQ 1 OFF	EQ 1 OFF	EQ 1 OFF	EQ 1 OFF	EQ 1 OFF	EQ 1 OFF
Hz 1000	Hz 1000	Hz 1000	Hz 1000	Hz 1000	Hz 1000	Hz 1000	Hz 1000	Hz 1000	Hz 1000
dB 0.0	dB 0.0	dB 0.0	dB 0.0	dB 0.0	dB 0.0	dB 0.0	dB 0.0	dB 0.0	dB 0.0
BW 1.5	BW 1.5	BW 1.5	BW 1.5	BW 1.5	BW 1.5	BW 1.5	BW 1.5	BW 1.5	BW 1.5
ALL EQ ON	ALL EQ ON	ALL EQ ON	ALL EQ ON	ALL EQ ON	ALL EQ ON	ALL EQ ON	ALL EQ ON	ALL EQ ON	ALL EQ ON
EQ ON	EQ ON	EQ ON	EQ ON	EQ ON	EQ ON	EQ ON	EQ ON	EQ ON	EQ ON
OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN	OPEN
L 100	R 100	L 100	R 100	L 100	R 100	L 100	R 100	L 100	R 100
SOLO MUTE	SOLO MUTE	SOLO MUTE	SOLO MUTE	SOLO MUTE	SOLO MUTE	SOLO MUTE	SOLO MUTE	SOLO MUTE	SOLO MUTE
1	2	3	4	5	6	7	8	9	
0.0	0.0	0.0							
REC AUTO	REC AUTO	REC AUTO	REC						

The main interface displays a mixer console with ten channels. Each channel has a bypass button, a list of plugins (Abbey Road, CLA-2A Ster, dbx-160 Ster), an EQ section with frequency, gain, and bandwidth controls, a solo/mute section, and a fader. An IR-L reverb plugin window is open, showing settings for a concert hall, including reverb time, RT60, and channels.

Options:

Post Notific

Transport: [Untitled Project]

The transport control window features standard playback buttons (stop, play, record, etc.), a punch button, and a lock button. It includes a large time display showing 00:01:48:16.5 and a smaller display for SMPTE time 00:00:00:00.0.

Disable smiles in this message