

---

Subject: Update....

Posted by [mikeaudet](#) on Thu, 19 May 2022 15:00:55 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hi Everyone,

It's been tough to make progress this year, but I'm finally getting traction. I've just started testing a version of the PSCL that is designed to work with jBridge. For those who haven't used jBridge, it allows a 32 bit host to connect with 64 bit VST files. I just started testing it with some 64 bit Waves plugins. So far, so good. The updated PSCL has a low priority thread that checks for jBridge processes and moves them off the CPU used by the PARIS application. This way, we can run 64 bit VSTs on all but one available CPU cores, while not running into the thread-safety issues in the PARIS application.

jBridge can be found here:

<https://jstuff.wordpress.com/jbridge/>

My next move is to work on the kernel driver (scherzo.sys). I bought a new ASUS motherboard with a PCI slot, and the driver does not work with this new board. The new board uses a I/O MMU, which is a new thing for PCs. I suspect that this is the problem, but I'll know more next week. An I/O MMU puts the PCI bus behind a memory controller that has to be programmed in order to allow PCI cards to access main memory. It's an extra level of indirection put in place for security reasons. The driver was not designed for this kind of thing.

I still haven't gotten the EV security certificate. The eventually rejected by documents that were signed by a justice of the peace. It's completely insane. An accountant or a lawyer will do just fine, but a judge can't be trusted. It's nuts. I'm going to go see a notary after I get the kernel driver updated. I only get a year on the certificate, so I think it makes sense to wait until I have this next phase done.

That's all I have to report for now.

All the best,  
Mike

---

## File Attachments

1) [PARIS\\_with\\_Waves.jpg](#), downloaded 8810 times

Edit Functions Settings EQ Aux Tracks Automation

The image shows a mixer interface with 10 channels. Each channel has a 'BYPASS' button, a list of EQ presets (Abbey Road, CLA-2A Ster, dbx-160 Ster), and an 'EQ 1 OFF' toggle. The EQ section includes frequency (Hz) knobs set to 1000, gain (dB) knobs set to 0.0, and bandwidth (BW) knobs set to 1.5. Below the EQ are 'ALL EQ' and 'EQ ON' toggles, and an 'OPEN' button. Further down are stereo level controls (L 100, R 100), solo/mute buttons, and a fader with a scale from 0 to 70. At the bottom of each channel are solo (S), auto (A), and record (REC) buttons, along with a 'REC' indicator.

The IR-L plugin window shows settings for a reverb effect. It includes a 'Full CPU' indicator, a name field 'Name: Hall - 1', and a type 'Type: Concert Hall'. Other fields include 'Date: 24 Mar 2004', 'SR: 96000Hz -> 44100Hz', and 'Emitter: Genelec 530D'. A table compares 'Original' and 'Current' settings for Convolution (1.85s), RT60 (1.4s), Channels (4), Size (11267), and Distance (13m). A graph on the right shows the impulse response. At the bottom, there are controls for 'Reverb Time' (0.000s), 'Conv. Length' (Full), 'Latency' (11ms), 'Dry/Wet' (100), 'Direct' (Off), and 'Output' levels (-2.8 and -2.6).

Options:  Post Notific

The transport control window shows playback controls: stop, play/pause, record, and next buttons. It includes a time display showing '00:01:48:16.6' and '00:00:00:00.0', and SMPTE timecode fields. Below the buttons are 'P', 'M', 'S', 'L', and '0' indicators, along with 'PUNCH' and 'LOCK' buttons.