

---

Subject: Patching question / help

Posted by [Ron Bloom](#) on Sat, 16 Aug 2008 18:02:44 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

OK so my head hurts as I am been trying to figure this out. I am sure I am missing something simple.

Details:

Newly running 3.0 on 98 machine

1 MEC

2 EDS cards

1 8 out card

1 8 in card

Trying to patch to second EDS card mixer:

Mec master A to mixer A (8 ins to mixer A 16 ins) working fine.

No option for second EDS card in object list window. Tried going to mixer

What am I doing wrong?

Thanks in advance

---

---

Subject: Re: Patching question / help

Posted by [Tom Bruhl](#) on Sat, 16 Aug 2008 18:55:45 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hi Ron,

Ya that's right. You can't patch across submixes.

You can make hardware connections if you have two Mecs or a 442.

What are you trying to do? If it's just record onto the second submix then you should switch the cards in the Global Master. Switch card A to Submix B. That'll assign all your hardware to Submix B. I'm not sure how you'll hear your master audio though???

I've always had multiple Mecs and left one as the Master A and swapped the second one around to different submixes this way.

If there's another reason for your patching question please post it.

Good luck,

Tom

"Ron" <concerts4u@prodigy.net> wrote in message news:48a71644\$1@linux...

>  
> OK so my head hurts as I am been trying to figure this out. I am sure I am  
> missing something simple.  
>  
> Details:  
>  
> Newly running 3.0 on 98 machine  
> 1 MEC  
> 2 EDS cards  
> 1 8 out card  
> 1 8 in card  
>  
> Trying to patch to second EDS card mixer:  
>  
> Mec master A to mixer A (8 ins to mixer A 16 ins) working fine.  
>  
> No option for second EDS card in object list window. Tried going to mixer  
> B from Mec master A and get this error "Could not make connection. You  
> cannot  
> patch objects across EDS-1000 card boundaries."  
>  
> What am I doing wrong?  
>  
> Thanks in advance

---

---

Subject: Re: Patching question / help  
Posted by [Ron Bloom](#) on Sat, 16 Aug 2008 19:24:31 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Tom,

I have an extra MEC would it be a good idea to use it or just stay the way I am with one. What are the advantages?

Back to the other question. I see it in the Globe Master - what should I set sub mix 1 to Virtual, or Native?

Thanks man!

"Tom Bruhl" <arpeggio@comcast.net> wrote:

>Hi Ron,

>  
>Ya that's right. You can't patch across submixes.  
>You can make hardware connections if you have two  
>Mecs or a 442.  
>  
>What are you trying to do? If it's just record onto the  
>second submix then you should switch the cards in the Global Master.  
>Switch card A to Submix B. That'll assign all your hardware to  
>Submix B. I'm not sure how you'll hear your master audio though???  
>I've always had multiple Mecs and left one as the Master A and swapped  
>the second one around to different submixes this way.  
>  
>If there's another reason for your patching question please post it.  
>  
>Good luck,  
>Tom  
>  
>  
>  
>  
>"Ron" <concerts4u@prodigy.net> wrote in message news:48a71644\$1@linux...  
>>  
>> OK so my head hurts as I am been trying to figure this out. I am sure  
I am  
>> missing something simple.  
>>  
>> Details:  
>>  
>> Newly running 3.0 on 98 machine  
>> 1 MEC  
>> 2 EDS cards  
>> 1 8 out card  
>> 1 8 in card  
>>  
>> Trying to patch to second EDS card mixer:  
>>  
>> Mec master A to mixer A (8 ins to mixer A 16 ins) working fine.  
>>  
>> No option for second EDS card in object list window. Tried going to mixer  
>> B from Mec master A and get this error "Could not make connection. You  
  
>> cannot  
>> patch objects across EDS-1000 card boundaries."  
>>  
>> What am I doing wrong?  
>>  
>> Thanks in advance  
>

>

---

Subject: Re: Patching question / help  
Posted by [Tom Bruhl](#) on Sat, 16 Aug 2008 19:43:40 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Ron,

To answer your question:

I usually have to switch it to virtual first and then assign the cards (Mecs attached to them) as I want them. In your case with only one mec you may have to drag tracks around to hear what is on submix A through Submix B or vice versa. You need hardware attached to Card and Submix A to hear your 2 bus mix.

In rethinking this I would leave your card assignments as they are. Drag the tracks from A to card B and continue recording to Submix card A. If you had two Mecs then you wouldn't have to do that. Make sure they're all time locked before dragging. All audio from both A & B will be heard and mixed together this way.

Tom

"Ron" <concerts4u@prodigy.net> wrote in message news:48a7296f\$1@linux...

>

> Tom,

>

> I have an extra MEC would it be a good idea to use it or just stay the way

> I am with one. What are the advantages?

>

> Back to the other question. I see it in the Globle Master - what should I

> set sub mix 1 to Virtual, or Native?

>

> Thanks man!

>

> "Tom Bruhl" <arpeggio@comcast.net> wrote:

>>Hi Ron,

>>

>>Ya that's right. You can't patch across submixes.

>>You can make hardware connections if you have two

>>Mecs or a 442.

>>  
>>What are you trying to do? If it's just record onto the  
>>second submix then you should switch the cards in the Global Master.  
>>Switch card A to Submix B. That'll assign all your hardware to  
>>Submix B. I'm not sure how you'll hear your master audio though???  
>>I've always had multiple Mecs and left one as the Master A and swapped  
>>the second one around to different submixes this way.  
>>  
>>If there's another reason for your patching question please post it.  
>>  
>>Good luck,  
>>Tom  
>>  
>>  
>>  
>>  
>>"Ron" <concerts4u@prodigy.net> wrote in message news:48a71644\$1@linux...  
>>>  
>>> OK so my head hurts as I am been trying to figure this out. I am sure  
> I am  
>>> missing something simple.  
>>>  
>>> Details:  
>>>  
>>> Newly running 3.0 on 98 machine  
>>> 1 MEC  
>>> 2 EDS cards  
>>> 1 8 out card  
>>> 1 8 in card  
>>>  
>>> Trying to patch to second EDS card mixer:  
>>>  
>>> Mec master A to mixer A (8 ins to mixer A 16 ins) working fine.  
>>>  
>>> No option for second EDS card in object list window. Tried going to  
>>> mixer  
>>> B from Mec master A and get this error "Could not make connection. You  
>  
>>> cannot  
>>> patch objects across EDS-1000 card boundaries."  
>>>  
>>> What am I doing wrong?  
>>>  
>>> Thanks in advance  
>>  
>>  
>

---

---

Subject: Re: Patching question / help

Posted by [Ron Bloom](#) on Sat, 16 Aug 2008 19:58:29 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Tom - You Rock !! Been stumped for days. Today is a good day

So now I am very curious about using two MECS. Lets say I hook up the second one. Do I tie the 2nd EDS card to the 2nd MEC using the EDS cable? DO I keep the EDS cards connected to each other the same way they are now 10 pin and 16 pin cables attached? How will my patch bay settings change? Is there a tutorial or ref on setting them up?

Sorry for so many questions, but I am getting excited about this :-)

ron

"Tom Bruhl" <arpeggio@comcast.net> wrote:

>Ron,

>

>To answer your question:

>I usually have to switch it to virtual first and then assign the cards (Mecs

>attached to them) as I want them. In your case with only one mec you

>may have to drag tracks around to hear what is on submix A through Submix

B

>or vice versa. You need hardware attached to Card and Submix A to hear

>your 2 bus mix.

>

>In rethinking this I would leave your card assignments as they are. Drag

the

>tracks

>from A to card B and continue recording to Submix card A. If you had two

>Mecs

>then you wouldn't have to do that. Make sure they're all time locked before

>dragging.

>All audio from both A & B will be heard and mixed together this way.

>

>Tom

>

>

>

>

>

>"Ron" <concerts4u@prodigy.net> wrote in message news:48a7296f\$1@linux...

>>

>> Tom,

>>

>> I have an extra MEC would it be a good idea to use it or just stay the way

>> I am with one. What are the advantages?  
>>  
>> Back to the other question. I see it in the Global Master - what should  
I  
>> set sub mix 1 to Virtual, or Native?  
>>  
>> Thanks man!  
>>  
>> "Tom Bruhl" <arpeggio@comcast.net> wrote:  
>>>Hi Ron,  
>>>  
>>>Ya that's right. You can't patch across submixes.  
>>>You can make hardware connections if you have two  
>>>Mecs or a 442.  
>>>  
>>>What are you trying to do? If it's just record onto the  
>>>second submix then you should switch the cards in the Global Master.  
>>>Switch card A to Submix B. That'll assign all your hardware to  
>>>Submix B. I'm not sure how you'll hear your master audio though???  
>>>I've always had multiple Mecs and left one as the Master A and swapped  
>>>the second one around to different submixes this way.  
>>>  
>>>If there's another reason for your patching question please post it.  
>>>  
>>>Good luck,  
>>>Tom  
>>>  
>>>  
>>>  
>>>  
>>>"Ron" <concerts4u@prodigy.net> wrote in message news:48a71644\$1@linux...  
>>>>  
>>>> OK so my head hurts as I am been trying to figure this out. I am sure  
>> I am  
>>>> missing something simple.  
>>>>  
>>>> Details:  
>>>>  
>>>> Newly running 3.0 on 98 machine  
>>>> 1 MEC  
>>>> 2 EDS cards  
>>>> 1 8 out card  
>>>> 1 8 in card  
>>>>  
>>>> Trying to patch to second EDS card mixer:  
>>>>  
>>>> Mec master A to mixer A (8 ins to mixer A 16 ins) working fine.  
>>>>

>>>> No option for second EDS card in object list window. Tried going to  
  
>>>> mixer  
>>>> B from Mec master A and get this error "Could not make connection. You  
>>  
>>>> cannot  
>>>> patch objects across EDS-1000 card boundaries."  
>>>>  
>>>> What am I doing wrong?  
>>>>  
>>>> Thanks in advance  
>>>  
>>>  
>>  
>  
>

---

---

Subject: Re: Patching question / help  
Posted by [Tom Bruhl](#) on Sat, 16 Aug 2008 20:44:50 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Ron,

You are correct with all your connections.  
You will need a word clock cable to attach from mec A  
word clock out to Mec B word clock in . Your existing patchbays  
will still work but you may add a few things with the new hardware.

You will have the 20 bit master section of your second mec to add  
connections in your Paris patchbay after mec B shows up. You can  
always add cards to that one too for 24 bit recording/inserts. The spdif  
is always there for 24 bit data too.

I'm glad you're pumped! Make sure power is off and your eds cables are  
in working order. I smoked three mecs with a bad cable.

Tom

"Ron" <concerts4u@prodigy.net> wrote in message news:48a73165\$1@linux...  
>  
> Tom - You Rock !! Been stumped for days. Today is a good day  
>  
> So now I am very curious about using two MECS. Lets say I hook up the  
> second  
> one. Do I tie the 2nd EDS card to the 2nd MEC using the EDS cable? DO I



> keep the EDS cards connected to each other the same way they are now 10  
> pin  
> and 16 pin cables attached? How will my patch bay settings change? Is  
> there  
> a tutorial or ref on setting them up?  
>  
> Sorry for so many questions, but I am getting excited about this :-)  
> ron  
>  
> "Tom Bruhl" <arpeggio@comcast.net> wrote:  
>>Ron,  
>>  
>>To answer your question:  
>>I usually have to switch it to virtual first and then assign the cards  
>>(Mecs  
>>attached to them) as I want them. In your case with only one mec you  
>>may have to drag tracks around to hear what is on submix A through Submix  
> B  
>>or vice versa. You need hardware attached to Card and Submix A to hear  
>>your 2 bus mix.  
>>  
>>In rethinking this I would leave your card assignments as they are. Drag  
> the  
>>tracks  
>>from A to card B and continue recording to Submix card A. If you had two  
>  
>>Mecs  
>>then you wouldn't have to do that. Make sure they're all time locked  
>>before  
>  
>>dragging.  
>>All audio from both A & B will be heard and mixed together this way.  
>>  
>>Tom  
>>  
>>  
>>  
>>  
>>  
>>"Ron" <concerts4u@prodigy.net> wrote in message news:48a7296f\$1@linux...  
>>>  
>>> Tom,  
>>>  
>>> I have an extra MEC would it be a good idea to use it or just stay the  
> way  
>>> I am with one. What are the advantages?  
>>>  
>>> Back to the other question. I see it in the Globe Master - what should

> I  
>>> set sub mix 1 to Virtual, or Native?  
>>>  
>>> Thanks man!  
>>>  
>>> "Tom Bruhl" <arpeggio@comcast.net> wrote:  
>>>>Hi Ron,  
>>>>  
>>>>Ya that's right. You can't patch across submixes.  
>>>>You can make hardware connections if you have two  
>>>>Mecs or a 442.  
>>>>  
>>>>What are you trying to do? If it's just record onto the  
>>>>second submix then you should switch the cards in the Global Master.  
>>>>Switch card A to Submix B. That'll assign all your hardware to  
>>>>Submix B. I'm not sure how you'll hear your master audio though???  
>>>>I've always had multiple Mecs and left one as the Master A and swapped  
>>>>the second one around to different submixes this way.  
>>>>  
>>>>If there's another reason for your patching question please post it.  
>>>>  
>>>>Good luck,  
>>>>Tom  
>>>>  
>>>>  
>>>>  
>>>>  
>>>>"Ron" <concerts4u@prodigy.net> wrote in message news:48a71644\$1@linux...  
>>>>>  
>>>>> OK so my head hurts as I am been trying to figure this out. I am sure  
>>>> I am  
>>>>> missing something simple.  
>>>>>  
>>>>> Details:  
>>>>>  
>>>>> Newly running 3.0 on 98 machine  
>>>>> 1 MEC  
>>>>> 2 EDS cards  
>>>>> 1 8 out card  
>>>>> 1 8 in card  
>>>>>  
>>>>> Trying to patch to second EDS card mixer:  
>>>>>  
>>>>> Mec master A to mixer A (8 ins to mixer A 16 ins) working fine.  
>>>>>  
>>>>> No option for second EDS card in object list window. Tried going to  
>  
>>>>> mixer

```

>>>>> B from Mec master A and get this error "Could not make connection. You
>>>
>>>>> cannot
>>>>> patch objects across EDS-1000 card boundaries."
>>>>>
>>>>> What am I doing wrong?
>>>>>
>>>>> Thanks in advance
>>>>
>>>>
>>>
>>
>>
>

```

---



---

Subject: Re: Patching question / help  
 Posted by [Ron](#) on Sun, 17 Aug 2008 00:43:47 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Tom,

Sounds like a plan I will connect 2nd MEC tonight to the second EDS card  
 and be prepared to rock. Why type of cable is a "word clock cable" Kind of  
 looks like an oscilloscope connector. Where do you find one of these?  
 ron

"Tom Bruhl" <arpeggio@comcast.net> wrote:

```

>Ron,
>
>You are correct with all your connections.
>You will need a word clock cable to attach from mec A
>word clock out to Mec B word clock in . Your existing patchbays
>will still work but you may add a few things with the new hardware.
>
>You will have the 20 bit master section of your second mec to add
>connections in your Paris patchbay after mec B shows up. You can
>always add cards to that one too for 24 bit recording/inserts. The spdif
>is always there for 24 bit data too.
>
>I'm glad you're pumped! Make sure power is off and your eds cables are
>in working order. I smoked three mecs with a bad cable.
>
>Tom
>
>
>
>"Ron" <concerts4u@prodigy.net> wrote in message news:48a73165$1@linux...

```

>>  
>> Tom - You Rock !! Been stumped for days. Today is a good day  
>>  
>> So now I am very curious about using two MECS. Lets say I hook up the  
  
>> second  
>> one. Do I tie the 2nd EDS card to the 2nd MEC using the EDS cable? DO  
I  
>> keep the EDS cards connected to each other the same way they are now 10  
  
>> pin  
>> and 16 pin cables attached? How will my patch bay settings change? Is  
  
>> there  
>> a tutorial or ref on setting them up?  
>>  
>> Sorry for so many questions, but I am getting excited about this :-)  
>> ron  
>>  
>> "Tom Bruhl" <arpeggio@comcast.net> wrote:  
>>>Ron,  
>>>  
>>>To answer your question:  
>>>I usually have to switch it to virtual first and then assign the cards  
  
>>>(Mecs  
>>>attached to them) as I want them. In your case with only one mec you  
>>>may have to drag tracks around to hear what is on submix A through Submix  
>> B  
>>>or vice versa. You need hardware attached to Card and Submix A to hear  
>>>your 2 bus mix.  
>>>  
>>>In rethinking this I would leave your card assignments as they are. Drag  
>> the  
>>>tracks  
>>>from A to card B and continue recording to Submix card A. If you had  
two  
>>  
>>>Mecs  
>>>then you wouldn't have to do that. Make sure they're all time locked  
  
>>>before  
>>  
>>>dragging.  
>>>All audio from both A & B will be heard and mixed together this way.  
>>>  
>>>Tom  
>>>

>>>  
>>>  
>>>  
>>>  
>>>"Ron" <concerts4u@prodigy.net> wrote in message news:48a7296f\$1@linux...  
>>>>  
>>>> Tom,  
>>>>  
>>>> I have an extra MEC would it be a good idea to use it or just stay the  
>> way  
>>>> I am with one. What are the advantages?  
>>>>  
>>>> Back to the other question. I see it in the Globle Master - what should  
>> I  
>>>> set sub mix 1 to Virtual, or Native?  
>>>>  
>>>> Thanks man!  
>>>>  
>>>> "Tom Bruhl" <arpeggio@comcast.net> wrote:  
>>>>>Hi Ron,  
>>>>>  
>>>>>Ya that's right. You can't patch across submixes.  
>>>>>You can make hardware connections if you have two  
>>>>>Mecs or a 442.  
>>>>>  
>>>>>What are you trying to do? If it's just record onto the  
>>>>>second submix then you should switch the cards in the Global Master.  
>>>>>Switch card A to Submix B. That'll assign all your hardware to  
>>>>>Submix B. I'm not sure how you'll hear your master audio though???  
>>>>>I've always had multiple Mecas and left one as the Master A and swapped  
>>>>>the second one around to different submixes this way.  
>>>>>  
>>>>>If there's another reason for your patching question please post it.  
>>>>>  
>>>>>Good luck,  
>>>>>Tom  
>>>>>  
>>>>>  
>>>>>  
>>>>>  
>>>>>"Ron" <concerts4u@prodigy.net> wrote in message news:48a71644\$1@linux...  
>>>>>>  
>>>>>> OK so my head hurts as I am been trying to figure this out. I am sure  
>>>>> I am  
>>>>>> missing something simple.  
>>>>>>  
>>>>>> Details:  
>>>>>>

>>>>> Newly running 3.0 on 98 machine  
>>>>> 1 MEC  
>>>>> 2 EDS cards  
>>>>> 1 8 out card  
>>>>> 1 8 in card  
>>>>>  
>>>>> Trying to patch to second EDS card mixer:  
>>>>>  
>>>>> Mec master A to mixer A (8 ins to mixer A 16 ins) working fine.  
>>>>>  
>>>>> No option for second EDS card in object list window. Tried going to  
>>  
>>>>> mixer  
>>>>> B from Mec master A and get this error "Could not make connection.  
You  
>>>>  
>>>>> cannot  
>>>>> patch objects across EDS-1000 card boundaries."  
>>>>>  
>>>>> What am I doing wrong?  
>>>>>  
>>>>> Thanks in advance  
>>>>>  
>>>>>  
>>>>  
>>>  
>>>  
>>  
>>  
>>  
>  
>

---

---

Subject: Re: Patching question / help  
Posted by [audioguy\\_editout\\_](#) on Sun, 17 Aug 2008 14:57:16 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Any good quality short 75 Ohm BNC to BNC cable will do nicely. Try a local pro video supplier or a music store that sells computer software/hardware. If you still can't find one, go to your local electronics supply store (or the aforementioned video supplier) and get two BNC to F-type adapters and use an RG6 TV cable between.

Like this:

<http://www.trianglecables.com/200-130.html>

David.

Ron wrote:

> Tom,

>

> Sounds like a plan I will connect 2nd MEC tonight to the second EDS card

> and be prepared to rock. Why type of cable is a "word clock cable" Kind of

> looks like an oscilloscope connector. Where do you find one of these?

> ron

>

> "Tom Bruhl" <arpegio@comcast.net> wrote:

>> Ron,

>>

>> You are correct with all your connections.

>> You will need a word clock cable to attach from mec A

>> word clock out to Mec B word clock in . Your existing patchbays

>> will still work but you may add a few things with the new hardware.

>>

>> You will have the 20 bit master section of your second mec to add

>> connections in your Paris patchbay after mec B shows up. You can

>> always add cards to that one too for 24 bit recording/inserts. The spdif

>> is always there for 24 bit data too.

>>

>> I'm glad you're pumped! Make sure power is off and your eds cables are

>> in working order. I smoked three mecs with a bad cable.

>>

>> Tom

>>

>>

>>

>> "Ron" <concerts4u@prodigy.net> wrote in message news:48a73165\$1@linux...

>>> Tom - You Rock !! Been stumped for days. Today is a good day

>>>

>>> So now I am very curious about using two MECS. Lets say I hook up the

>

>>> second

>>> one. Do I tie the 2nd EDS card to the 2nd MEC using the EDS cable? DO

> |

>>> keep the EDS cards connected to each other the same way they are now 10

>

>>> pin

>>> and 16 pin cables attached? How will my patch bay settings change? Is

>

>>> there

>>> a tutorial or ref on setting them up?

>>>

>>> Sorry for so many questions, but I am getting excited about this :-)

>>> ron

>>>

>>> "Tom Bruhl" <arpegio@comcast.net> wrote:

>>>> Ron,  
>>>>  
>>>> To answer your question:  
>>>> I usually have to switch it to virtual first and then assign the cards  
>  
>>>> (Mecs  
>>>> attached to them) as I want them. In your case with only one mec you  
>>>> may have to drag tracks around to hear what is on submix A through Submix  
>>>> B  
>>>> or vice versa. You need hardware attached to Card and Submix A to hear  
>>>> your 2 bus mix.  
>>>>  
>>>> In rethinking this I would leave your card assignments as they are. Drag  
>>>> the  
>>>> tracks  
>>>> >from A to card B and continue recording to Submix card A. If you had  
>>>> two  
>>>> Mecs  
>>>> then you wouldn't have to do that. Make sure they're all time locked  
>  
>>>> before  
>>>> dragging.  
>>>> All audio from both A & B will be heard and mixed together this way.  
>>>>  
>>>> Tom  
>>>>  
>>>>  
>>>>  
>>>>  
>>>>  
>>>> "Ron" <concerts4u@prodigy.net> wrote in message news:48a7296f\$1@linux...  
>>>>> Tom,  
>>>>>  
>>>>> I have an extra MEC would it be a good idea to use it or just stay the  
>>>>> way  
>>>>> I am with one. What are the advantages?  
>>>>>  
>>>>> Back to the other question. I see it in the Globle Master - what should  
>>>>> I  
>>>>> set sub mix 1 to Virtual, or Native?  
>>>>>  
>>>>> Thanks man!  
>>>>>  
>>>>> "Tom Bruhl" <arpeggio@comcast.net> wrote:  
>>>>>> Hi Ron,  
>>>>>>  
>>>>>> Ya that's right. You can't patch across submixes.  
>>>>>> You can make hardware connections if you have two



>>>>> Mecs or a 442.  
>>>>>  
>>>>> What are you trying to do? If it's just record onto the  
>>>>> second submix then you should switch the cards in the Global Master.  
>>>>> Switch card A to Submix B. That'll assign all your hardware to  
>>>>> Submix B. I'm not sure how you'll hear your master audio though???  
>>>>> I've always had multiple Mecs and left one as the Master A and swapped  
>>>>> the second one around to different submixes this way.  
>>>>>  
>>>>> If there's another reason for your patching question please post it.  
>>>>>  
>>>>> Good luck,  
>>>>> Tom  
>>>>>  
>>>>>  
>>>>>  
>>>>> "Ron" <concerts4u@prodigy.net> wrote in message news:48a71644\$1@linux...  
>>>>>> OK so my head hurts as I am been trying to figure this out. I am sure  
>>>>> I am  
>>>>>> missing something simple.  
>>>>>>  
>>>>>> Details:  
>>>>>>  
>>>>>> Newly running 3.0 on 98 machine  
>>>>>> 1 MEC  
>>>>>> 2 EDS cards  
>>>>>> 1 8 out card  
>>>>>> 1 8 in card  
>>>>>>  
>>>>>> Trying to patch to second EDS card mixer:  
>>>>>>  
>>>>>> Mec master A to mixer A (8 ins to mixer A 16 ins) working fine.  
>>>>>>  
>>>>>> No option for second EDS card in object list window. Tried going to  
>>>>>> mixer  
>>>>>> B from Mec master A and get this error "Could not make connection."  
> You  
>>>>>> cannot  
>>>>>> patch objects across EDS-1000 card boundaries."  
>>>>>>  
>>>>>> What am I doing wrong?  
>>>>>>  
>>>>>> Thanks in advance  
>>>>>>  
>>>>>  
>>>>  
>>  
>

---