
Subject: Paris hardware problem part II
Posted by [Tom Bruhl](#) on Tue, 24 Jul 2007 05:03:36 GMT
[View Forum Message](#) <> [Reply to Message](#)

This is a multi-part message in MIME format.

-----=_NextPart_000_013D_01C7CD8E.7702C9B0
Content-Type: text/plain;
charset="iso-8859-1"
Content-Transfer-Encoding: quoted-printable

Okay, I got a new rig fired up and booting properly with Paris with XP = Pro.

Here's what I've done so far:

- 1) I checked all SCSI cables and they turned out to be fine with one EDS card. I did some finessing of the pins alignment.
- 2) Checked all clock and interconnect cables with two cards. They all seem to be fine using the same A card attached to the 442 and four different B cards as Aaron suggested.
- 3) Tried four cards as card B and they seemed to work with no hardware attached to them. Seemed good.
- 4) I tried to scale back to just one card to try each as an A card with = the 442 attached but now Paris won't boot. Major badness.

It says:"An error occurred while reading the "Default Project" for new = project settings.

A new empty project will be created instead. There are not = enough resources

available." I click that away and it then says:

"Error in creating new project. There are not enough resources = available."

The readme says to try reinstalling the Paris drivers. I did but no = help there.

Two cards have given me the same results. I assume it's a driver = issue

or something else. I tried reducing the cache size in Paris.cfg but = that

didn't help either. I am seeing the Paris MIDI driver and a single = Scherzo.

When I click the faulty Paris project away it takes Windows with it = usually.

increase the cache, disk I/O and buffers again.

128/80/8/med or something like that always worked for me.
Change the settings with a text editor and restart Paris.

David.

Tom Bruhl wrote:

> Okay, I got a new rig fired up and booting properly with Paris with XP Pro.
> Here's what I've done so far:
>
> 1) I checked all SCSI cables and they turned out to be fine with
> one EDS card. I did some finessing of the pins alignment.
>
> 2) Checked all clock and interconnect cables with two cards.
> They all seem to be fine using the same A card attached to the 442
> and four different B cards as Aaron suggested.
>
> 3) Tried four cards as card B and they seemed to work with no hardware
> attached to them. Seemed good.
>
> 4) I tried to scale back to just one card to try each as an A card with the
> 442 attached but now Paris won't boot. Major badness.
>
> It says:"An error occurred while reading the "Default Project" for new
> project settings.
> A new empty project will be created instead. There are not
> enough resources
> available." I click that away and it then says:
> "Error in creating new project. There are not enough resources
> available."
>
> The readme says to try reinstalling the Paris drivers. I did but no
> help there.
> Two cards have given me the same results. I assume it's a driver issue
> or something else. I tried reducing the cache size in Paris.cfg but that
> didn't help either. I am seeing the Paris MIDI driver and a single
> Scherzo.
> When I click the faulty Paris project away it takes Windows with it
> usually.
>
> I really don't have time for this crap (not that it's your fault) but
> it's making me rethink
> everything all of the sudden.
>
> Oh and since Paris hasn't been in front of Cubase feeding it ADAT WC I
> can't open any

> of my Cubase projects. I get a white screen and can go nowhere. Great huh?
> This is getting disgusting. Sorry for the attitude but I have no time,
> tons of gigs and
> studio work and I can't get either system to run.
>
> Anything at this point would be better than what I've got.
> Thanks for whatever you can come up with,
> Tom
>
>
>
> I choose Polesoft Lockspam to fight spam, and you?
> <http://www.polesoft.com/refer.html>

Subject: Re: Paris hardware problem part II
Posted by [JeffH](#) on Tue, 24 Jul 2007 05:07:42 GMT
[View Forum Message](#) <> [Reply to Message](#)

Tom,

It's 10pm pacific. I'll be up a couple hours so call me. DON't know if I can help much but I'll do what I can.

Jeff
503-704-3701

Bruhl wrote:

> Okay, I got a new rig fired up and booting properly with Paris with XP Pro.
> Here's what I've done so far:
>
> 1) I checked all SCSI cables and they turned out to be fine with
> one EDS card. I did some finessing of the pins alignment.
>
> 2) Checked all clock and interconnect cables with two cards.
> They all seem to be fine using the same A card attached to the 442
> and four different B cards as Aaron suggested.
>
> 3) Tried four cards as card B and they seemed to work with no hardware
> attached to them. Seemed good.
>
> 4) I tried to scale back to just one card to try each as an A card with the
> 442 attached but now Paris won't boot. Major badness.
>
> It says:"An error occurred while reading the "Default Project" for new
> project settings.
> A new empty project will be created instead. There are not
> enough resources

> available." I click that away and it then says:
> "Error in creating new project. There are not enough resources
> available."
>
> The readme says to try reinstalling the Paris drivers. I did but no
> help there.
> Two cards have given me the same results. I assume it's a driver issue
> or something else. I tried reducing the cache size in Paris.cfg but that
> didn't help either. I am seeing the Paris MIDI driver and a single
> Scherzo.
> When I click the faulty Paris project away it takes Windows with it
> usually.
>
> I really don't have time for this crap (not that it's your fault) but
> it's making me rethink
> everything all of the sudden.
>
> Oh and since Paris hasn't been in front of Cubase feeding it ADAT WC I
> can't open any
> of my Cubase projects. I get a white screen and can go nowhere. Great huh?
> This is getting disgusting. Sorry for the attitude but I have no time,
> tons of gigs and
> studio work and I can't get either system to run.
>
> Anything at this point would be better than what I've got.
> Thanks for whatever you can come up with,
> Tom
>
>
>
> I choose Polesoft Lockspam to fight spam, and you?
> <http://www.polesoft.com/refer.html>

Subject: Re: Paris hardware problem part II
Posted by [DJ](#) on Tue, 24 Jul 2007 05:21:10 GMT
[View Forum Message](#) <> [Reply to Message](#)

This is a multi-part message in MIME format.

-----=_NextPart_000_04E5_01C7CD80.27BCA190
Content-Type: text/plain;
charset="iso-8859-1"
Content-Transfer-Encoding: quoted-printable

Tom,

does your Default project have a bunch of patching in the virtual =

patchbay? I've had the same message happen when I disconnected a MEC and =
I had previously had 4 x MECs with a default patch routing. with 3 x =
MECs, it freaked out because the patch routing was for 4 x MECs and it =
suddenly felt insecure and inadequate that it couldn't meet the needs of =
it's routing config with fewer resources available., I guess.

"Tom Bruhl" <arpeggio@comcast.net> wrote in message =
news:46a58928@linux...

Okay, I got a new rig fired up and booting properly with Paris with XP =
Pro.

Here's what I've done so far:

- 1) I checked all SCSI cables and they turned out to be fine with
one EDS card. I did some finessing of the pins alignment.
- 2) Checked all clock and interconnect cables with two cards.
They all seem to be fine using the same A card attached to the 442
and four different B cards as Aaron suggested.
- 3) Tried four cards as card B and they seemed to work with no hardware
attached to them. Seemed good.
- 4) I tried to scale back to just one card to try each as an A card =
with the
442 attached but now Paris won't boot. Major badness.

It says:"An error occurred while reading the "Default Project" for new =
project settings.

A new empty project will be created instead. There are not =
enough resources

available." I click that away and it then =
says:

"Error in creating new project. There are not enough resources =
available."

The readme says to try reinstalling the Paris drivers. I did but =
no help there.

Two cards have given me the same results. I assume it's a driver =
issue

or something else. I tried reducing the cache size in Paris.cfg =
but that

didn't help either. I am seeing the Paris MIDI driver and a single =
Scherzo.

When I click the faulty Paris project away it takes Windows with it =
usually.

I really don't have time for this crap (not that it's your fault) but =
it's making me rethink
everything all of the sudden.

Oh and since Paris hasn't been in front of Cubase feeding it ADAT WC I =
can't open any

of my Cubase projects. I get a white screen and can go nowhere. =
Great huh?

This is getting disgusting. Sorry for the attitude but I have no =
time, tons of gigs and=20
studio work and I can't get either system to run.

Anything at this point would be better than what I've got.
Thanks for whatever you can come up with,=20
Tom

I choose Polesoft Lockspam to fight spam, and you?

<http://www.polesoft.com/refer.html>
-----=_NextPart_000_04E5_01C7CD80.27BCA190
Content-Type: text/html;
charset="iso-8859-1"
Content-Transfer-Encoding: quoted-printable

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html"; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.6000.16414" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT face=3DArial size=3D2>Tom,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>does your Default project have a bunch =
of patching=20
in the virtual patchbay? I've had the same message happen when I =
disconnected a=20
MEC and I had previously had 4 x MECs with a default patch routing. with =
3 x=20
MECs, it freaked out because the patch routing was for 4 x MECs and it =
suddenly=20
felt insecure and inadequate that it couldn't meet the needs of it's =
routing=20
config with fewer resources available., I guess.</FONT></DIV>
<BLOCKQUOTE dir=3Dltr=20
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">
<DIV>"Tom Bruhl" &lt;A=20
href=3D"mailto:arpeggio@comcast.net">arpeggio@comcast.net</A>&gt; wrote =
```

news:46a58928@linux...</DIV>
<DIV>Okay, I got a new rig fired up and =
booting=20

<DIV>Here's what I've done so far:</DIV>

<DIV>1) I checked all SCSI cables and they =
turned out=20
to be fine with</DIV>

finessing of the pins alignment.</DIV>

<DIV>2) Checked all clock and interconnect = cables with=20
two cards.</DIV>

the same A card attached to the 442

Aaron suggested.

3) Tried four cards as card B and =
they seemed to=20

 attached to =
them. Seemed=20
good.</DIV>

<DIV>4) I tried to scale back to just one = card to try=20

 442 attached but =
now Paris=20
won't boot. Major badness.

<DIV>It says:"An error occurred while =
reading the=20

<DIV><FONT face=3DArial=20
=

new empty project will be created instead. There are not enough=20
resources</DIV>

better than what=20
I've got.</DIV>
<DIV>Thanks for whatever you can come up=20
with, </DIV>
<DIV>Tom</DIV>
<DIV> </DIV>
<DIV>

I choose Polesoft Lockspam to fight spam, =
and=20
you?
<A=20
=
href=3D"http://www.polesoft.com/refer.html">http://www.polesoft.com/refer=
..html </DIV></BLOCKQUOTE ></BODY></HTML>

-----=_NextPart_000_04E5_01C7CD80.27BCA190--

Subject: Re: Paris hardware problem part II
Posted by [Tom Bruhl](#) on Tue, 24 Jul 2007 05:31:59 GMT
[View Forum Message](#) <> [Reply to Message](#)

This is a multi-part message in MIME format.

-----=_NextPart_000_0026_01C7CD92.6DF52490
Content-Type: text/plain;
charset="iso-8859-1"
Content-Transfer-Encoding: quoted-printable

David,
I'll try that first.

Jeff,
Thanks and I might take you up on the offer.

DJ,
It's the default project for a 442 sending to 4 channels
so I'll delete all the patches and save it if I can get into the=20
project.

Thanks for the fast response you guys!
Tom
"Dave(EK Sound)" <audioguy_editout_@shaw.ca> wrote in message =
news:46a58a03\$1@linux...
A fresh install zeros out your config file. Go in and=20
increase the cache, disk I/O and buffers again.

128/80/8/med or something like that always worked for me.=20
Change the settings with a text editor and restart Paris.

David.

Tom Bruhl wrote:

> Okay, I got a new rig fired up and booting properly with Paris with =
XP Pro.
> Here's what I've done so far:
> =20
> 1) I checked all SCSI cables and they turned out to be fine with
> one EDS card. I did some finessing of the pins alignment.
> =20
> 2) Checked all clock and interconnect cables with two cards.
> They all seem to be fine using the same A card attached to the =
442
> and four different B cards as Aaron suggested.
> =20
> 3) Tried four cards as card B and they seemed to work with no =
hardware
> attached to them. Seemed good.
> =20
> 4) I tried to scale back to just one card to try each as an A card =
with the
> 442 attached but now Paris won't boot. Major badness.
> =20
> It says:"An error occurred while reading the "Default Project" for =
new=20
> project settings.
> A new empty project will be created instead. There are =
not=20
> enough resources
> available." I click that away and it then =
says:
> "Error in creating new project. There are not enough resources=20
> available."
> =20
> The readme says to try reinstalling the Paris drivers. I did but =
no=20
> help there.
> Two cards have given me the same results. I assume it's a driver =
issue
> or something else. I tried reducing the cache size in Paris.cfg =
but that
> didn't help either. I am seeing the Paris MIDI driver and a =
single=20
> Scherzo.
> When I click the faulty Paris project away it takes Windows with =
it=20
> usually.

> =20
> I really don't have time for this crap (not that it's your fault) =
but=20
> it's making me rethink
> everything all of the sudden.
> =20
> Oh and since Paris hasn't been in front of Cubase feeding it ADAT WC =
I=20
> can't open any
> of my Cubase projects. I get a white screen and can go nowhere. =
Great huh?
> This is getting disgusting. Sorry for the attitude but I have no =
time,=20

> tons of gigs and=20
> studio work and I can't get either system to run.
> =20
> Anything at this point would be better than what I've got.
> Thanks for whatever you can come up with,=20
> Tom
> =20
> =20
> =20
> I choose Polesoft Lockspam to fight spam, and you?
> <http://www.polesoft.com/refer.html>

-----=_NextPart_000_0026_01C7CD92.6DF52490

Content-Type: text/html;
charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.2800.1400" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT face=3DArial size=3D2>David,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>I'll try that first.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>Jeff,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Thanks and I might take you up on the=20
offer.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>DJ,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>It's the default project for a 442 =
sending to 4=20
channels</FONT></DIV>
```

[illegible]

[illegible]

Lockspam to fight spam, and you?
> <A=20
=
href=3D"http://www.polesoft.com/refer.html">http://www.polesoft.com/refer=
..html</BLOCKQUOTE></BODY></HTML>

-----=_NextPart_000_0026_01C7CD92.6DF52490--

Subject: Re: Paris hardware problem part II
Posted by [Tom Bruhl](#) on Tue, 24 Jul 2007 06:16:04 GMT
[View Forum Message](#) <> [Reply to Message](#)

This is a multi-part message in MIME format.

-----=_NextPart_000_0050_01C7CD98.96A9EC30
Content-Type: text/plain;
charset="iso-8859-1"
Content-Transfer-Encoding: quoted-printable

David,
Your suggestion didn't totally make sense to me.
Which part of the Config should be set to 8?
I've never used a number that low there.
I don't have the option to adjust to med either for some reason.
Not sure what that's about.

I can tell you one thing though, the Midi drivers are not installed.
I go to install them manually and it says no good. I am pointing it
at the Paris folder with all the goods in it. Maybe I have faulty =
drivers?

That would explain all the crap since after I reinstalled a week ago.
I'll go look on the web for the drivers I guess.
Tom

I choose Polesoft Lockspam to fight spam, and you?
<http://www.polesoft.com/refer.html>
-----=_NextPart_000_0050_01C7CD98.96A9EC30
Content-Type: text/html;
charset="iso-8859-1"
Content-Transfer-Encoding: quoted-printable

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>

<META http-equiv=3DContent-Type content=3D"text/html"; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.2800.1400" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV>David,</DIV>
<DIV>Your suggestion didn't totally make =
sense to=20
me.</DIV>
<DIV>Which part of the Config should be set =
to=20
8?</DIV>
<DIV>I've never used a number that low=20
there.</DIV>
<DIV>I don't have the option to adjust to =
med either for=20
some reason.</DIV>
<DIV>Not sure what that's =
about.</DIV>
<DIV> </DIV>
<DIV>I can tell you one thing though, the =
Midi drivers=20
are not installed.</DIV>
<DIV>I go to install them manually and it =
says no=20
good. </DIV>
<DIV>at the Paris folder with all the goods =
in it. </DIV>
<DIV>Maybe I have faulty drivers?</DIV>
<DIV> </DIV>
<DIV>That would explain all the crap since =
after I=20
reinstalled a week ago.</DIV>
<DIV>I'll go look on the web for the drivers =
I=20
guess.</DIV>
<DIV>Tom</DIV>
<DIV> </DIV>
<DIV> </DIV>
<DIV> </DIV>
<DIV>

I choose Polesoft Lockspam to fight spam, =
and=20
you?
<A=20
href=3D"http://www.polesoft.com/refer.html">http://www.polesoft.com/refer=
..html </DIV></BODY></HTML>

-----=_NextPart_000_0050_01C7CD98.96A9EC30--

Subject: Re: Paris hardware problem part II
Posted by [Tom Bruhl](#) on Tue, 24 Jul 2007 06:39:36 GMT
[View Forum Message](#) <> [Reply to Message](#)

This is a multi-part message in MIME format.

-----=_NextPart_000_006C_01C7CD9B.DFB6E9C0
Content-Type: text/plain;
charset="iso-8859-1"
Content-Transfer-Encoding: quoted-printable

Okay everyone Jeff straightened me out right quick.

I had made a default project . . . As I now understand from Jeff, that's the final stage after all is totally well with hardware, plugins drivers etc.. Jeff had me remove the default project and all was better.

So back to my final testing of cards and I'll keep you informed on the next step with the Magma in a week or so.

I can at least sleep tonight knowing I have another trick up my sleeve to harness Paris' unruly tendencies.
T.

"Tom Bruhl" <arpeggio@comcast.net> wrote in message =
news:46a59a24@linux...

David,

Your suggestion didn't totally make sense to me.

Which part of the Config should be set to 8?

I've never used a number that low there.

I don't have the option to adjust to med either for some reason.

Not sure what that's about.

I can tell you one thing though, the Midi drivers are not installed. I go to install them manually and it says no good. I am pointing it at the Paris folder with all the goods in it. Maybe I have faulty = drivers?

That would explain all the crap since after I reinstalled a week ago. I'll go look on the web for the drivers I guess.

Tom

I choose Polesoft Lockspam to fight spam, and you?

http://www.polesoft.com/refer.html
-----=_NextPart_000_006C_01C7CD9B.DFB6E9C0
Content-Type: text/html;
charset="iso-8859-1"
Content-Transfer-Encoding: quoted-printable

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html"; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.2800.1400" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT face=3DArial size=3D2>Okay everyone Jeff straightened me out =
right=20
quick.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>I had made a default project . . =
..&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>Jeff, that's the final stage after all =
is totally=20
well with hardware,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>plugins drivers etc.&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>Jeff had me =
remove the=20
default project</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>and all was better.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>So back to my final testing of cards =
and I'll keep=20
you informed</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>on the next step with the Magma in a =
week or=20
so.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>I can at least sleep tonight knowing I =
have another=20
trick up my</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>sleeve to&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>harness Paris' unruly=20
tendencies.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>T.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<BLOCKQUOTE dir=3Dltr=20
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">
  <DIV>"Tom Bruhl" &lt;<A=20
```

href=3D"mailto:arpeggio@comcast.net">arpeggio@comcast.net> wrote =
in message=20
news:46a59a24@linux...</DIV>
<DIV>David,</DIV>
<DIV>Your suggestion didn't totally make =
sense to=20
me.</DIV>
<DIV>Which part of the Config should be =
set to=20
8?</DIV>
<DIV>I've never used a number that low=20
there.</DIV>
<DIV>I don't have the option to adjust to =
med either=20
for some reason.</DIV>
<DIV>Not sure what that's =
about.</DIV>
<DIV> </DIV>
<DIV>I can tell you one thing though, the =
Midi drivers=20
are not installed.</DIV>
<DIV>I go to install them manually and it =
says no=20
good. </DIV>
<DIV>at the Paris folder with all the =
goods in=20
it. </DIV>
<DIV> </DIV>
<DIV>That would explain all the crap since =
after I=20
reinstalled a week ago.</DIV>
<DIV>I'll go look on the web for the =
drivers I=20
guess.</DIV>
<DIV>Tom</DIV>
<DIV> </DIV>
<DIV> </DIV>
<DIV> </DIV>
<DIV>

I choose Polesoft Lockspam to fight spam, =
and=20
you?
<A=20
=
href=3D"http://www.polesoft.com/refer.html">http://www.polesoft.com/refer=
..html </DIV></BLOCKQUOTE ></BODY></HTML>

-----=_NextPart_000_006C_01C7CD9B.DFB6E9C0--
