
Subject: Update....

Posted by [mikeaudet](#) on Thu, 19 May 2022 15:00:55 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi Everyone,

It's been tough to make progress this year, but I'm finally getting traction. I've just started testing a version of the PSCL that is designed to work with jBridge. For those who haven't used jBridge, it allows a 32 bit host to connect with 64 bit VST files. I just started testing it with some 64 bit Waves plugins. So far, so good. The updated PSCL has a low priority thread that checks for jBridge processes and moves them off the CPU used by the PARIS application. This way, we can run 64 bit VSTs on all but one available CPU cores, while not running into the thread-safety issues in the PARIS application.

jBridge can be found here:

<https://jstuff.wordpress.com/jbridge/>

My next move is to work on the kernel driver (scherzo.sys). I bought a new ASUS motherboard with a PCI slot, and the driver does not work with this new board. The new board uses a I/O MMU, which is a new thing for PCs. I suspect that this is the problem, but I'll know more next week. An I/O MMU puts the PCI bus behind a memory controller that has to be programmed in order to allow PCI cards to access main memory. It's an extra level of indirection put in place for security reasons. The driver was not designed for this kind of thing.

I still haven't gotten the EV security certificate. The eventually rejected by documents that were signed by a justice of the peace. It's completely insane. An accountant or a lawyer will do just fine, but a judge can't be trusted. It's nuts. I'm going to go see a notary after I get the kernel driver updated. I only get a year on the certificate, so I think it makes sense to wait until I have this next phase done.

That's all I have to report for now.

All the best,
Mike

File Attachments

1) [PARIS_with_Waves.jpg](#), downloaded 4712 times

Edit Functions Settings EQ Aux Tracks Automation

The screenshot displays a mixer interface with 10 tracks. Each track has a 'BYPASS' button, a list of EQ presets (Abbey Road, CLA-2A Ster, dbx-160 Ster), and an 'EQ 1 OFF' toggle. Below these are frequency sliders for 1000 Hz, gain sliders for 0.0 dB, and bandwidth sliders for 1.5. An 'ALL EQ' toggle is present for each track. Further down are 'EQ ON' toggles and 'L/R' stereo width sliders (e.g., L 100, R 100). Each track also features 'SOLO' and 'MUTE' buttons, and a vertical fader with a gain slider (e.g., 0.0). At the bottom of the mixer are 'REC' and 'AUTO' buttons.

IR-L Full CPU
Name: Hall - 1
Type: Concert Hall
Date: 24 Mar 2004
SR: 96000Hz -> 44100Hz
Emitter: Genelec 530D

	Original	Current
Convolution:	1.85s	1.85s
RT60:	1.4s	1.4s
Channels:	4	4
Size:	11267	11267
Distance:	13m	NA

Reverb Time: 0.000s
Conv. Start: 0.000s
Conv. Length: Full
Latency: 11ms
Dry/Wet: 100
Direct: Off
Output: 0.0
Pre-delay: 0.000Sec

Options:

Post Notific

Transport: [Untitled Project]

The transport control panel includes buttons for previous, next, stop, play, and record. Below these are buttons for 'P', 'M', 'S', 'L', and '0'. There are also 'PUNCH' and 'LOCK' buttons. A large digital display shows the current time as 00:01:48:16.6 and a SMPTE timecode as 00:00:00:00.0.

Disable smiles in this message