Subject: OT: Motherboard swap?? Posted by brandon[2] on Fri, 01 Sep 2006 12:55:10 GMT

View Forum Message <> Reply to Message

This is a multi-part message in MIME format.

-----=_NextPart_000_0111_01C6CD9B.F32597F0 Content-Type: text/plain;

charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

I know the answer to this question or at least I think I do, but I am hoping someone will tell me different. Is there a way to swap a motherboard with a totally different MB and reload all the drivers without wiping the HD clean and starting from scratch & still have a stable system?

Thanks.

--=20

Brandon

----=_NextPart_000_0111_01C6CD9B.F32597F0

Content-Type: text/html; charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">

<HTML><HEAD>

<META http-equiv=3DContent-Type content=3D"text/html; =

charset=3Diso-8859-1">

<META content=3D"MSHTML 6.00.2800.1476" name=3DGENERATOR>

<STYLE></STYLE>

</HEAD>

<BODY bgColor=3D#ffffff>

<DIV> </DIV>

<DIV>I know the answer to this question or at least I think I do, =

but</DIV>

<DIV>I am hoping someone will tell me different.</DIV>

<DIV>Is there a way to swap a motherboard with a totally different =

MB</DIV>

<DIV>and reload all the drivers without wiping the HD clean and starting =

from</DIV>

<DIV>scratch & amp; still have a stable system?</DIV>

<DIV> </DIV>

<DIV>Thanks.</DIV>

<DIV>
--
Brandon </DIV></BODY></HTML>

Subject: Re: OT: Motherboard swap??

```
Posted by John [1] on Fri, 01 Sep 2006 14:30:20 GMT
View Forum Message <> Reply to Message
Nope. Do a fresh install, make a ghost image and be happy.
John
"Brandon" <a@a.com> wrote:
>
>I know the answer to this question or at least I think I do, but
>I am hoping someone will tell me different.
>Is there a way to swap a motherboard with a totally different MB
>and reload all the drivers without wiping the HD clean and starting from
>scratch & still have a stable system?
>Thanks,
>--=20
>Brandon
><!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
><HTML><HEAD>
><META http-equiv=3DContent-Type content=3D"text/html; =
>charset=3Diso-8859-1">
><META content=3D"MSHTML 6.00.2800.1476" name=3DGENERATOR>
><STYLE></STYLE>
></HEAD>
><BODY bgColor=3D#ffffff>
><DIV>I know the answer to this question or at least I think I do, =
>but</DIV>
><DIV>I am hoping someone will tell me different.</DIV>
><DIV>Is there a way to swap a motherboard with a totally different =
>MB</DIV>
><DIV>and reload all the drivers without wiping the HD clean and starting
>from</DIV>
><DIV>scratch & still have a stable system?</DIV>
><DIV>Thanks,</DIV>
```

><DIV>
--
Brandon </DIV></BODY></HTML>

Subject: Re: Motherboard swap??

Posted by Deej [1] on Fri, 01 Sep 2006 14:55:24 GMT

View Forum Message <> Reply to Message

This is a multi-part message in MIME format.

----=_NextPart_000_002F_01C6CDA4.5D456F40 Content-Type: text/plain; charset="iso-8859-1" Content-Transfer-Encoding: quoted-printable

Maybe......if the old and new mobo uses the VIA chipset. I have = moved system drives from a mobos running VIA chipsets to mobo's (same = same or different brands) running newer versions of VIA chipsets and it = was as simple as just loading the new dirvers. I have never had any luck = moving from a VIA chipset to any other chipset and have never tried this = with any other kind of other *older to newer* versiuon of chipset other = than VIA. It might be worth a try if you're moving from an older mobo = with something like an older NForce to a newer NForce chipset, but be = sure to Ghost (or whatever backup you use) first, just in case. If = you're swapping chipsets, do a clean install.

Deej

"Brandon" <a@a.com> wrote in message news:44f82c23\$1@linux...

I know the answer to this question or at least I think I do, but I am hoping someone will tell me different.

Is there a way to swap a motherboard with a totally different MB and reload all the drivers without wiping the HD clean and starting = from

scratch & still have a stable system?

Thanks,

--=20

Brandon

----=_NextPart_000_002F_01C6CDA4.5D456F40

Content-Type: text/html; charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">

<HTML><HEAD>

<META http-equiv=3DContent-Type content=3D"text/html; =

```
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.2800.1106" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT face=3DArial size=3D2>Maybe......if the old and new mobo =
uses the VIA=20
chipset. </FONT><FONT face=3DArial size=3D2>I have =
moved system drives=20
</FONT><FONT face=3DArial size=3D2>from a mobos r</FONT><FONT =
face=3DArial=20
size=3D2>unning  VIA  chipsets to mobo's (same same or =
different brands)=20
</FONT><FONT face=3DArial size=3D2>running newer versions of =
VIA </FONT><FONT=20
face=3DArial size=3D2>chipsets </FONT><FONT face=3DArial size=3D2>and it =
was as simple=20
as just loading the new dirvers. I have never had any luck moving from a =
VIA=20
chipset to any other chipset and have never tried this with any other =
kind of=20
other *older to newer* versiuon of chipset other than VIA. It might be =
worth a=20
try if you're moving from an older mobo with something like an older =
NForce to a=20
newer NForce chipset, but be sure to Ghost (or whatever backup you use) =
first,=20
just in case. If you're swapping chipsets, do a clean =
install.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2>Deei</FONT></DIV>
<BLOCKQUOTE dir=3Dltr=20
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">
 <DIV>"Brandon" &lt;<A href=3D"mailto:a@a.com">a@a.com</A>&gt; wrote in =
message=20
 <A href=3D"news:44f82c23$1@linux">news:44f82c23$1@linux
 <DIV><FONT face=3DArial></FONT>&nbsp;</DIV><FONT face=3DArial>
 <DIV>I know the answer to this question or at least I think I do, =
but</DIV>
 <DIV>I am hoping someone will tell me different.</DIV>
 <DIV>Is there a way to swap a motherboard with a totally different =
MB</DIV>
 <DIV>and reload all the drivers without wiping the HD clean and =
starting=20
 from</DIV>
 <DIV>scratch & amp; still have a stable system?</DIV>
 <DIV>&nbsp;</DIV>
```

```
<DIV>Thanks,</DIV>
  <DIV><BR>--- <BR>Brandon </FONT></DIV></BLOCKQUOTE></BODY></HTML>
-----=_NextPart_000_002F_01C6CDA4.5D456F40--
```

Subject: Re: Motherboard swap??

Posted by Erick Kent on Mon, 04 Sep 2006 04:19:17 GMT

View Forum Message <> Reply to Message

This is a multi-part message in MIME format.

Content-Transfer-Encoding: quoted-printable

-----=_NextPart_000_002A_01C6CFAF.60AFFAD0 Content-Type: text/plain; charset="iso-8859-1"

Not sure how far you are into this thing, but you can do it and I have = done it many times. Just install the new motherboard and when windows = begins to boot it will begin installing the new hardware for your new = motherboard. All the stuff it can't find drivers for it will put an = exclamation point by in the device manager. Just go on the internet or = find your disks and load the drivers for the stuff it couldn't install. = Also, if you are using Windows XP you will have to call in and explain = to them what your doing (it will give you the number to call). Just tell = them you changed motherboards, read them a bunch of numbers off the = screen, they will read you a bunch of numbers to plug in, and your off.

--=20

Erick Kent

"Brandon" <a@a.com> wrote in message news:44f82c23\$1@linux...

I know the answer to this question or at least I think I do, but I am hoping someone will tell me different.

Is there a way to swap a motherboard with a totally different MB and reload all the drivers without wiping the HD clean and starting = from

scratch & still have a stable system?

Thanks,

--=20

Brandon
-----= NextPart 000 002A 01C6CFAF.60AFFAD0

Content-Type: text/html; charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

```
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.2900.2963" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT face=3D"Comic Sans MS" size=3D2>Not sure how far you are into =
this thing,=20
but you can do it and I have done it many times. Just install the new=20
motherboard and when windows begins to boot it will begin installing the =
new=20
hardware for your new motherboard. All the stuff it can't find drivers =
for it=20
will put an exclamation point by in the device manager. Just go on the =
internet=20
or find your disks and load the drivers for the stuff it couldn't =
install. Also.=20
if you are using Windows XP you will have to call in and explain to them =
what=20
your doing (it will give you the number to call). Just tell them you =
changed=20
motherboards, read them a bunch of numbers off the screen, they will =
read you a=20
bunch of numbers to plug in, and your off.</FONT></DIV>
<DIV><BR>-- <BR>Erick Kent</DIV>
<BLOCKQUOTE dir=3Dltr=20
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">
 <DIV>"Brandon" &lt;<A href=3D"mailto:a@a.com">a@a.com</A>&gt; wrote in =
message=20
 <A href=3D"news:44f82c23$1@linux">news:44f82c23$1@linux</A>...</DIV>
 <DIV><FONT face=3DArial></FONT>&nbsp;</DIV><FONT face=3DArial>
 <DIV>I know the answer to this question or at least I think I do, =
but</DIV>
 <DIV>I am hoping someone will tell me different.</DIV>
 <DIV>Is there a way to swap a motherboard with a totally different =
MB</DIV>
 <DIV>and reload all the drivers without wiping the HD clean and =
starting=20
 from</DIV>
 <DIV>scratch & amp; still have a stable system?</DIV>
 <DIV>&nbsp;</DIV>
 <DIV>Thanks,</DIV>
 <DIV><BR>-- <BR>Brandon </FONT></DIV></BLOCKQUOTE></BODY></HTML>
----= NextPart 000 002A 01C6CFAF.60AFFAD0--
```

Subject: Re: Motherboard swap?? Posted by Tom Bruhl on Mon, 04 Sep 2006 07:42:37 GMT

View Forum Message <> Reply to Message

This is a multi-part message in MIME format.

-----=_NextPart_000_0020_01C6CFD4.29F9F020 Content-Type: text/plain;

charset="iso-8859-1"

Content-Transfer-Encoding: quoted-printable

Erick.

That sounds easier than it seems?=20 I'll keep my note pad ready on the next reinstall. Next time maybe I'll succeed? Thanks for the tip, Tom

"Erick Kent" <erick at thefollower.com> wrote in message = news:44fba78a@linux...

Not sure how far you are into this thing, but you can do it and I have = done it many times. Just install the new motherboard and when windows = begins to boot it will begin installing the new hardware for your new = motherboard. All the stuff it can't find drivers for it will put an = exclamation point by in the device manager. Just go on the internet or = find your disks and load the drivers for the stuff it couldn't install. = Also, if you are using Windows XP you will have to call in and explain = to them what your doing (it will give you the number to call). Just tell = them you changed motherboards, read them a bunch of numbers off the = screen, they will read you a bunch of numbers to plug in, and your off.

--=20

Erick Kent

"Brandon" <a@a.com> wrote in message news:44f82c23\$1@linux...

I know the answer to this question or at least I think I do, but I am hoping someone will tell me different.

Is there a way to swap a motherboard with a totally different MB and reload all the drivers without wiping the HD clean and starting = from

scratch & still have a stable system?

Thanks,

--=20

Brandon=20

```
I choose Polesoft Lockspam to fight spam, and you?
http://www.polesoft.com/refer.html
----=_NextPart_000_0020_01C6CFD4.29F9F020
Content-Type: text/html;
charset="iso-8859-1"
Content-Transfer-Encoding: quoted-printable
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.2800.1400" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT face=3DArial size=3D2>Erick,</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>That sounds easier than it seems? =
</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>I'll keep my note pad ready on the next =
reinstall.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Next time maybe I'll =
succeed?</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Thanks for the tip.</FONT></DIV>
<DIV><FONT face=3DArial size=3D2>Tom</FONT></DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<DIV><FONT face=3DArial size=3D2></FONT>&nbsp;</DIV>
<BLOCKQUOTE dir=3Dltr=20
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">
 <DIV>"Erick Kent" &lt;erick at thefollower.com&gt; wrote in message <A =
 href=3D"news:44fba78a@linux">news:44fba78a@linux</A>...</DIV>
 <DIV><FONT face=3D"Comic Sans MS" size=3D2>Not sure how far you are =
into this=20
 thing, but you can do it and I have done it many times. Just install =
the new=20
 motherboard and when windows begins to boot it will begin installing =
the new=20
 hardware for your new motherboard. All the stuff it can't find drivers =
for it=20
 will put an exclamation point by in the device manager. Just go on the =
 internet or find your disks and load the drivers for the stuff it =
couldn't=20
 install. Also, if you are using Windows XP you will have to call in =
and=20
 explain to them what your doing (it will give you the number to call). =
```

```
Just=20
 tell them you changed motherboards, read them a bunch of numbers off =
the=20
 screen, they will read you a bunch of numbers to plug in, and your=20
 off.</FONT></DIV>
 <DIV><BR>--- <BR>Erick Kent</DIV>
 <BLOCKQUOTE dir=3Dltr=20
 style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">
  <DIV>"Brandon" &lt;<A href=3D"mailto:a@a.com">a@a.com</A>&gt; wrote =
in message=20
  <A href=3D"news:44f82c23$1@linux">news:44f82c23$1@linux</A>...</DIV>
  <DIV><FONT face=3DArial></FONT>&nbsp;</DIV><FONT face=3DArial>
  <DIV>I know the answer to this question or at least I think I do, =
but</DIV>
  <DIV>I am hoping someone will tell me different.</DIV>
  <DIV>Is there a way to swap a motherboard with a totally different =
MB</DIV>
  <DIV>and reload all the drivers without wiping the HD clean and =
starting=20
  from</DIV>
  <DIV>scratch & amp; still have a stable system?</DIV>
  <DIV>&nbsp;</DIV>
  <DIV>Thanks,</DIV>
  <DIV><BR>-- <BR>Brandon </FONT></DIV></BLOCKQUOTE></BLOCKQUOTE>
<DIV><FONT size=3D2><BR><BR>I choose Polesoft Lockspam to fight spam, =
and=20
vou?<BR><A=20
href=3D"http://www.polesoft.com/refer.html">http://www.polesoft.com/refer=
..html</A>&nbsp;&nbsp;&nbsp;</FONT></DIV></BODY ></HTML>
----= NextPart 000 0020 01C6CFD4.29F9F020--
```

Subject: Re: Motherboard swap??
Posted by Martin Harrington on Mon, 04 Sep 2006 23:16:55 GMT
View Forum Message <> Reply to Message

This is a multi-part message in MIME format.

```
-----=_NextPart_000_01E2_01C6D0CC.085323D0
Content-Type: text/plain;
charset="iso-8859-1"
Content-Transfer-Encoding: quoted-printable

I've done it many times, but it's a little more difficult if you're = using XP, (unless your using a crack, that is);>p
---=20
```

```
"Brandon" <a@a.com> wrote in message news:44f82c23$1@linux...
 I know the answer to this question or at least I think I do, but
 I am hoping someone will tell me different.
 Is there a way to swap a motherboard with a totally different MB
 and reload all the drivers without wiping the HD clean and starting =
from
 scratch & still have a stable system?
 Thanks,
 --=20
 Brandon
-----= NextPart 000 01E2 01C6D0CC.085323D0
Content-Type: text/html;
charset="iso-8859-1"
Content-Transfer-Encoding: quoted-printable
<!DOCTYPE HTML PUBLIC "-//W3C//DTD HTML 4.0 Transitional//EN">
<HTML><HEAD>
<META http-equiv=3DContent-Type content=3D"text/html; =
charset=3Diso-8859-1">
<META content=3D"MSHTML 6.00.5450.4" name=3DGENERATOR>
<STYLE></STYLE>
</HEAD>
<BODY bgColor=3D#ffffff>
<DIV><FONT size=3D2>I've done it many times, but it's a little more =
difficult if=20
you're using XP, (unless your using a crack, that is) =
:&at;p</FONT><BR>--=20
<BR>Martin Harrington<BR><A=20
href=3D"http://www.lendanear-sound.com">www.lendanear-sound.com</A><BR></=
DIV>
<BLOCKQUOTE dir=3Dltr=20
style=3D"PADDING-RIGHT: 0px; PADDING-LEFT: 5px; MARGIN-LEFT: 5px; =
BORDER-LEFT: #000000 2px solid; MARGIN-RIGHT: 0px">
 <DIV>"Brandon" &lt;<A href=3D"mailto:a@a.com">a@a.com</A>&gt; wrote in =
message=20
 <A href=3D"news:44f82c23$1@linux">news:44f82c23$1@linux</A>...</DIV>
 <DIV><FONT face=3DArial></FONT>&nbsp;</DIV><FONT face=3DArial>
 <DIV>I know the answer to this question or at least I think I do, =
but</DIV>
 <DIV>I am hoping someone will tell me different.</DIV>
 <DIV>Is there a way to swap a motherboard with a totally different =
MB</DIV>
```

```
<DIV>and reload all the drivers without wiping the HD clean and =
starting=20
from</DIV>
  <DIV>scratch & amp; still have a stable system?</DIV>
  <DIV>&nbsp;</DIV>
  <DIV>Thanks,</DIV>
  <DIV>>Thanks,</DIV>
  <DIV><BR>--- <BR>Brandon </FONT></DIV></BLOCKQUOTE></BODY></HTML>
-----=_NextPart_000_01E2_01C6D0CC.085323D0--
```