Subject: Trivial BS you guys probably don't care about.....but..... Posted by Deej [4] on Fri, 16 Feb 2007 04:29:36 GMT View Forum Message <> Reply to Message

I just figured out a relatively (as in , less \$\$\$ than other ways I've found) to digitally integrate an older outboard FX box with digital I/O that will only work at 48kHz max sample rates with a DAW running at 88.2 or 96K.

Subject: Re: Trivial BS you guys probably don't care about....but..... Posted by Deej [4] on Fri, 16 Feb 2007 05:37:53 GMT View Forum Message <> Reply to Message

hehehe!!!!!!! thought you'd never ask.....OK then.....first of all, but 2 x Behringer SRC 2496 boxes from MF for \$129.00 each...then

digital out of DAW at 88.2 to digital in of #1 Behringer SRC 2496> downsample to 44.1 in #1 SRC 2496 and route 44.1 signal to digital in of outboard processor, send digital out of processor at 44.1 to digital input of #2 Behringer SRC 2496 and upsample signal to 88.2, then return upsampled 88.2 signal to DAW running at 88.2.

I have the Behringer boxes here. I haven't tried it yet, but according to what the F'in'M says, this should work. I'll try it after I get a little further along in patching together my new world of native insanity......which now includes two Behringer products.....which I'll probably regret, but the only other box that does this is the RME ADI 8-DD or the RME ADI 8-192, those cost \$800 or 1400.00 each respectively and you have to have two of them. If the Behringers die, I hope it's before 45 days. I have open rack spaces above and below them in case they catch on fire.

If this works, I'll bet I could buy 6 more of these at a discount and I would have all of my old digital signal processors integrated with 88.2 projects for under a grand. Now the question is, WTF would I want to do this when patching analog would probably sound as good or better once all of the SRC stuff was said and done?

Well, I just had to see if I could pull it off and since my Yardstick doesn't have AD/DA converters, the Behringer boxes do and will allow me to patch

it into higher rez projects using their AD/DA's which are surprisingly good when they work.which is why I got the Behringers in the first place..

;0)

"Neil" <IUOIU@OIU.com> wrote in message news:45d535b2\$1@linux...

>
> and that way is?
>
>
> "DJ" <www.aarrrrggghhh!!!.com> wrote:</www.aarrrrggghhh!!!.com>
>>I just figured out a relatively (as in , less \$\$\$ than other ways I've
>>found) to digitally integrate an older outboard FX box with digital I/O
> that
>>will only work at 48kHz max sample rates with a DAW running at 88.2 or
>>96K.
>>
>>
>>
>

Subject: Re: Trivial BS you guys probably don't care about....but..... Posted by Nil on Fri, 16 Feb 2007 05:40:18 GMT View Forum Message <> Reply to Message

and that way is....?

"DJ" <www.aarrrrggghhh!!!.com> wrote:

>I just figured out a relatively (as in , less \$\$\$ than other ways I've >found) to digitally integrate an older outboard FX box with digital I/O that

>will only work at 48kHz max sample rates with a DAW running at 88.2 or 96K.

>

- >
- >

Subject: Re: Trivial BS you guys probably don't care about....but..... Posted by Neil on Fri, 16 Feb 2007 07:54:01 GMT View Forum Message <> Reply to Message

MORE Behringer?

When is your birthday? Because Christmas is too long to wait for me to send you a fire extinguisher.

:)

"DJ" <www.aarrrrggghhh!!!.com> wrote: >hehehe!!!!!!! thought you'd never ask......OK then......first of all,

>but 2 x Behringer SRC 2496 boxes from MF for \$129.00 each...then >

>digital out of DAW at 88.2 to digital in of #1 Behringer SRC 2496>
>downsample to 44.1 in #1 SRC 2496 and route 44.1 signal to digital in of

>outboard processor, send digital out of processor at 44.1 to digital input

>of #2 Behringer SRC 2496 and upsample signal to 88.2, then return upsampled

>88.2 signal to DAW running at 88.2.

>

>I have the Behringer boxes here. I haven't tried it yet, but according to

>what the F'in'M says, this should work. I'll try it after I get a little

>further along in patching together my new world of native >insanity.....which now includes two Behringer products.....which I'll

>probably regret, but the only other box that does this is the RME ADI 8-DD

>or the RME ADI 8-192, those cost \$800 or 1400.00 each respectively and you

>have to have two of them. If the Behringers die, I hope it's before 45

>days. I have open rack spaces above and below them in case they catch on

>fire.

>

>If this works, I'll bet I could buy 6 more of these at a discount and I

>would have all of my old digital signal processors integrated with 88.2

>projects for under a grand. Now the question is, WTF would I want to do this

>when patching analog would probably sound as good or better once all of the

>SRC stuff was said and done?

>

>Well, I just had to see if I could pull it off and since my Yardstick

>doesn't have AD/DA converters, the Behringer boxes do and will allow me to

>patch

>it into higher rez projects using their AD/DA's which are surprisingly good

>when they work.which is why I got the Behringers in the first place..

>

>;0)

```
>
>
>"Neil" <IUOIU@OIU.com> wrote in message news:45d535b2$1@linux...
>>
>> and that way is....?
>>
>>
>> "DJ" <www.aarrrrggghhh!!!.com> wrote:
>>>I just figured out a relatively (as in , less $$$ than other ways I've
>>>found) to digitally integrate an older outboard FX box with digital I/O
>> that
>>>will only work at 48kHz max sample rates with a DAW running at 88.2 or
>>>96K.
>>>
>>>
>>>
>>
>
>
```

Subject: Re: Trivial BS you guys probably don't care about....but..... Posted by rick on Fri, 16 Feb 2007 09:48:44 GMT View Forum Message <> Reply to Message

you can always send him an empty one 4/01/07...

On 16 Feb 2007 17:54:01 +1000, "Neil" <OIUOIU@OIU.com> wrote:

> >MORE Behringer? > >When is your birthday? Because Christmas is too long to wait >for me to send you a fire extinguisher. > >:) > > >"DJ" <www.aarrrrggghhh!!!.com> wrote: >>hehehe!!!!!!! thought you'd never ask......OK then......first of >all. >>but 2 x Behringer SRC 2496 boxes from MF for \$129.00 each...then >> >>digital out of DAW at 88.2 to digital in of #1 Behringer SRC 2496> >>downsample to 44.1 in #1 SRC 2496 and route 44.1 signal to digital in of > >>outboard processor, send digital out of processor at 44.1 to digital input

>

```
>>of #2 Behringer SRC 2496 and upsample signal to 88.2, then return upsampled
>
>>88.2 signal to DAW running at 88.2.
>>
>>I have the Behringer boxes here. I haven't tried it yet, but according to
>
>>what the F'in'M says, this should work. I'll try it after I get a little
>
>>further along in patching together my new world of native
>>insanity......which now includes two Behringer products......which I'll
>
>>probably regret, but the only other box that does this is the RME ADI 8-DD
>
>>or the RME ADI 8-192, those cost $800 or 1400.00 each respectively and you
>
>>have to have two of them. If the Behringers die, I hope it's before 45
>
>>days. I have open rack spaces above and below them in case they catch on
>
>>fire.
>>
>>If this works, I'll bet I could buy 6 more of these at a discount and I
>
>>would have all of my old digital signal processors integrated with 88.2
>
>>projects for under a grand. Now the question is, WTF would I want to do
>this
>>when patching analog would probably sound as good or better once all of
>the
>>SRC stuff was said and done?
>>
>>Well, I just had to see if I could pull it off and since my Yardstick
>>doesn't have AD/DA converters, the Behringer boxes do and will allow me
>to
>>patch
>>it into higher rez projects using their AD/DA's which are surprisingly good
>
>>when they work.which is why I got the Behringers in the first place..
>>
>>;0)
>>
>>
>>"Neil" <IUOIU@OIU.com> wrote in message news:45d535b2$1@linux...
>>>
>>> and that way is .....?
>>>
>>>
```

>>> "DJ" <www.aarrrrggghhh!!!.com> wrote:

>>>I just figured out a relatively (as in , less \$\$\$ than other ways I've >>>found) to digitally integrate an older outboard FX box with digital I/O >>> that

>>>will only work at 48kHz max sample rates with a DAW running at 88.2 or >

>>>>96K.		
>>>>		
>>>>		
>>>>		
>>>		
>>		
>>		

Subject: Re: Trivial BS you guys probably don't care about.....but..... Posted by chuck duffy on Fri, 16 Feb 2007 14:46:32 GMT View Forum Message <> Reply to Message

I figured out the analog way, it wasn't hard, although the cables cost almost 10 dollars each to make :-)

Chuck

"DJ" <www.aarrrrggghhh!!!.com> wrote: >I just figured out a relatively (as in , less \$\$\$ than other ways I've >found) to digitally integrate an older outboard FX box with digital I/O that

>will only work at 48kHz max sample rates with a DAW running at 88.2 or 96K.

>

>

>

Subject: Re: Trivial BS you guys probably don't care about....but..... Posted by Deej [4] on Fri, 16 Feb 2007 15:21:39 GMT View Forum Message <> Reply to Message

heh! yeah! that was what I was going for when I ran across this. One of my processors only has AES I/O and I needed a way to be able to use it digitally at 44.1 or to use it analog at higher sample rates. The Behringer SRC is the only box I could find that I could afford that will allow this.

;0)

"chuck duffy" <c@c.com> wrote in message news:45d5b5b8\$1@linux...

>

> I figured out the analog way, it wasn't hard, although the cables cost

> almost

> 10 dollars each to make :-)

- >
- > Chuck

> "DJ" <www.aarrrrggghhh!!!.com> wrote:

>>I just figured out a relatively (as in , less \$\$\$ than other ways I've >>found) to digitally integrate an older outboard FX box with digital I/O > that

>>will only work at 48kHz max sample rates with a DAW running at 88.2 or >>96K.

>>

>>

>>

>

Subject: Re: Trivial BS you guys probably don't care about....but..... Posted by gene lennon on Sat, 17 Feb 2007 01:53:26 GMT View Forum Message <> Reply to Message

LOL

Gene

"chuck duffy" <c@c.com> wrote:

>

>I figured out the analog way, it wasn't hard, although the cables cost almost >10 dollars each to make :-)

>

>Chuck

>"DJ" <www.aarrrrggghhh!!!.com> wrote:

>>I just figured out a relatively (as in , less \$\$\$ than other ways I've

>>found) to digitally integrate an older outboard FX box with digital I/O >that

>>will only work at 48kHz max sample rates with a DAW running at 88.2 or 96K.

>>

>>

>>

>